

PLC3G823014 Information



For Reference Only

Part Number PLC3G823014 Manufacturer ITT Cannon, LLC

Category Connectors, Interconnects Circular Connectors

Description CONN RCPT FMALE 14POS GOLD SLDR

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PLC3G823014 Specifications

Manufacturer Part Number PLC3G823014 Manufacturer ITT Cannon, LLC Category Connectors, Interconnects Package - Series PL Connector Type Receptacle, Female Sockets Number of Positions 14 Shell Size - Insert - Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Latch Lock, Push-Pull Orientation 0° Ingress Protection IP50 - Dust Protected Shell Material, Finish Polysulfone (PSU) Contact Finish Gold Features Strain Relief Nut Voltage - Rated - Current Rating 2A		
CategoryConnectors, InterconnectsPackage-SeriesPLConnector TypeReceptacle, Female SocketsNumber of Positions14Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeLatch Lock, Push-PullOrientation0°Ingress ProtectionIP50 - Dust ProtectedShell Material, FinishPolysulfone (PSU)Contact FinishGoldFeaturesStrain Relief NutVoltage - Rated-Current Rating2A	Manufacturer Part Number	PLC3G823014
Package-SeriesPLConnector TypeReceptacle, Female SocketsNumber of Positions14Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeLatch Lock, Push-PullOrientation0°Ingress ProtectionIP50 - Dust ProtectedShell Material, FinishPolysulfone (PSU)Contact FinishGoldFeaturesStrain Relief NutVoltage - Rated-Current Rating2A	Manufacturer	ITT Cannon, LLC
Package-SeriesPLConnector TypeReceptacle, Female SocketsNumber of Positions14Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeLatch Lock, Push-PullOrientation0°Ingress ProtectionIP50 - Dust ProtectedShell Material, FinishPolysulfone (PSU)Contact FinishGoldFeaturesStrain Relief NutVoltage - Rated-Current Rating2A	Category	Connectors, Interconnects
SeriesPLConnector TypeReceptacle, Female SocketsNumber of Positions14Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeLatch Lock, Push-PullOrientation0°Ingress ProtectionIP50 - Dust ProtectedShell Material, FinishPolysulfone (PSU)Contact FinishGoldFeaturesStrain Relief NutVoltage - Rated-Current Rating2A		Circular Connectors
Connector Type Receptacle, Female Sockets Number of Positions 14 Shell Size - Insert - Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Latch Lock, Push-Pull Orientation 0° Ingress Protection IP50 - Dust Protected Shell Material, Finish Polysulfone (PSU) Contact Finish Gold Features Strain Relief Nut Voltage - Rated - Current Rating 2A	Package	-
Number of Positions14Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeLatch Lock, Push-PullOrientation0°Ingress ProtectionIP50 - Dust ProtectedShell Material, FinishPolysulfone (PSU)Contact FinishGoldFeaturesStrain Relief NutVoltage - Rated-Current Rating2A	Series	PL
Shell Size - Insert Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Latch Lock, Push-Pull Orientation 0° Ingress Protection IP50 - Dust Protected Shell Material, Finish Polysulfone (PSU) Contact Finish Gold Features Strain Relief Nut Voltage - Rated Current Rating 2A	Connector Type	Receptacle, Female Sockets
Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Latch Lock, Push-Pull Orientation 0° Ingress Protection IP50 - Dust Protected Shell Material, Finish Polysulfone (PSU) Contact Finish Gold Features Strain Relief Nut Voltage - Rated - Current Rating 2A	Number of Positions	14
Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeLatch Lock, Push-PullOrientation0°Ingress ProtectionIP50 - Dust ProtectedShell Material, FinishPolysulfone (PSU)Contact FinishGoldFeaturesStrain Relief NutVoltage - Rated-Current Rating2A	Shell Size - Insert	-
Termination Solder Cup Fastening Type Latch Lock, Push-Pull Orientation 0° Ingress Protection IP50 - Dust Protected Shell Material, Finish Polysulfone (PSU) Contact Finish Gold Features Strain Relief Nut Voltage - Rated - Current Rating 2A	Shell Size, MIL	-
Fastening Type Crientation O° Ingress Protection Ingress Protection Shell Material, Finish Polysulfone (PSU) Contact Finish Gold Features Strain Relief Nut Voltage - Rated Current Rating Latch Lock, Push-Pull O° IP50 - Dust Protected Folysulfone (PSU) Contact Finish Gold Strain Relief Nut - Current Rating	Mounting Type	Free Hanging (In-Line)
Orientation 0° Ingress Protection IP50 - Dust Protected Shell Material, Finish Polysulfone (PSU) Contact Finish Gold Features Strain Relief Nut Voltage - Rated - Current Rating 2A	Termination	Solder Cup
Ingress Protection IP50 - Dust Protected Shell Material, Finish Polysulfone (PSU) Contact Finish Gold Features Strain Relief Nut Voltage - Rated - Current Rating 2A	Fastening Type	Latch Lock, Push-Pull
Shell Material, Finish Contact Finish Gold Features Strain Relief Nut Voltage - Rated Current Rating Polysulfone (PSU) Gold Strain Relief Nut - 2A	Orientation	0°
Contact Finish Gold Features Strain Relief Nut Voltage - Rated Current Rating 2A	Ingress Protection	IP50 - Dust Protected
Features Strain Relief Nut Voltage - Rated - Current Rating 2A	Shell Material, Finish	Polysulfone (PSU)
Voltage - Rated - Current Rating 2A	Contact Finish	Gold
Current Rating 2A	Features	Strain Relief Nut
	Voltage - Rated	-
	Current Rating	2A
Report errors?		Report errors?

PLC3G823014 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PLC3G823014 Payment Methods





















PLC3G823014 Shipping Methods













If you have any question about PLC3G823014, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com