



PLED120W-171-C0700 Information

Part Number PLED120W-171-C0700 Manufacturer Thomas Research Products

Category Power Supplies - External/Internal (Off-Board)

LED Drivers

Description LED DRIVR CC AC/DC 57-171V 700MA

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PLED120W-171-C0700 Specifications

Manufacturer Thomas Research Products Category Power Supplies - External/Internal (Off-Board) LED Drivers Package - Series PLED120W Type Constant Current Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 100VAC Voltage - Input (Max) 277VAC Voltage - Output 57 ~ 171 V Current - Output (Max) 700mA Power (Watts) 120W Voltage - Isolation - Dimming - Features OCP, OVP, SCP Ratings IP66, NEMA 6 Operating Temperature - Efficiency 91% Termination Style Wire Leads		
Power Supplies - External/Internal (Off-Board)	Manufacturer Part Number	PLED120W-171-C0700
LED Drivers Package - Series PLED120W Type Constant Current Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 100VAC Voltage - Input (Max) 277VAC Voltage - Output (Max) 700mA Power (Watts) 120W Voltage - Isolation - Dimming - Features OCP, OVP, SCP Ratings IP66, NEMA 6 Operating Temperature - Efficiency 91% Termination Style Wire Leads Size / Dimension 7.60" L x 2.33" W x 1.47" H (193.0mm x 59.2mm x 37.3mm)	Manufacturer	Thomas Research Products
Package - Series PLED120W Type Constant Current Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 100VAC Voltage - Input (Max) 277VAC Voltage - Output 57 ~ 171 V Current - Output (Max) 700mA Power (Watts) 120W Voltage - Isolation - Dimming - Features OCP, OVP, SCP Ratings IP66, NEMA 6 Operating Temperature - Efficiency 91% Termination Style Wire Leads Size / Dimension 7.60" L x 2.33" W x 1.47" H (193.0mm x 59.2mm x 37.3mm)	Category	Power Supplies - External/Internal (Off-Board)
Series PLED120W Type Constant Current Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 100VAC Voltage - Input (Max) 277VAC Voltage - Output 57 ~ 171 V Current - Output (Max) 700mA Power (Watts) 120W Voltage - Isolation - Dimming - Features OCP, OVP, SCP Ratings IP66, NEMA 6 Operating Temperature - Efficiency 91% Termination Style Wire Leads Size / Dimension 7.60" L x 2.33" W x 1.47" H (193.0mm x 59.2mm x 37.3mm)		LED Drivers
Type Constant Current Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 100VAC Voltage - Input (Max) 277VAC Voltage - Output 57 ~ 171 V Current - Output (Max) 700mA Power (Watts) 120W Voltage - Isolation - Dimming - Features OCP, OVP, SCP Ratings IP66, NEMA 6 Operating Temperature - Efficiency 91% Termination Style Wire Leads Size / Dimension 7.60" L x 2.33" W x 1.47" H (193.0mm x 59.2mm x 37.3mm)	Package	-
AC DC Converter	Series	PLED120W
Number of Outputs 1 Voltage - Input (Min) 100VAC Voltage - Input (Max) 277VAC Voltage - Output 57 ~ 171 V Current - Output (Max) 700mA Power (Watts) 120W Voltage - Isolation - Dimming - Features OCP, OVP, SCP Ratings IP66, NEMA 6 Operating Temperature - Efficiency 91% Termination Style Wire Leads Size / Dimension 7.60" L x 2.33" W x 1.47" H (193.0mm x 59.2mm x 37.3mm)	Type	Constant Current
Voltage - Input (Min) 100VAC Voltage - Input (Max) 277VAC Voltage - Output 57 ~ 171 V Current - Output (Max) 700mA Power (Watts) 120W Voltage - Isolation - Dimming - Features OCP, OVP, SCP Ratings IP66, NEMA 6 Operating Temperature - Efficiency 91% Termination Style Wire Leads Size / Dimension 7.60" L x 2.33" W x 1.47" H (193.0mm x 59.2mm x 37.3mm)	Topology	AC DC Converter
Voltage - Input (Max) 277VAC Voltage - Output 57 ~ 171 V Current - Output (Max) 700mA Power (Watts) 120W Voltage - Isolation - Dimming - Features OCP, OVP, SCP Ratings IP66, NEMA 6 Operating Temperature - Efficiency 91% Termination Style Wire Leads Size / Dimension 7.60" L x 2.33" W x 1.47" H (193.0mm x 59.2mm x 37.3mm)	Number of Outputs	1
Voltage - Output 57 ~ 171 V Current - Output (Max) 700mA Power (Watts) 120W Voltage - Isolation - Dimming - Features OCP, OVP, SCP Ratings IP66, NEMA 6 Operating Temperature - Efficiency 91% Termination Style Wire Leads Size / Dimension 7.60" L x 2.33" W x 1.47" H (193.0mm x 59.2mm x 37.3mm)	Voltage - Input (Min)	100VAC
Current - Output (Max) Power (Watts) 120W Voltage - Isolation - Dimming - Features OCP, OVP, SCP Ratings IP66, NEMA 6 Operating Temperature Efficiency 91% Termination Style Size / Dimension 7.60" L x 2.33" W x 1.47" H (193.0mm x 59.2mm x 37.3mm)	Voltage - Input (Max)	277VAC
Power (Watts) 120W Voltage - Isolation Dimming - Features OCP, OVP, SCP Ratings IP66, NEMA 6 Operating Temperature Efficiency 91% Termination Style Size / Dimension 120W - 120W	Voltage - Output	57 ~ 171 V
Voltage - Isolation Dimming - Features OCP, OVP, SCP Ratings IP66, NEMA 6 Operating Temperature - Efficiency 91% Termination Style Size / Dimension - Voltage - Isolation - UR OCP, OVP, SCP IP66, NEMA 6 Wire Leads Vire Leads	Current - Output (Max)	700mA
Dimming Features OCP, OVP, SCP Ratings IP66, NEMA 6 Operating Temperature	Power (Watts)	120W
Features OCP, OVP, SCP Ratings IP66, NEMA 6 Operating Temperature - Efficiency 91% Termination Style Wire Leads Size / Dimension 7.60" L x 2.33" W x 1.47" H (193.0mm x 59.2mm x 37.3mm)	Voltage - Isolation	-
Ratings IP66, NEMA 6 Operating Temperature - Efficiency 91% Termination Style Wire Leads Size / Dimension 7.60" L x 2.33" W x 1.47" H (193.0mm x 59.2mm x 37.3mm)	Dimming	-
Operating Temperature - Efficiency 91% Termination Style Wire Leads Size / Dimension 7.60" L x 2.33" W x 1.47" H (193.0mm x 59.2mm x 37.3mm)	Features	OCP, OVP, SCP
Efficiency 91% Termination Style Wire Leads Size / Dimension 7.60" L x 2.33" W x 1.47" H (193.0mm x 59.2mm x 37.3mm)	Ratings	IP66, NEMA 6
Termination Style Wire Leads Size / Dimension 7.60" L x 2.33" W x 1.47" H (193.0mm x 59.2mm x 37.3mm)	Operating Temperature	-
Size / Dimension 7.60" L x 2.33" W x 1.47" H (193.0mm x 59.2mm x 37.3mm)	Efficiency	91%
	Termination Style	Wire Leads
Report errors?	Size / Dimension	7.60" L x 2.33" W x 1.47" H (193.0mm x 59.2mm x 37.3mm)
		Report errors?

PLED120W-171-C0700 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PLED120W-171-C0700 Payment Methods

































If you have any question about PLED120W-171-C0700, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com