

## PLED96W-046-C2100-HV

## PLED96W-046-C2100-HV Information



For Reference Only

**Part Number** PLED96W-046-C2100-HV **Manufacturer** Thomas Research Products

Category Power Supplies - External/Internal (Off-Board)

**LED Drivers** 

**Description** LED DRIVER CC AC/DC 16-46V 2.1A

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# PLED96W-046-C2100-HV Specifications

Category         Power Supplies - External/Internal (Off-Board)           LED Drivers           Package         -           Series         PLED96W-HV           Type         Constant Current           Topology         AC DC Converter           Number of Outputs         1           Voltage - Input (Min)         277VAC           Voltage - Input (Max)         480VAC           Voltage - Output         16 ~ 46 V           Current - Output (Max)         2.1A           Power (Watts)         96W           Voltage - Isolation         -           Dimming         -           Features         OCP, OVP, SCP           Ratings         IP66, NEMA 6           Operating Temperature         -			
Category         Power Supplies - External/Internal (Off-Board)           LED Drivers           Package         -           Series         PLED96W-HV           Type         Constant Current           Topology         AC DC Converter           Number of Outputs         1           Voltage - Input (Min)         277VAC           Voltage - Input (Max)         480VAC           Voltage - Output         16 ~ 46 V           Current - Output (Max)         2.1A           Power (Watts)         96W           Voltage - Isolation         -           Dimming         -           Features         OCP, OVP, SCP           Ratings         IP66, NEMA 6           Operating Temperature         -           Efficiency         85%           Termination Style         Wire Leads           Size / Dimension         8.54" L x 2.33" W x 1.47" H (217.0mm x 59.2mm x 37.3mm)	Manufacturer Part Number	PLED96W-046-C2100-HV	
LED Drivers           Package         -           Series         PLED96W-HV           Type         Constant Current           Topology         AC DC Converter           Number of Outputs         1           Voltage - Input (Min)         277VAC           Voltage - Input (Max)         480VAC           Voltage - Output         16 ~ 46 V           Current - Output (Max)         2.1A           Power (Watts)         96W           Voltage - Isolation         -           Dimming         -           Features         OCP, OVP, SCP           Ratings         IP66, NEMA 6           Operating Temperature         -           Efficiency         85%           Termination Style         Wire Leads           Size / Dimension         8.54" L x 2.33" W x 1.47" H (217.0mm x 59.2mm x 37.3mm)	Manufacturer	Thomas Research Products	
Package         -           Series         PLED96W-HV           Type         Constant Current           Topology         AC DC Converter           Number of Outputs         1           Voltage - Input (Min)         277VAC           Voltage - Input (Max)         480VAC           Voltage - Output         16 ~ 46 V           Current - Output (Max)         2.1A           Power (Watts)         96W           Voltage - Isolation         -           Dimming         -           Features         OCP, OVP, SCP           Ratings         IP66, NEMA 6           Operating Temperature         -           Efficiency         85%           Termination Style         Wire Leads           Size / Dimension         8.54" L x 2.33" W x 1.47" H (217.0mm x 59.2mm x 37.3mm)	Category	Power Supplies - External/Internal (Off-Board)	
Series         PLED96W-HV           Type         Constant Current           Topology         AC DC Converter           Number of Outputs         1           Voltage - Input (Min)         277VAC           Voltage - Input (Max)         480VAC           Voltage - Output         16 ~ 46 V           Current - Output (Max)         2.1A           Power (Watts)         96W           Voltage - Isolation         -           Dimming         -           Features         OCP, OVP, SCP           Ratings         IP66, NEMA 6           Operating Temperature         -           Efficiency         85%           Termination Style         Wire Leads           Size / Dimension         8.54" L x 2.33" W x 1.47" H (217.0mm x 59.2mm x 37.3mm)		LED Drivers	
Type         Constant Current           Topology         AC DC Converter           Number of Outputs         1           Voltage - Input (Min)         277VAC           Voltage - Input (Max)         480VAC           Voltage - Output         16 ~ 46 V           Current - Output (Max)         2.1A           Power (Watts)         96W           Voltage - Isolation         -           Dimming         -           Features         OCP, OVP, SCP           Ratings         IP66, NEMA 6           Operating Temperature         -           Efficiency         85%           Termination Style         Wire Leads           Size / Dimension         8.54" L x 2.33" W x 1.47" H (217.0mm x 59.2mm x 37.3mm)	Package	-	
Topology       AC DC Converter         Number of Outputs       1         Voltage - Input (Min)       277V AC         Voltage - Input (Max)       480V AC         Voltage - Output       16 ~ 46 V         Current - Output (Max)       2.1A         Power (Watts)       96W         Voltage - Isolation       -         Dimming       -         Features       OCP, OVP, SCP         Ratings       IP66, NEMA 6         Operating Temperature       -         Efficiency       85%         Termination Style       Wire Leads         Size / Dimension       8.54" L x 2.33" W x 1.47" H (217.0mm x 59.2mm x 37.3mm)	Series	PLED96W-HV	
Number of Outputs       1         Voltage - Input (Min)       277VAC         Voltage - Input (Max)       480VAC         Voltage - Output       16 ~ 46 V         Current - Output (Max)       2.1A         Power (Watts)       96W         Voltage - Isolation       -         Dimming       -         Features       OCP, OVP, SCP         Ratings       IP66, NEMA 6         Operating Temperature       -         Efficiency       85%         Termination Style       Wire Leads         Size / Dimension       8.54" L x 2.33" W x 1.47" H (217.0mm x 59.2mm x 37.3mm)	Туре	Constant Current	
Voltage - Input (Min)       277VAC         Voltage - Input (Max)       480VAC         Voltage - Output       16 ~ 46 V         Current - Output (Max)       2.1A         Power (Watts)       96W         Voltage - Isolation       -         Dimming       -         Features       OCP, OVP, SCP         Ratings       IP66, NEMA 6         Operating Temperature       -         Efficiency       85%         Termination Style       Wire Leads         Size / Dimension       8.54" L x 2.33" W x 1.47" H (217.0mm x 59.2mm x 37.3mm)	Topology	AC DC Converter	
Voltage - Input (Max)       480VAC         Voltage - Output       16 ~ 46 V         Current - Output (Max)       2.1A         Power (Watts)       96W         Voltage - Isolation       -         Dimming       -         Features       OCP, OVP, SCP         Ratings       IP66, NEMA 6         Operating Temperature       -         Efficiency       85%         Termination Style       Wire Leads         Size / Dimension       8.54" L x 2.33" W x 1.47" H (217.0mm x 59.2mm x 37.3mm)	Number of Outputs	1	
Voltage - Output (Max) 2.1A  Power (Watts) 96W  Voltage - Isolation - Dimming - Features OCP, OVP, SCP  Ratings IP66, NEMA 6  Operating Temperature - Efficiency 85%  Termination Style Wire Leads  Size / Dimension 8.54" L x 2.33" W x 1.47" H (217.0mm x 59.2mm x 37.3mm)	Voltage - Input (Min)	277VAC	
Current - Output (Max)  Power (Watts)  96W  Voltage - Isolation  - Dimming  - Features  OCP, OVP, SCP  Ratings  IP66, NEMA 6  Operating Temperature  Efficiency  85%  Termination Style  Size / Dimension  2.1A  96W  OCP, OVP  SCP  - L x 2.33" W x 1.47" H (217.0mm x 59.2mm x 37.3mm)	Voltage - Input (Max)	480VAC	
Power (Watts) 96W  Voltage - Isolation -  Dimming -  Features OCP, OVP, SCP  Ratings IP66, NEMA 6  Operating Temperature -  Efficiency 85%  Termination Style Wire Leads  Size / Dimension 8.54" L x 2.33" W x 1.47" H (217.0mm x 59.2mm x 37.3mm)	Voltage - Output	16 ~ 46 V	
Voltage - Isolation  Dimming  - Features  OCP, OVP, SCP  Ratings  IP66, NEMA 6  Operating Temperature  - Efficiency  85%  Termination Style  Wire Leads  Size / Dimension  - Size / Dimension  Size / Dimension  - Size / Size / Size / Dimension  - Size / Si	Current - Output (Max)	2.1A	
Dimming Features OCP, OVP, SCP Ratings IP66, NEMA 6 Operating Temperature	Power (Watts)	96W	
Features OCP, OVP, SCP Ratings IP66, NEMA 6 Operating Temperature - Efficiency 85% Termination Style Wire Leads Size / Dimension 8.54" L x 2.33" W x 1.47" H (217.0mm x 59.2mm x 37.3mm)	Voltage - Isolation	-	
Ratings IP66, NEMA 6  Operating Temperature -  Efficiency 85%  Termination Style Wire Leads  Size / Dimension 8.54" L x 2.33" W x 1.47" H (217.0mm x 59.2mm x 37.3mm)	Dimming	-	
Operating Temperature -  Efficiency 85%  Termination Style Wire Leads  Size / Dimension 8.54" L x 2.33" W x 1.47" H (217.0mm x 59.2mm x 37.3mm)	Features	OCP, OVP, SCP	
Efficiency 85% Termination Style Wire Leads Size / Dimension 8.54" L x 2.33" W x 1.47" H (217.0mm x 59.2mm x 37.3mm)	Ratings	IP66, NEMA 6	
Termination Style Wire Leads Size / Dimension 8.54" L x 2.33" W x 1.47" H (217.0mm x 59.2mm x 37.3mm)	Operating Temperature	-	
Size / Dimension 8.54" L x 2.33" W x 1.47" H (217.0mm x 59.2mm x 37.3mm)	Efficiency	85%	
	Termination Style	Wire Leads	
Report errors?	Size / Dimension	8.54" L x 2.33" W x 1.47" H (217.0mm x 59.2mm x 37.3mm)	
			Report errors?

### PLED96W-046-C2100-HV Guarantees



### **Ouality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### PLED96W-046-C2100-HV Payment Methods





















### PLED96W-046-C2100-HV Shipping Methods













If you have any question about PLED96W-046-C2100-HV, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com