

### PLV-050S024 Information



For Reference Only

Part Number PLV-050S024

Manufacturer Qualtek

Category Power Supplies - External/Internal (Off-Board)

**LED Drivers** 

**Description** LED DRIVER CV AC/DC 24V 2.08A

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# PLV-050S024 Specifications

Manufacturer Part Number         PLV-0508024           Manufacturer         Qualtek           Category         Power Supplies - External/Internal (Off-Board)           LED Drivers           Package         -           Series         PLV-050           Type         Constant Voltage           Topology         AC DC Converter           Number of Outputs         1           Voltage - Input (Min)         90VAC           Voltage - Input (Max)         305VAC           Voltage - Output         24V           Current - Output (Max)         2.08A           Power (Watts)         50W           Voltage - Isolation         2kV (2000V)           Dimming         -           Features         OCP, OTP, OVP, SCP           Ratings         IP67           Operating Temperature         -35°C ~ 70°C           Efficiency         84%           Termination Style         Wire Leads           Size / Dimension         7.83" L x 1.67" W x 1.34" H (199.0mm x 42.5mm x 34.0mm)		
Category         Power Supplies - External/Internal (Off-Board)           LED Drivers           Package         -           Series         PLV-050           Type         Constant Voltage           Topology         AC DC Converter           Number of Outputs         1           Voltage - Input (Min)         90VAC           Voltage - Input (Max)         305VAC           Voltage - Output         24V           Current - Output (Max)         2.08A           Power (Watts)         50W           Voltage - Isolation         2kV (2000V)           Dimming         -           Features         OCP, OTP, OVP, SCP           Ratings         IP67           Operating Temperature         -35°C ~ 70°C           Efficiency         84%           Termination Style         Wire Leads           Size / Dimension         7.83" L x 1.67" W x 1.34" H (199.0mm x 42.5mm x 34.0mm)	Manufacturer Part Number	PLV-050S024
Package         -           Series         PLV-050           Type         Constant Voltage           Topology         AC DC Converter           Number of Outputs         1           Voltage - Input (Min)         90VAC           Voltage - Input (Max)         305VAC           Voltage - Output         24V           Current - Output (Max)         2.08A           Power (Watts)         50W           Voltage - Isolation         2kV (2000V)           Dimming         -           Features         OCP, OTP, OVP, SCP           Ratings         IP67           Operating Temperature         -35°C ~ 70°C           Efficiency         84%           Termination Style         Wire Leads           Size / Dimension         7.83" L x 1.67" W x 1.34" H (199.0mm x 42.5mm x 34.0mm)	Manufacturer	Qualtek
Package         -           Series         PLV-050           Type         Constant Voltage           Topology         AC DC Converter           Number of Outputs         1           Voltage - Input (Min)         90VAC           Voltage - Input (Max)         305VAC           Voltage - Output         24V           Current - Output (Max)         2.08A           Power (Watts)         50W           Voltage - Isolation         2kV (2000V)           Dimming         -           Features         OCP, OTP, OVP, SCP           Ratings         IP67           Operating Temperature         -35°C ~ 70°C           Efficiency         84%           Termination Style         Wire Leads           Size / Dimension         7.83" L x 1.67" W x 1.34" H (199.0mm x 42.5mm x 34.0mm)	Category	Power Supplies - External/Internal (Off-Board)
Series         PLV-050           Type         Constant Voltage           Topology         AC DC Converter           Number of Outputs         1           Voltage - Input (Min)         90VAC           Voltage - Input (Max)         305VAC           Voltage - Output         24V           Current - Output (Max)         2.08A           Power (Watts)         50W           Voltage - Isolation         2kV (2000V)           Dimming         -           Features         OCP, OTP, OVP, SCP           Ratings         IP67           Operating Temperature         -35°C ~ 70°C           Efficiency         84%           Termination Style         Wire Leads           Size / Dimension         7.83" L x 1.67" W x 1.34" H (199.0mm x 42.5mm x 34.0mm)		LED Drivers
Type         Constant Voltage           Topology         AC DC Converter           Number of Outputs         1           Voltage - Input (Min)         90VAC           Voltage - Input (Max)         305VAC           Voltage - Output         24V           Current - Output (Max)         2.08A           Power (Watts)         50W           Voltage - Isolation         2kV (2000V)           Dimming         -           Features         OCP, OTP, OVP, SCP           Ratings         IP67           Operating Temperature         -35°C ~ 70°C           Efficiency         84%           Termination Style         Wire Leads           Size / Dimension         7.83" L x 1.67" W x 1.34" H (199.0mm x 42.5mm x 34.0mm)	Package	-
Topology         AC DC Converter           Number of Outputs         1           Voltage - Input (Min)         90VAC           Voltage - Input (Max)         305VAC           Voltage - Output         24V           Current - Output (Max)         2.08A           Power (Watts)         50W           Voltage - Isolation         2kV (2000V)           Dimming         -           Features         OCP, OTP, OVP, SCP           Ratings         IP67           Operating Temperature         -35°C ~ 70°C           Efficiency         84%           Termination Style         Wire Leads           Size / Dimension         7.83" L x 1.67" W x 1.34" H (199.0mm x 42.5mm x 34.0mm)	Series	PLV-050
Number of Outputs       1         Voltage - Input (Min)       90VAC         Voltage - Input (Max)       305VAC         Voltage - Output       24V         Current - Output (Max)       2.08A         Power (Watts)       50W         Voltage - Isolation       2kV (2000V)         Dimming       -         Features       OCP, OTP, OVP, SCP         Ratings       IP67         Operating Temperature       -35°C ~ 70°C         Efficiency       84%         Termination Style       Wire Leads         Size / Dimension       7.83" L x 1.67" W x 1.34" H (199.0mm x 42.5mm x 34.0mm)	Type	Constant Voltage
Voltage - Input (Min)         90VAC           Voltage - Input (Max)         305VAC           Voltage - Output         24V           Current - Output (Max)         2.08A           Power (Watts)         50W           Voltage - Isolation         2kV (2000V)           Dimming         -           Features         OCP, OTP, OVP, SCP           Ratings         IP67           Operating Temperature         -35°C ~ 70°C           Efficiency         84%           Termination Style         Wire Leads           Size / Dimension         7.83" L x 1.67" W x 1.34" H (199.0mm x 42.5mm x 34.0mm)	Topology	AC DC Converter
Voltage - Input (Max)         305VAC           Voltage - Output         24V           Current - Output (Max)         2.08A           Power (Watts)         50W           Voltage - Isolation         2kV (2000V)           Dimming         -           Features         OCP, OTP, OVP, SCP           Ratings         IP67           Operating Temperature         -35°C ~ 70°C           Efficiency         84%           Termination Style         Wire Leads           Size / Dimension         7.83" L x 1.67" W x 1.34" H (199.0mm x 42.5mm x 34.0mm)	Number of Outputs	1
Voltage - Output24VCurrent - Output (Max)2.08APower (Watts)50WVoltage - Isolation2kV (2000V)Dimming-FeaturesOCP, OTP, OVP, SCPRatingsIP67Operating Temperature-35°C ~ 70°CEfficiency84%Termination StyleWire LeadsSize / Dimension7.83" L x 1.67" W x 1.34" H (199.0mm x 42.5mm x 34.0mm)	Voltage - Input (Min)	90VAC
Current - Output (Max)  Power (Watts)  50W  Voltage - Isolation  2kV (2000V)  Dimming  - Features  OCP, OTP, OVP, SCP  Ratings  IP67  Operating Temperature  -35°C ~ 70°C  Efficiency  84%  Termination Style  Wire Leads  Size / Dimension  2.08A  50W  Composition  2kV (2000V)  COP, OTP, OVP, SCP  84%  Wire Leads  7.83" L x 1.67" W x 1.34" H (199.0mm x 42.5mm x 34.0mm)	Voltage - Input (Max)	305VAC
Power (Watts) 50W  Voltage - Isolation 2kV (2000V)  Dimming -  Features OCP, OTP, OVP, SCP  Ratings IP67  Operating Temperature -35°C ~ 70°C  Efficiency 84%  Termination Style Wire Leads  Size / Dimension 7.83" L x 1.67" W x 1.34" H (199.0mm x 42.5mm x 34.0mm)	Voltage - Output	24V
Voltage - Isolation 2kV (2000V)  Dimming -  Features OCP, OTP, OVP, SCP  Ratings IP67  Operating Temperature -35°C ~ 70°C  Efficiency 84%  Termination Style Wire Leads  Size / Dimension 7.83" L x 1.67" W x 1.34" H (199.0mm x 42.5mm x 34.0mm)	Current - Output (Max)	2.08A
Dimming  Features OCP, OTP, OVP, SCP  Ratings IP67 Operating Temperature -35°C ~ 70°C  Efficiency 84%  Termination Style Wire Leads Size / Dimension 7.83" L x 1.67" W x 1.34" H (199.0mm x 42.5mm x 34.0mm)	Power (Watts)	50W
Features OCP, OTP, OVP, SCP  Ratings IP67 Operating Temperature -35°C ~ 70°C  Efficiency 84% Termination Style Wire Leads Size / Dimension 7.83" L x 1.67" W x 1.34" H (199.0mm x 42.5mm x 34.0mm)	Voltage - Isolation	2kV (2000V)
Ratings IP67 Operating Temperature -35°C ~ 70°C  Efficiency 84% Termination Style Wire Leads Size / Dimension 7.83" L x 1.67" W x 1.34" H (199.0mm x 42.5mm x 34.0mm)	Dimming	-
Operating Temperature -35°C ~ 70°C  Efficiency 84%  Termination Style Wire Leads  Size / Dimension 7.83" L x 1.67" W x 1.34" H (199.0mm x 42.5mm x 34.0mm)	Features	OCP, OTP, OVP, SCP
Efficiency 84%  Termination Style Wire Leads  Size / Dimension 7.83" L x 1.67" W x 1.34" H (199.0mm x 42.5mm x 34.0mm)	Ratings	IP67
Termination Style Wire Leads Size / Dimension 7.83" L x 1.67" W x 1.34" H (199.0mm x 42.5mm x 34.0mm)	Operating Temperature	-35°C ~ 70°C
Size / Dimension 7.83" L x 1.67" W x 1.34" H (199.0mm x 42.5mm x 34.0mm)	Efficiency	84%
	Termination Style	Wire Leads
Report errors?	Size / Dimension	7.83" L x 1.67" W x 1.34" H (199.0mm x 42.5mm x 34.0mm)
		Report errors

#### PLV-050S024 Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### PLV-050S024 Payment Methods



















## PLV-050S024 Shipping Methods













If you have any question about PLV-050S024, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com