

PM12565S-7R0 Information

Heisener.com

Part Number PM12565S-7R0 Manufacturer Bourns Inc.

Category Inductors, Coils, Chokes

Fixed Inductors

Description FIXED IND 7UH 5A 21 MOHM SMD

Package Nonstandard

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PM12565S-7R0 Specifications

Manufacturer Bourns Inc. Category Inductors, Coils, Chokes Fixed Inductors Package Nonstandard Series PM12565S Type Wirewound Material - Core Ferrite Inductance 7μH Tolerance ±30% Current Rating 5A Current - Saturation 5.7A Shielding Shielded DC Resistance (DCR) 21 mOhm Max Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature -20°C ~ 105°C Frequency - Test 1kHz Features - Mounting Type Surface Mount Package / Case Nonstandard	Manufacturer Part Number	PM12565S-7R0
Fixed Inductors Package Nonstandard Series PM12565S Type Wirewound Material - Core Ferrite Inductance 7μH Tolerance ±30% Current Rating 5A Current - Saturation 5.7A Shielding Shielded DC Resistance (DCR) 21 mOhm Max Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature -20°C ~ 105°C Frequency - Test IkHz Features - Mounting Type Surface Mount Package / Case Nonstandard	Manufacturer	Bourns Inc.
PackageNonstandardSeriesPM12565STypeWirewoundMaterial - CoreFerriteInductance7μHTolerance±30%Current Rating5ACurrent - Saturation5.7AShieldingShieldedDC Resistance (DCR)21 mOhm MaxQ @ Freq-Frequency - Self Resonant-Ratings-Operating Temperature-20°C ~ 105°CFrequency - Test1kHzFeatures-Mounting TypeSurface MountPackage / CaseNonstandard	Category	Inductors, Coils, Chokes
Series PM12565S Type Wirewound Material - Core Ferrite Inductance 7μH Tolerance ±30% Current Rating 5A Current - Saturation 5.7A Shielding Shielded DC Resistance (DCR) 21 mOhm Max Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature -20°C ~ 105°C Frequency - Test 1kHz Features - Mounting Type Surface Mount Package / Case Nonstandard		Fixed Inductors
Type Wirewound Material - Core Ferrite Inductance 7μH Tolerance ±30% Current Rating 5A Current - Saturation 5.7A Shielding Shielded DC Resistance (DCR) 21 mOhm Max Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature -20°C ~ 105°C Frequency - Test 1kHz Features - Mounting Type Surface Mount Package / Case Nonstandard	Package	Nonstandard
Material - Core Ferrite Inductance 7μH Tolerance ±30% Current Rating 5A Current - Saturation 5.7A Shielding Shielded DC Resistance (DCR) 21 mOhm Max Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature -20°C ~ 105°C Frequency - Test 1kHz Features - Mounting Type Surface Mount Package / Case Nonstandard	Series	PM12565S
Inductance 7μH Tolerance ±30% Current Rating 5A Current - Saturation 5.7A Shielding Shielded DC Resistance (DCR) 21 mOhm Max Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature -20°C ~ 105°C Frequency - Test 1kHz Features - Mounting Type Surface Mount Package / Case Nonstandard	Туре	Wirewound
Tolerance ±30% Current Rating 5A Current - Saturation 5.7A Shielding Shielded DC Resistance (DCR) 21 mOhm Max Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature -20°C ~ 105°C Frequency - Test 1kHz Features - Mounting Type Surface Mount Package / Case Nonstandard	Material - Core	Ferrite
Current Rating 5A Current - Saturation 5.7A Shielding Shielded DC Resistance (DCR) 21 mOhm Max Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature -20°C ~ 105°C Frequency - Test 1kHz Features - Mounting Type Surface Mount Package / Case Nonstandard	Inductance	7μΗ
Current - Saturation 5.7A Shielding Shielded DC Resistance (DCR) 21 mOhm Max Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature -20°C ~ 105°C Frequency - Test 1kHz Features - Mounting Type Surface Mount Package / Case Nonstandard	Tolerance	±30%
Shielding DC Resistance (DCR) 21 mOhm Max Q @ Freq - Frequency - Self Resonant Ratings - Operating Temperature Frequency - Test Frequency - Test Features Mounting Type Surface Mount Package / Case Shielded 21 mOhm Max - Lange Mount Surface Mount Nonstandard	Current Rating	5A
DC Resistance (DCR) Q @ Freq Frequency - Self Resonant Ratings Operating Temperature Frequency - Test IkHz Features Mounting Type Surface Mount Package / Case 21 mOhm Max 22 mOhm Max Lange And And Max Lange And	Current - Saturation	5.7A
Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature -20°C ~ 105°C Frequency - Test 1kHz Features - Mounting Type Surface Mount Package / Case Nonstandard	Shielding	Shielded
Frequency - Self Resonant Ratings Operating Temperature -20°C ~ 105°C Frequency - Test 1kHz Features Mounting Type Surface Mount Package / Case Nonstandard	DC Resistance (DCR)	21 mOhm Max
Ratings - Operating Temperature -20°C ~ 105°C Frequency - Test 1kHz Features - Mounting Type Surface Mount Package / Case Nonstandard	Q @ Freq	-
$ \begin{array}{cccccccccccccccccccccccccccccccccccc$	Frequency - Self Resonant	-
Frequency - Test 1kHz Features - Mounting Type Surface Mount Package / Case Nonstandard	Ratings	-
Features - Mounting Type Surface Mount Package / Case Nonstandard	Operating Temperature	-20°C ~ 105°C
Mounting Type Surface Mount Package / Case Nonstandard	Frequency - Test	1kHz
Package / Case Nonstandard	Features	-
-	Mounting Type	Surface Mount
	Package / Case	Nonstandard
Supplier Device Package -	Supplier Device Package	-
Size / Dimension 0.492" L x 0.492" W (12.50mm x 12.50mm)	Size / Dimension	0.492" L x 0.492" W (12.50mm x 12.50mm)

Height - Seated (Max) 0.256" (6.50mm) Report errors?

PM12565S-7R0 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PM12565S-7R0 Payment Methods





















PM12565S-7R0 Shipping Methods













If you have any question about PM12565S-7R0, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com