

**PM125S-100M Information**


For Reference Only

**Part Number** [PM125S-100M](#)  
**Manufacturer** Bourns Inc.  
**Category** Inductors, Coils, Chokes  
[Fixed Inductors](#)  
**Description** FIXED IND 10UH 2.65A 50 MOHM SMD  
**Package** Nonstandard  
 For the pricing/inventory/lead time, please contact us  
 Website: <https://www.heisener.com>  
 E-mail: [salesdept@heisener.com](mailto:salesdept@heisener.com)


[Request a Quote](#)
**Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.


**PM125S-100M Specifications**

Manufacturer Part Number	<a href="#">PM125S-100M</a>
Manufacturer	Bourns Inc.
Category	Inductors, Coils, Chokes <a href="#">Fixed Inductors</a>
Package	Nonstandard
Series	PM125S
Type	Wirewound
Material - Core	Ferrite
Inductance	10μH
Tolerance	±20%
Current Rating	2.65A
Current - Saturation	4.43A
Shielding	Shielded
DC Resistance (DCR)	50 mOhm Max
Q @ Freq	-
Frequency - Self Resonant	24MHz
Ratings	-
Operating Temperature	-40°C ~ 125°C
Frequency - Test	2.52MHz
Features	-
Mounting Type	Surface Mount
Package / Case	Nonstandard
Supplier Device Package	-
Size / Dimension	0.496" L x 0.457" W (12.60mm x 11.60mm)

Height - Seated (Max)	0.213" (5.40mm)
-----------------------	-----------------

[Report errors?](#)

## PM125S-100M Guarantees



### Quality Guarantees

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



### Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## PM125S-100M Payment Methods



## PM125S-100M Shipping Methods



If you have any question about PM125S-100M, please do not hesitate to contact us!

Website: <https://www.heisener.com>

E-mail: [salesdept@heisener.com](mailto:salesdept@heisener.com)