

PM3602-5-B-RC

PM3602-5-B-RC Information

| - | Part Number | PM3602-5-B-RC |
|--|--------------|---|
| A STATE OF STATE | | 1 MJ002-J-D-ICC |
| | Manufacturer | Bourns Inc. |
| any weather an | Category | Inductors, Coils, Chokes Arrays, Signal Transformers |
| 0 | Description | INDUCT ARRAY 2 COIL 5UH SMD |
| | Package | Nonstandard |
| | | For the pricing/inventory/lead time, please contact |
| | | us |
| For Reference Only | | Website: https://www.heisener.com |
| | | E-mail: salesdept@heisener.com |



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



PM3602-5-B-RC Specifications

| Manufacturer Bourns Inc. Category Inductors, Coils, Chokes Arrays, Signal Transformers Arrays, Signal Transformers Package Nonstandard Series PM3600 Number of Coils 2 Test Inductance - Connected In Series 20µH Inductance - Connected In Parallel 5µH Tolerance ±20% Current Rating - Parallel 2.41A Current Rating - Series 1.2A Current Saturation - Parallel 2 DC Resistance (DCR) - Parallel 23 mOhm Max DC Resistance (DCR) - Series 92 mOhm Max Shielding Unshielded Operating Temperature -55°C ~ 125°C Mounting Type Surface Mount Package / Case Nonstandard | | |
|--|---------------------------------------|--|
| CategoryInductors, Coils, ChokesArrays, Signal TransformersPackageNonstandardSeriesPM3600Number of Coils2Test Inductance - Connected In Series20µHInductance - Connected In Parallel5µHTolerance2.41ACurrent Rating - Series1.2ACurrent Saturation - Parallel-Current Saturation - Series92 mOhm MaxDC Resistance (DCR) - Parallel23 mOhm MaxDC Resistance (DCR) - Series92 mOhm MaxShieldingUnshieldedOperating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / CaseNonstandardSize / Dimension0.452° L x 0.354" W (11.48mm x 8.99mm)Height0.225" (5.72mm) | Manufacturer Part Number | PM3602-5-B-RC |
| Arrays, Signal TransformersPackageNonstandardSeriesPM3600Number of Coils2Test Inductance - Connected In Series20μHInductance - Connected In Parallel5μHTolerance±20%Current Rating - Parallel2.41ACurrent Rating - Series1.2ACurrent Saturation - Parallel-DC Resistance (DCR) - Parallel23 mOhm MaxDC Resistance (DCR) - Series92 mOhm MaxShieldingUnshieldedOperating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / CaseNonstandardKiep / LawsNostandardSize / Dimension0.452° Lx 0.354° W (11.48mm x 8.99mm)Height0.225° (5.72mm) | Manufacturer | Bourns Inc. |
| PackageNonstandardSeriesPM3600Number of Coils2Test Inductance - Connected In Series20μHInductance - Connected In Parallel5μHTolerance±20%Current Rating - Parallel2.41ACurrent Rating - Series1.2ACurrent Saturation - Parallel-Current Saturation - Series-DC Resistance (DCR) - Parallel23 mOhm MaxDC Resistance (DCR) - Series92 mOhm MaxShieldingUnshieldedOperating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / CaseNonstandardSize / Dimension0.452" L x 0.354" W (11.48mm x 8.99mm)Height0.225" (5.72mm) | Category | Inductors, Coils, Chokes |
| Series PM3600 Number of Coils 2 Test Inductance - Connected In Series 20µH Inductance - Connected In Parallel 5µH Tolerance ±20% Current Rating - Parallel 2.41A Current Saturation - Parallel - Current Saturation - Parallel - Current Saturation - Series - DC Resistance (DCR) - Parallel 23 mOhm Max DC Resistance (DCR) - Series 92 mOhm Max Shielding Unshielded Operating Temperature -55°C ~ 125°C Mounting Type Surface Mount Package / Case Nonstandard Size / Dimension 0.452" L x 0.354" W (11.48mm x 8.99mm) Height 0.225" (5.72mm) | | Arrays, Signal Transformers |
| Number of Coils2Test Inductance - Connected In Series20µHInductance - Connected In Parallel5µHTolerance±20%Current Rating - Parallel2.41ACurrent Rating - Series1.2ACurrent Saturation - Parallel-Current Saturation - Series23 mOhm MaxDC Resistance (DCR) - Parallel23 mOhm MaxDC Resistance (DCR) - Series92 mOhm MaxShieldingUnshieldedOperating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / CaseNonstandardSize / Dimension0.452" L x 0.354" W (11.48mm x 8.99mm)Height0.225" (5.72mm) | Package | Nonstandard |
| Test Inductance - Connected In Series20μHInductance - Connected In Parallel5μHTolerance±20%Current Rating - Parallel2.41ACurrent Rating - Series1.2ACurrent Saturation - Parallel-Current Saturation - Series23 mOhm MaxDC Resistance (DCR) - Parallel20 mOhm MaxDC Resistance (DCR) - Series92 mOhm MaxShieldingUnshieldedOperating TemperatureSurface MountPackage / CaseNonstandardSize / Dimension0.452" L x 0.354" W (11.48mm x 8.99mm)Height0.225" (5.72mm) | Series | PM3600 |
| Inductance - Connected In Parallel5µHTolerance±20%Current Rating - Parallel2.41ACurrent Rating - Series1.2ACurrent Saturation - Parallel-Current Saturation - Parallel-Current Saturation - Series-DC Resistance (DCR) - Parallel23 mOhm MaxDC Resistance (DCR) - Series92 mOhm MaxShieldingUnshieldedOperating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / CaseNonstandardSize / Dimension0.452" L x 0.354" W (11.48mm x 8.99mm)Height0.225" (5.72mm) | Number of Coils | 2 |
| Tolerance±20%Current Rating - Parallel2.41ACurrent Rating - Series1.2ACurrent Saturation - Parallel-Current Saturation - Series-DC Resistance (DCR) - Parallel23 mOhm MaxDC Resistance (DCR) - Series92 mOhm MaxShieldingUnshieldedOperating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / CaseNonstandardSize / Dimension0.452" L x 0.354" W (11.48mm x 8.99mm)Height0.225" (5.72mm) | Test Inductance - Connected In Series | 20µН |
| Current Rating - Parallel2.41ACurrent Rating - Series1.2ACurrent Saturation - Parallel-Current Saturation - Series-Current Saturation - Series23 mOhm MaxDC Resistance (DCR) - Parallel23 mOhm MaxDC Resistance (DCR) - Series92 mOhm MaxShieldingUnshieldedOperating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / CaseNonstandardSize / Dimension0.452" L x 0.354" W (11.48mm x 8.99mm)Height0.225" (5.72mm) | Inductance - Connected In Parallel | 5µH |
| Current Rating - Series1.2ACurrent Saturation - Parallel-Current Saturation - Series-DC Resistance (DCR) - Parallel23 mOhm MaxDC Resistance (DCR) - Series92 mOhm MaxShieldingUnshieldedOperating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / CaseNonstandardSize / Dimension0.452" L x 0.354" W (11.48mm x 8.99mm)Height0.225" (5.72mm) | Tolerance | ±20% |
| Current Saturation - Parallel-Current Saturation - Series-DC Resistance (DCR) - Parallel23 mOhm MaxDC Resistance (DCR) - Series92 mOhm MaxShieldingUnshieldedOperating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / CaseNonstandardSize / Dimension0.452" L x 0.354" W (11.48mm x 8.99mm)Height0.225" (5.72mm) | Current Rating - Parallel | 2.41A |
| Current Saturation - Series-DC Resistance (DCR) - Parallel23 mOhm MaxDC Resistance (DCR) - Series92 mOhm MaxShieldingUnshieldedOperating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / CaseNonstandardSize / Dimension0.452" L x 0.354" W (11.48mm x 8.99mm)Height0.225" (5.72mm) | Current Rating - Series | 1.2A |
| DC Resistance (DCR) - Parallel23 mOhm MaxDC Resistance (DCR) - Series92 mOhm MaxShieldingUnshieldedOperating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / CaseNonstandardSize / Dimension0.452" L x 0.354" W (11.48mm x 8.99mm)Height0.225" (5.72mm) | Current Saturation - Parallel | - |
| DC Resistance (DCR) - Series92 mOhm MaxShieldingUnshieldedOperating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / CaseNonstandardSize / Dimension0.452" L x 0.354" W (11.48mm x 8.99mm)Height0.225" (5.72mm) | Current Saturation - Series | - |
| ShieldingUnshieldedOperating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / CaseNonstandardSize / Dimension0.452" L x 0.354" W (11.48mm x 8.99mm)Height0.225" (5.72mm) | DC Resistance (DCR) - Parallel | 23 mOhm Max |
| Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / CaseNonstandardSize / Dimension0.452" L x 0.354" W (11.48mm x 8.99mm)Height0.225" (5.72mm) | DC Resistance (DCR) - Series | 92 mOhm Max |
| Nounting TypeSurface MountPackage / CaseNonstandardSize / Dimension0.452" L x 0.354" W (11.48mm x 8.99mm)Height0.225" (5.72mm) | Shielding | Unshielded |
| Package / Case Nonstandard Size / Dimension 0.452" L x 0.354" W (11.48mm x 8.99mm) Height 0.225" (5.72mm) | Operating Temperature | -55°C ~ 125°C |
| Size / Dimension 0.452" L x 0.354" W (11.48mm x 8.99mm) Height 0.225" (5.72mm) | Mounting Type | Surface Mount |
| Height 0.225" (5.72mm) | Package / Case | Nonstandard |
| - | Size / Dimension | 0.452" L x 0.354" W (11.48mm x 8.99mm) |
| Report errors? | Height | 0.225" (5.72mm) |
| | | Report errors? |

PM3602-5-B-RC Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

PM3602-5-B-RC Payment Methods



PM3602-5-B-RC Shipping Methods



If you have any question about PM3602-5-B-RC, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com