



PM3ACW6.0 Information

Heisener.com

Part Number PM3ACW6.0 **Manufacturer** Bivar Inc.

Category Optoelectronics

Panel Indicators, Pilot Lights

Description LED ASSY PNL 3MM AMB WTR CLR 6"

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PM3ACW6.0 Specifications

Manufacturer Part Number PM3ACW6.0 Manufacturer Bivar Inc. Category Optoelectronics Panel Indicators, Pilot Lights Package - Scries - Type LED Lamp Color Amber Lens Color Colorless Lens Transparency Clear Ratings Vf (Typ), If (Max) Voltage 2V Current 20mA Panel Cutout Shape Round Panel Cutout Dimensions 0.16" (4.06mm) Lens Style/Size Round with Domed Top, 3mm (T-1) Millicandela Rating 40mcd Wavelength - Peak 605nm Viewing Angle 30° Termination Style Wire Leads - 6" (152.40mm) Ingress Protection - Features -		
Category Optoelectronics Panel Indicators, Pilot Lights Package - Series - Type LED Lamp Color Amber Lens Color Colorless Lens Transparency Clear Ratings Vf (Typ), If (Max) Voltage 2V Current 20mA Panel Cutout Shape Round Panel Cutout Dimensions 0.16" (4.06mm) Lens Style/Size Round with Domed Top, 3mm (T-1) Millicandela Rating 40mcd Wavelength - Peak 605nm Viewing Angle 30° Termination Style Wire Leads - 6" (152.40mm) Ingress Protection - Features -	Manufacturer Part Number	PM3ACW6.0
Package Series Type LED Lamp Color Amber Lens Color Colorless Lens Transparency Clear Ratings Vf (Typ), If (Max) Voltage 2V Current 20mA Panel Cutout Shape Round Panel Cutout Dimensions 0.16" (4.06mm) Lens Style/Size Round with Domed Top, 3mm (T-1) Millicandela Rating 40mcd Wavelength - Peak 605nm Viewing Angle 30° Termination Style Wire Leads - 6" (152.40mm) Ingress Protection Features	Manufacturer	Bivar Inc.
Package - Series - Type LED Lamp Color Amber Lens Color Colorless Lens Transparency Clear Ratings Vf (Typ), If (Max) Voltage 2V Current 20mA Panel Cutout Shape Round Panel Cutout Dimensions 0.16" (4.06mm) Lens Style/Size Round with Domed Top, 3mm (T-1) Millicandela Rating 40mcd Wavelength - Peak 605nm Viewing Angle 30° Termination Style Wire Leads - 6" (152.40mm) Ingress Protection - Features -	Category	Optoelectronics
Series - LED Lamp Color Amber Lens Color Colorless Lens Transparency Clear Ratings Vf (Typ), If (Max) Voltage 2V Current 20mA Panel Cutout Shape Round Panel Cutout Dimensions 0.16" (4.06mm) Lens Style/Size Round with Domed Top, 3mm (T-1) Millicandela Rating 40mcd Wavelength - Peak 605nm Viewing Angle 30° Termination Style Wire Leads - 6" (152.40mm) Ingress Protection - Features Features		Panel Indicators, Pilot Lights
TypeLEDLamp ColorAmberLens ColorColorlessLens TransparencyClearRatingsVf (Typ), If (Max)Voltage2VCurrent20mAPanel Cutout ShapeRoundPanel Cutout Dimensions0.16" (4.06mm)Lens Style/SizeRound with Domed Top, 3mm (T-1)Millicandela Rating40mcdWavelength - Peak605nmViewing Angle30°Termination StyleWire Leads - 6" (152.40mm)Ingress Protection-Features-	Package	-
Lamp Color Lens Color Colorless Lens Transparency Clear Ratings Vf (Typ), If (Max) Voltage 2V Current 20mA Panel Cutout Shape Round Panel Cutout Dimensions Lens Style/Size Round with Domed Top, 3mm (T-1) Millicandela Rating Wavelength - Peak Viewing Angle Termination Style Ingress Protection Features Amber Amber Am	Series	-
Lens ColorColorlessLens TransparencyClearRatingsVf (Typ), If (Max)Voltage2VCurrent20mAPanel Cutout ShapeRoundPanel Cutout Dimensions0.16" (4.06mm)Lens Style/SizeRound with Domed Top, 3mm (T-1)Millicandela Rating40mcdWavelength - Peak605nmViewing Angle30°Termination StyleWire Leads - 6" (152.40mm)Ingress Protection-Features-	Туре	LED
Lens TransparencyClearRatingsVf (Typ), If (Max)Voltage2VCurrent20mAPanel Cutout ShapeRoundPanel Cutout Dimensions0.16" (4.06mm)Lens Style/SizeRound with Domed Top, 3mm (T-1)Millicandela Rating40mcdWavelength - Peak605nmViewing Angle30°Termination StyleWire Leads - 6" (152.40mm)Ingress Protection-Features-	Lamp Color	Amber
Ratings Voltage 2V Current 20mA Panel Cutout Shape Round Panel Cutout Dimensions 0.16" (4.06mm) Lens Style/Size Round with Domed Top, 3mm (T-1) Millicandela Rating 40mcd Wavelength - Peak 605nm Viewing Angle 30° Termination Style Wire Leads - 6" (152.40mm) Ingress Protection Features -	Lens Color	Colorless
Voltage 2V Current 20mA Panel Cutout Shape Round Panel Cutout Dimensions 0.16" (4.06mm) Lens Style/Size Round with Domed Top, 3mm (T-1) Millicandela Rating 40mcd Wavelength - Peak 605nm Viewing Angle 30° Termination Style Wire Leads - 6" (152.40mm) Ingress Protection - Features -	Lens Transparency	Clear
Current 20mA Panel Cutout Shape Round Panel Cutout Dimensions 0.16" (4.06mm) Lens Style/Size Round with Domed Top, 3mm (T-1) Millicandela Rating 40mcd Wavelength - Peak 605nm Viewing Angle 30° Termination Style Wire Leads - 6" (152.40mm) Ingress Protection - Features -	Ratings	Vf (Typ), If (Max)
Panel Cutout Dimensions O.16" (4.06mm) Lens Style/Size Round with Domed Top, 3mm (T-1) Millicandela Rating 40mcd Wavelength - Peak 605nm Viewing Angle Termination Style Ingress Protection Features Round Wind Wind Wind Wind Round With Domed Top, 3mm (T-1) Features Round With Domed Top, 3mm (T-1) Wind Wire Leads - 6" (152.40mm)	Voltage	2V
Panel Cutout Dimensions O.16" (4.06mm) Lens Style/Size Round with Domed Top, 3mm (T-1) Millicandela Rating 40mcd Wavelength - Peak 605nm Viewing Angle Termination Style Wire Leads - 6" (152.40mm) Ingress Protection Features -	Current	20mA
Lens Style/SizeRound with Domed Top, 3mm (T-1)Millicandela Rating40mcdWavelength - Peak605nmViewing Angle30°Termination StyleWire Leads - 6" (152.40mm)Ingress Protection-Features-	Panel Cutout Shape	Round
Millicandela Rating 40mcd Wavelength - Peak 605nm Viewing Angle Termination Style Ingress Protection Features 40mcd 605nm Wire Leads - 6" (152.40mm) -	Panel Cutout Dimensions	0.16" (4.06mm)
Wavelength - Peak Viewing Angle 30° Termination Style Ingress Protection Features 605nm Wire Leads - 6" (152.40mm) -	Lens Style/Size	Round with Domed Top, 3mm (T-1)
Viewing Angle30°Termination StyleWire Leads - 6" (152.40mm)Ingress Protection-Features-	Millicandela Rating	40mcd
Termination Style Wire Leads - 6" (152.40mm) Ingress Protection - Features -	Wavelength - Peak	605nm
Ingress Protection - Features -	Viewing Angle	30°
Features -	Termination Style	Wire Leads - 6" (152.40mm)
	Ingress Protection	-
Report errors?	Features	-
		Report errors?

PM3ACW6.0 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PM3ACW6.0 Payment Methods





















PM3ACW6.0 Shipping Methods













If you have any question about PM3ACW6.0, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com