



PM3ADW6.0 Information

Heisener.com

Part Number PM3ADW6.0 Manufacturer Bivar Inc.

Category Optoelectronics

Panel Indicators, Pilot Lights

Description LED ASSY PNL 3MM AMB DIFF 6"

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PM3ADW6.0 Specifications

Manufacturer Part Number PM3ADW6.0 Manufacturer Bivar Inc. Category Optoelectronics Package - Scries - Type LED Lamp Color Amber Lens Color - Lens Transparency Diffused Ratings Vf (Typ), If (Max) Voltage 2V Current 20mA Panel Cutout Shape Round Panel Cutout Dimensions 0.16" (4.06mm) Lens Style/Size Round with Domed Top, 3mm (T-1) Millicandela Rating 25mcd Wavelength - Peak 605nm Viewing Angle 40° Termination Style Wire Leads - 6" (152.40mm) Ingress Protection - Features -		
CategoryOptoelectronicsPackage-Series-TypeLEDLamp ColorAmberLens TransparencyDiffusedRatingsVf (Typ), If (Max)Voltage2VCurrent20mAPanel Cutout ShapeRoundPanel Cutout Dimensions0.16" (4.06mm)Lens Style/SizeRound with Domed Top, 3mm (T-1)Millicandela Rating25mcdWavelength - Peak605nmViewing Angle40°Termination StyleWire Leads - 6" (152.40mm)Ingress Protection-Features-	Manufacturer Part Number	PM3ADW6.0
Package Series Type LED Lamp Color Amber Lens Transparency Diffused Ratings Vf (Typ), If (Max) Voltage 2V Current 20mA Panel Cutout Shape Round Panel Cutout Dimensions 0.16" (4.06mm) Lens Style/Size Round with Domed Top, 3mm (T-1) Millicandela Rating 25mcd Wavelength - Peak 605nm Viewing Angle 40° Termination Style Wire Leads - 6" (152.40mm) Ingress Protection Features	Manufacturer	Bivar Inc.
Package - Series - Type LED Lamp Color Amber Lens Color - Lens Transparency Diffused Ratings Vf (Typ), If (Max) Voltage 2V Current 20mA Panel Cutout Shape Round Panel Cutout Dimensions 0.16" (4.06mm) Lens Style/Size Round with Domed Top, 3mm (T-1) Millicandela Rating 25mcd Wavelength - Peak 605mm Viewing Angle 40° Termination Style Wire Leads - 6" (152.40mm) Ingress Protection - Features -	Category	Optoelectronics
Series - Type LED Lamp Color Amber Lens Color - Lens Transparency Diffused Ratings Vf (Typ), If (Max) Voltage 2V Current 20mA Panel Cutout Shape Round Panel Cutout Dimensions 0.16" (4.06mm) Lens Style/Size Round with Domed Top, 3mm (T-1) Millicandela Rating 25mcd Wavelength - Peak 605nm Viewing Angle 40° Termination Style Wire Leads - 6" (152.40mm) Ingress Protection - Features -		Panel Indicators, Pilot Lights
TypeLEDLamp ColorAmberLens Color-Lens TransparencyDiffusedRatingsVf (Typ), If (Max)Voltage2VCurrent20mAPanel Cutout ShapeRoundPanel Cutout Dimensions0.16" (4.06mm)Lens Style/SizeRound with Domed Top, 3mm (T-1)Millicandela Rating25mcdWavelength - Peak605nmViewing Angle40°Termination StyleWire Leads - 6" (152.40mm)Ingress Protection-Features-	Package	-
Lamp Color Lens Color Lens Transparency Diffused Ratings Vf (Typ), If (Max) Voltage 2V Current 20mA Panel Cutout Shape Racings Round Panel Cutout Dimensions Lens Style/Size Round with Domed Top, 3mm (T-1) Millicandela Rating 25mcd Wavelength - Peak 605nm Viewing Angle 40° Termination Style Ingress Protection Features Amber Amber Amb	Series	-
Lens Color-Lens TransparencyDiffusedRatingsVf (Typ), If (Max)Voltage2VCurrent20mAPanel Cutout ShapeRoundPanel Cutout Dimensions0.16" (4.06mm)Lens Style/SizeRound with Domed Top, 3mm (T-1)Millicandela Rating25mcdWavelength - Peak605nmViewing Angle40°Termination StyleWire Leads - 6" (152.40mm)Ingress Protection-Features-	Type	LED
Lens TransparencyDiffusedRatingsVf (Typ), If (Max)Voltage2VCurrent20mAPanel Cutout ShapeRoundPanel Cutout Dimensions0.16" (4.06mm)Lens Style/SizeRound with Domed Top, 3mm (T-1)Millicandela Rating25mcdWavelength - Peak605nmViewing Angle40°Termination StyleWire Leads - 6" (152.40mm)Ingress Protection-Features-	Lamp Color	Amber
Ratings Vf (Typ), If (Max) Voltage 2V Current 20mA Panel Cutout Shape Round Panel Cutout Dimensions 0.16" (4.06mm) Lens Style/Size Round with Domed Top, 3mm (T-1) Millicandela Rating 25mcd Wavelength - Peak 605nm Viewing Angle 40° Termination Style Wire Leads - 6" (152.40mm) Ingress Protection - Features -	Lens Color	-
Voltage 2V Current 20mA Panel Cutout Shape Round Panel Cutout Dimensions 0.16" (4.06mm) Lens Style/Size Round with Domed Top, 3mm (T-1) Millicandela Rating 25mcd Wavelength - Peak 605nm Viewing Angle 40° Termination Style Wire Leads - 6" (152.40mm) Ingress Protection - Features -	Lens Transparency	Diffused
Current 20mA Panel Cutout Shape Round Panel Cutout Dimensions 0.16" (4.06mm) Lens Style/Size Round with Domed Top, 3mm (T-1) Millicandela Rating 25mcd Wavelength - Peak 605nm Viewing Angle 40° Termination Style Wire Leads - 6" (152.40mm) Ingress Protection - Features -	Ratings	Vf (Typ), If (Max)
Panel Cutout Dimensions 0.16" (4.06mm) Lens Style/Size Round with Domed Top, 3mm (T-1) Millicandela Rating 25mcd Wavelength - Peak 605nm Viewing Angle 40° Termination Style Wire Leads - 6" (152.40mm) Ingress Protection - Features -	Voltage	2V
Panel Cutout Dimensions O.16" (4.06mm) Lens Style/Size Round with Domed Top, 3mm (T-1) Millicandela Rating 25mcd Wavelength - Peak 605nm Viewing Angle Termination Style Wire Leads - 6" (152.40mm) Ingress Protection Features -	Current	20mA
Lens Style/SizeRound with Domed Top, 3mm (T-1)Millicandela Rating25mcdWavelength - Peak605nmViewing Angle40°Termination StyleWire Leads - 6" (152.40mm)Ingress Protection-Features-	Panel Cutout Shape	Round
Millicandela Rating Wavelength - Peak 605nm Viewing Angle Termination Style Ingress Protection Features 25mcd 605nm 40° Wire Leads - 6" (152.40mm) -	Panel Cutout Dimensions	0.16" (4.06mm)
Wavelength - Peak Viewing Angle 40° Termination Style Ingress Protection Features 605nm Wire Leads - 6" (152.40mm) - -	Lens Style/Size	Round with Domed Top, 3mm (T-1)
Viewing Angle40°Termination StyleWire Leads - 6" (152.40mm)Ingress Protection-Features-	Millicandela Rating	25mcd
Termination Style Wire Leads - 6" (152.40mm) Ingress Protection - Features -	Wavelength - Peak	605nm
Ingress Protection - Features -	Viewing Angle	40°
Features -	Termination Style	Wire Leads - 6" (152.40mm)
	Ingress Protection	-
Report errors?	Features	-
		Report errors?

PM3ADW6.0 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PM3ADW6.0 Payment Methods



















PM3ADW6.0 Shipping Methods













If you have any question about PM3ADW6.0, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com