



PM3GDLW6 Information

Heisener.com

Part Number PM3GDLW6 **Manufacturer** Bivar Inc.

Category Optoelectronics

Panel Indicators, Pilot Lights

Description PNL MNT 7MA GREEN W/WIRE 6"

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com





Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PM3GDLW6 Specifications

Manufacturer PM3GDLW6 Manufacturer Bivar Inc. Category Optoelectronics Panel Indicators, Pilot Lights Package - Series PM3 Type LED Lamp Color Green Lens Color Green Lens Transparency Diffused Ratings Vf (Typ), If (Max) Voltage 2.1V Current 7mA Panel Cutout Shape Round Panel Cutout Dimensions 0.16" (4.06mm) Lens Style/Size Round with Domed Top, 3mm (T-1) Millicandela Rating 2mcd Wavelength - Peak 568nm Viewing Angle 40° Termination Style Wire Leads - 6" (152.40mm) Ingress Protection - Features -		
CategoryOptoelectronicsPackage-SeriesPM3TypeLEDLamp ColorGreenLens TransparencyDiffusedRatingsVf (Typ), If (Max)Voltage2.1VCurrent7mAPanel Cutout ShapeRoundPanel Cutout Dimensions0.16" (4.06mm)Lens Style/SizeRound with Domed Top, 3mm (T-1)Millicandela Rating2mcdWavelength - Peak568nmViewing Angle40°Termination StyleWire Leads - 6" (152.40mm)Ingress Protection-Features-	Manufacturer Part Number	PM3GDLW6
Package-SeriesPM3TypeLEDLamp ColorGreenLens TransparencyDiffusedRatingsVf (Typ), If (Max)Voltage2.1VCurrent7mAPanel Cutout ShapeRoundPanel Cutout Dimensions0.16" (4.06mm)Lens Style/SizeRound with Domed Top, 3mm (T-1)Millicandela Rating2mcdWavelength - Peak568nmViewing Angle40°Termination StyleWire Leads - 6" (152.40mm)Ingress Protection-Features-	Manufacturer	Bivar Inc.
Package - Series PM3 Type LED Lamp Color Green Lens Color Green Lens Transparency Diffused Ratings Vf (Typ), If (Max) Voltage 2.1V Current 7mA Panel Cutout Shape Round Panel Cutout Dimensions 0.16" (4.06mm) Lens Style/Size Round with Domed Top, 3mm (T-1) Millicandela Rating 2mcd Wavelength - Peak 568nm Viewing Angle 40° Termination Style Wire Leads - 6" (152.40mm) Ingress Protection - Features -	Category	Optoelectronics
Series PM3 Type LED Lamp Color Green Lens Color Green Lens Transparency Diffused Ratings Vf (Typ), If (Max) Voltage 2.1V Current 7mA Panel Cutout Shape Round Panel Cutout Dimensions 0.16" (4.06mm) Lens Style/Size Round with Domed Top, 3mm (T-1) Millicandela Rating 2mcd Wavelength - Peak 568nm Viewing Angle 40° Termination Style Wire Leads - 6" (152.40mm) Ingress Protection - Features -		Panel Indicators, Pilot Lights
TypeLEDLamp ColorGreenLens ColorGreenLens TransparencyDiffusedRatingsVf (Typ), If (Max)Voltage2.1VCurrent7mAPanel Cutout ShapeRoundPanel Cutout Dimensions0.16" (4.06mm)Lens Style/SizeRound with Domed Top, 3mm (T-1)Millicandela Rating2mcdWavelength - Peak568nmViewing Angle40°Termination StyleWire Leads - 6" (152.40mm)Ingress Protection-Features-	Package	-
Lamp Color Lens Color Creen Cens Transparency Diffused Ratings Vf (Typ), If (Max) Voltage 2.1V Current 7mA Panel Cutout Shape Panel Cutout Dimensions Cens Tyle/Size Round with Domed Top, 3mm (T-1) Millicandela Rating Mavelength - Peak Viewing Angle Viewing Angle Vire Leads - 6" (152.40mm) Ingress Protection Features Green	Series	PM3
Lens ColorGreenLens TransparencyDiffusedRatingsVf (Typ), If (Max)Voltage2.1VCurrent7mAPanel Cutout ShapeRoundPanel Cutout Dimensions0.16" (4.06mm)Lens Style/SizeRound with Domed Top, 3mm (T-1)Millicandela Rating2mcdWavelength - Peak568nmViewing Angle40°Termination StyleWire Leads - 6" (152.40mm)Ingress Protection-Features-	Type	LED
Lens TransparencyDiffusedRatingsVf (Typ), If (Max)Voltage2.1VCurrent7mAPanel Cutout ShapeRoundPanel Cutout Dimensions0.16" (4.06mm)Lens Style/SizeRound with Domed Top, 3mm (T-1)Millicandela Rating2mcdWavelength - Peak568nmViewing Angle40°Termination StyleWire Leads - 6" (152.40mm)Ingress Protection-Features-	Lamp Color	Green
Ratings Vf (Typ), If (Max) Voltage 2.1V Current 7mA Panel Cutout Shape Round Panel Cutout Dimensions 0.16" (4.06mm) Lens Style/Size Round with Domed Top, 3mm (T-1) Millicandela Rating 2mcd Wavelength - Peak 568nm Viewing Angle 40° Termination Style Wire Leads - 6" (152.40mm) Ingress Protection Features -	Lens Color	Green
Voltage 2.1V Current 7mA Panel Cutout Shape Round Panel Cutout Dimensions 0.16" (4.06mm) Lens Style/Size Round with Domed Top, 3mm (T-1) Millicandela Rating 2mcd Wavelength - Peak 568nm Viewing Angle 40° Termination Style Wire Leads - 6" (152.40mm) Ingress Protection - Features -	Lens Transparency	Diffused
Current 7mA Panel Cutout Shape Round Panel Cutout Dimensions 0.16" (4.06mm) Lens Style/Size Round with Domed Top, 3mm (T-1) Millicandela Rating 2mcd Wavelength - Peak 568nm Viewing Angle 40° Termination Style Wire Leads - 6" (152.40mm) Ingress Protection - Features -	Ratings	Vf (Typ), If (Max)
Panel Cutout Shape Round Panel Cutout Dimensions 0.16" (4.06mm) Lens Style/Size Round with Domed Top, 3mm (T-1) Millicandela Rating 2mcd Wavelength - Peak 568nm Viewing Angle 40° Termination Style Wire Leads - 6" (152.40mm) Ingress Protection - Features -	Voltage	2.1V
Panel Cutout Dimensions 0.16" (4.06mm) Lens Style/Size Round with Domed Top, 3mm (T-1) Millicandela Rating 2mcd Wavelength - Peak 568nm Viewing Angle 40° Termination Style Wire Leads - 6" (152.40mm) Ingress Protection - Features -	Current	7mA
Lens Style/SizeRound with Domed Top, 3mm (T-1)Millicandela Rating2mcdWavelength - Peak568nmViewing Angle40°Termination StyleWire Leads - 6" (152.40mm)Ingress Protection-Features-	Panel Cutout Shape	Round
Millicandela Rating Wavelength - Peak 568nm Viewing Angle Termination Style Ingress Protection Features 2mcd 568nm 40° Wire Leads - 6" (152.40mm)	Panel Cutout Dimensions	0.16" (4.06mm)
Wavelength - Peak Viewing Angle 40° Termination Style Mire Leads - 6" (152.40mm) Ingress Protection Features -	Lens Style/Size	Round with Domed Top, 3mm (T-1)
Viewing Angle40°Termination StyleWire Leads - 6" (152.40mm)Ingress Protection-Features-	Millicandela Rating	2mcd
Termination Style Wire Leads - 6" (152.40mm) Ingress Protection - Features -	Wavelength - Peak	568nm
Ingress Protection Features	Viewing Angle	40°
Features -	Termination Style	Wire Leads - 6" (152.40mm)
	Ingress Protection	-
Report errors?	Features	-
		Report errors?

PM3GDLW6 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PM3GDLW6 Payment Methods



















PM3GDLW6 Shipping Methods













If you have any question about PM3GDLW6, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com