



### **PM3HDW6 Information**

Heisener.com

**Part Number** PM3HDW6 **Manufacturer** Bivar Inc.

**Category** Optoelectronics

Panel Indicators, Pilot Lights

**Description** PANEL MOUNT ASSEMBLY 3MM RED

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **PM3HDW6 Specifications**

Manufacturer Part Number         PM3HDW6           Manufacturer         Bivar Inc.           Category         Optoelectronies           Package         -           Series         PM3           Type         LED           Lamp Color         Red           Lens Color         Red           Lens Transparency         Diffused           Ratings         Vf (Typ), If (Max)           Voltage         2V           Current         30mA           Panel Cutout Shape         Round           Panel Cutout Dimensions         0.16" (4.06mm)           Lens Style/Size         Round with Domed Top, 3mm (T-1)           Millicandela Rating         30mcd           Wavelength - Peak         625nm           Viewing Angle         40°           Termination Style         Wire Leads - 6" (152.40mm)           Ingress Protection         -           Features         -		
Category Optoelectronics Panel Indicators, Pilot Lights  Package - Series PM3  Type LED Lamp Color Red Lens Color Red Lens Transparency Diffused Ratings Vf (Typ), If (Max)  Voltage 2V  Current 30mA Panel Cutout Shape Round Panel Cutout Dimensions 0.16" (4.06mm) Lens Style/Size Round with Domed Top, 3mm (T-1)  Millicandela Rating 30mcd Wavelength - Peak 625nm  Viewing Angle 40°  Termination Style Wire Leads - 6" (152.40mm) Ingress Protection - Features -	Manufacturer Part Number	PM3HDW6
Package - Series PM3 Type LED Lamp Color Red Lens Color Red Lens Transparency Diffused Ratings Vf (Typ), If (Max) Voltage 2V Current 30mA Panel Cutout Dimensions 0.16" (4.06mm) Lens Style/Size Round with Domed Top, 3mm (T-1) Millicandela Rating 30mcd Wavelength - Peak 625nm Viewing Angle 40° Termination Style Wire Leads - 6" (152.40mm) Ingress Protection - Features - Features PM3  PM3  Augusta Indicators, Pilot Lights  Augusta	Manufacturer	Bivar Inc.
Package         -           Series         PM3           Type         LED           Lamp Color         Red           Lens Color         Red           Lens Transparency         Diffused           Ratings         Vf (Typ), If (Max)           Voltage         2V           Current         30mA           Panel Cutout Shape         Round           Panel Cutout Dimensions         0.16" (4.06mm)           Lens Style/Size         Round with Domed Top, 3mm (T-1)           Millicandela Rating         30mcd           Wavelength - Peak         625nm           Viewing Angle         40°           Termination Style         Wire Leads - 6" (152.40mm)           Ingress Protection         -           Features         -	Category	Optoelectronics
SeriesPM3TypeLEDLamp ColorRedLens ColorRedLens TransparencyDiffusedRatingsVf (Typ), If (Max)Voltage2VCurrent30mAPanel Cutout ShapeRoundPanel Cutout Dimensions0.16" (4.06mm)Lens Style/SizeRound with Domed Top, 3mm (T-1)Millicandela Rating30mcdWavelength - Peak625nmViewing Angle40°Termination StyleWire Leads - 6" (152.40mm)Ingress Protection-Features-		Panel Indicators, Pilot Lights
TypeLEDLamp ColorRedLens ColorRedLens TransparencyDiffusedRatingsVf (Typ), If (Max)Voltage2VCurrent30mAPanel Cutout ShapeRoundPanel Cutout Dimensions0.16" (4.06mm)Lens Style/SizeRound with Domed Top, 3mm (T-1)Millicandela Rating30mcdWavelength - Peak625nmViewing Angle40°Termination StyleWire Leads - 6" (152.40mm)Ingress Protection-Features-	Package	-
Lamp Color Lens Color Red Lens Transparency Diffused  Vf (Typ), If (Max) Voltage 2V Current 30mA Panel Cutout Shape Round Panel Cutout Dimensions Lens Style/Size Round with Domed Top, 3mm (T-1) Millicandela Rating Wavelength - Peak Viewing Angle Termination Style Ingress Protection Features Red Wed Red Red Red Red Red Red Red Red Red R	Series	PM3
Lens ColorRedLens TransparencyDiffusedRatingsVf (Typ), If (Max)Voltage2VCurrent30mAPanel Cutout ShapeRoundPanel Cutout Dimensions0.16" (4.06mm)Lens Style/SizeRound with Domed Top, 3mm (T-1)Millicandela Rating30mcdWavelength - Peak625nmViewing Angle40°Termination StyleWire Leads - 6" (152.40mm)Ingress Protection-Features-	Туре	LED
Lens Transparency  Ratings  Vf (Typ), If (Max)  Voltage  2V  Current  30mA  Panel Cutout Shape  Round  Panel Cutout Dimensions  0.16" (4.06mm)  Lens Style/Size  Round with Domed Top, 3mm (T-1)  Millicandela Rating  30mcd  Wavelength - Peak  625nm  Viewing Angle  40°  Termination Style  Wire Leads - 6" (152.40mm)  Ingress Protection  - Features  -  Diffused  Vf (Typ), If (Max)  Aux  Viewing Angle  Diffused  40°  Wire Leads - 6" (152.40mm)  - Features	Lamp Color	Red
Ratings Vf (Typ), If (Max)  Voltage 2V  Current 30mA  Panel Cutout Shape Round Panel Cutout Dimensions 0.16" (4.06mm)  Lens Style/Size Round with Domed Top, 3mm (T-1)  Millicandela Rating 30mcd  Wavelength - Peak 625nm  Viewing Angle 40°  Termination Style Wire Leads - 6" (152.40mm)  Ingress Protection Features -	Lens Color	Red
Voltage2VCurrent30mAPanel Cutout ShapeRoundPanel Cutout Dimensions0.16" (4.06mm)Lens Style/SizeRound with Domed Top, 3mm (T-1)Millicandela Rating30mcdWavelength - Peak625nmViewing Angle40°Termination StyleWire Leads - 6" (152.40mm)Ingress Protection-Features-	Lens Transparency	Diffused
Current 30mA Panel Cutout Shape Round Panel Cutout Dimensions 0.16" (4.06mm) Lens Style/Size Round with Domed Top, 3mm (T-1) Millicandela Rating 30mcd Wavelength - Peak 625nm Viewing Angle 40° Termination Style Wire Leads - 6" (152.40mm) Ingress Protection - Features -	Ratings	Vf (Typ), If (Max)
Panel Cutout Dimensions 0.16" (4.06mm)  Lens Style/Size Round with Domed Top, 3mm (T-1)  Millicandela Rating 30mcd  Wavelength - Peak 625nm  Viewing Angle 40°  Termination Style Wire Leads - 6" (152.40mm)  Ingress Protection -  Features -	Voltage	2V
Panel Cutout Dimensions  O.16" (4.06mm)  Lens Style/Size  Round with Domed Top, 3mm (T-1)  Millicandela Rating  30mcd  Wavelength - Peak  625nm  Viewing Angle  Termination Style  Wire Leads - 6" (152.40mm)  Ingress Protection  Features  -	Current	30mA
Lens Style/SizeRound with Domed Top, 3mm (T-1)Millicandela Rating30mcdWavelength - Peak625nmViewing Angle40°Termination StyleWire Leads - 6" (152.40mm)Ingress Protection-Features-	Panel Cutout Shape	Round
Millicandela Rating  Wavelength - Peak  625nm  Viewing Angle  Termination Style  Ingress Protection  Features  30mcd  625nm  40°  Wire Leads - 6" (152.40mm)  -	Panel Cutout Dimensions	0.16" (4.06mm)
Wavelength - Peak  Viewing Angle  Termination Style  Ingress Protection  Features  625nm  Wire Leads - 6" (152.40mm)  -  -	Lens Style/Size	Round with Domed Top, 3mm (T-1)
Viewing Angle40°Termination StyleWire Leads - 6" (152.40mm)Ingress Protection-Features-	Millicandela Rating	30mcd
Termination Style Wire Leads - 6" (152.40mm)  Ingress Protection -  Features -	Wavelength - Peak	625nm
Ingress Protection	Viewing Angle	40°
Features -	Termination Style	Wire Leads - 6" (152.40mm)
	Ingress Protection	-
Report errors?	Features	-
		Report errors?

#### **PM3HDW6 Guarantees**



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **PM3HDW6 Payment Methods**



















## **PM3HDW6 Shipping Methods**













If you have any question about PM3HDW6, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com