



### **PM3HT Information**

(A) Heisener.com

**Part Number** PM3HT Manufacturer Bivar Inc.

**Category** Optoelectronics

Panel Indicators, Pilot Lights

**Description** PNL MNT W/ WIRE 625NM 50MCD RED

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **PM3HT Specifications**

Manufacturer Part Number         PM3HT           Manufacturer         Bivar Inc.           Category         Optoelectronics           Panel Indicators, Pilot Lights           Package         -           Series         PM3           Type         LED           Lamp Color         Red           Lens Color         Red           Lens Transparency         Clear           Ratings         Vf (Typ), If (Max)           Voltage         2V           Current         30mA           Panel Cutout Shape         Round           Panel Cutout Dimensions         0.16" (4.06mm)           Lens Style/Size         Round with Domed Top, 3mm (T-1)           Millicandela Rating         50mcd           Wavelength - Peak         625nm           Viewing Angle         30°           Termination Style         -           Ingress Protection         -           Features         -           Lens Stylerors?*		
CategoryOptoelectronicsPackage-SeriesPM3TypeLEDLamp ColorRedLens ColorRedLens TransparencyClearRatingsVf (Typ), If (Max)Voltage2VCurrent30mAPanel Cutout ShapeRoundPanel Cutout Dimensions0.16" (4.06mm)Lens Style/SizeRound with Domed Top, 3mm (T-1)Millicandela Rating50mcdWavelength - Peak625nmViewing Angle30°Termination Style-Ingress Protection-Features-	Manufacturer Part Number	РМЗНТ
Package         -           Series         PM3           Type         LED           Lamp Color         Red           Lens Color         Red           Lens Transparency         Clear           Ratings         Vf (Typ), If (Max)           Voltage         2V           Current         30mA           Panel Cutout Shape         Round           Panel Cutout Dimensions         0.16" (4.06mm)           Lens Style/Size         Round with Domed Top, 3mm (T-1)           Millicandela Rating         50mcd           Wavelength - Peak         625nm           Viewing Angle         30°           Termination Style         -           Ingress Protection         -           Features         -	Manufacturer	Bivar Inc.
Package         -           Series         PM3           Type         LED           Lamp Color         Red           Lens Color         Red           Lens Transparency         Clear           Ratings         Vf (Typ), If (Max)           Voltage         2V           Current         30mA           Panel Cutout Shape         Round           Panel Cutout Dimensions         0.16" (4.06mm)           Lens Style/Size         Round with Domed Top, 3mm (T-1)           Millicandela Rating         50mcd           Wavelength - Peak         625nm           Viewing Angle         30°           Termination Style         -           Ingress Protection         -           Features         -	Category	Optoelectronics
Series         PM3           Type         LED           Lamp Color         Red           Lens Color         Red           Lens Transparency         Clear           Ratings         Vf (Typ), If (Max)           Voltage         2V           Current         30mA           Panel Cutout Shape         Round           Panel Cutout Dimensions         0.16" (4.06mm)           Lens Style/Size         Round with Domed Top, 3mm (T-1)           Millicandela Rating         50mcd           Wavelength - Peak         625nm           Viewing Angle         30°           Termination Style         -           Ingress Protection         -           Features         -		Panel Indicators, Pilot Lights
TypeLEDLamp ColorRedLens ColorRedLens TransparencyClearRatingsVf (Typ), If (Max)Voltage2VCurrent30mAPanel Cutout ShapeRoundPanel Cutout Dimensions0.16" (4.06mm)Lens Style/SizeRound with Domed Top, 3mm (T-1)Millicandela Rating50mcdWavelength - Peak625nmViewing Angle30°Termination Style-Ingress Protection-Features-	Package	-
Lamp Color Lens Color Red Lens Transparency Clear Ratings Vf (Typ), If (Max) Voltage 2V Current 30mA Panel Cutout Shape Round Panel Cutout Dimensions Lens Style/Size Round with Domed Top, 3mm (T-1) Millicandela Rating Somcd Wavelength - Peak Viewing Angle Termination Style Ingress Protection Features  Red Red Red Red Red Red Red Red Red Re	Series	PM3
Lens ColorRedLens TransparencyClearRatingsVf (Typ), If (Max)Voltage2VCurrent30mAPanel Cutout ShapeRoundPanel Cutout Dimensions0.16" (4.06mm)Lens Style/SizeRound with Domed Top, 3mm (T-1)Millicandela Rating50mcdWavelength - Peak625nmViewing Angle30°Termination Style-Ingress Protection-Features-	Туре	LED
Lens TransparencyClearRatingsVf (Typ), If (Max)Voltage2VCurrent30mAPanel Cutout ShapeRoundPanel Cutout Dimensions0.16" (4.06mm)Lens Style/SizeRound with Domed Top, 3mm (T-1)Millicandela Rating50mcdWavelength - Peak625nmViewing Angle30°Termination Style-Ingress Protection-Features-	Lamp Color	Red
RatingsVf (Typ), If (Max)Voltage2VCurrent30mAPanel Cutout ShapeRoundPanel Cutout Dimensions0.16" (4.06mm)Lens Style/SizeRound with Domed Top, 3mm (T-1)Millicandela Rating50mcdWavelength - Peak625nmViewing Angle30°Termination Style-Ingress Protection-Features-	Lens Color	Red
Voltage 2V Current 30mA Panel Cutout Shape Round Panel Cutout Dimensions 0.16" (4.06mm) Lens Style/Size Round with Domed Top, 3mm (T-1) Millicandela Rating 50mcd Wavelength - Peak 625nm Viewing Angle 30° Termination Style - Ingress Protection - Features -	Lens Transparency	Clear
Current 30mA Panel Cutout Shape Round Panel Cutout Dimensions 0.16" (4.06mm) Lens Style/Size Round with Domed Top, 3mm (T-1) Millicandela Rating 50mcd Wavelength - Peak 625nm Viewing Angle 30° Termination Style - Ingress Protection - Features -	Ratings	Vf (Typ), If (Max)
Panel Cutout ShapeRoundPanel Cutout Dimensions0.16" (4.06mm)Lens Style/SizeRound with Domed Top, 3mm (T-1)Millicandela Rating50mcdWavelength - Peak625nmViewing Angle30°Termination Style-Ingress Protection-Features-	Voltage	2V
Panel Cutout Dimensions  O.16" (4.06mm)  Round with Domed Top, 3mm (T-1)  Millicandela Rating  50mcd  Wavelength - Peak  625nm  Viewing Angle  70 compared to the property of	Current	30mA
Lens Style/SizeRound with Domed Top, 3mm (T-1)Millicandela Rating50mcdWavelength - Peak625nmViewing Angle30°Termination Style-Ingress Protection-Features-	Panel Cutout Shape	Round
Millicandela Rating 50mcd  Wavelength - Peak 625nm  Viewing Angle 30°  Termination Style - Ingress Protection - Features -	Panel Cutout Dimensions	0.16" (4.06mm)
Wavelength - Peak  Viewing Angle  Termination Style  Ingress Protection  Features  625nm  625nm  -  -  -  -  -  -  -  -  -  -  -  -  -	Lens Style/Size	Round with Domed Top, 3mm (T-1)
Viewing Angle30°Termination Style-Ingress Protection-Features-	Millicandela Rating	50mcd
Termination Style - Ingress Protection - Features -	Wavelength - Peak	625nm
Ingress Protection - Features -	Viewing Angle	30°
Features -	Termination Style	-
	Ingress Protection	-
Report errors?	Features	-
		Report errors?

### **PM3HT Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **PM3HT Payment Methods**



















### **PM3HT Shipping Methods**













If you have any question about PM3HT, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com