



### **PM3SGDW10 Information**

Heisener.com

Part Number PM3SGDW10

Manufacturer Bivar Inc.

**Category** Optoelectronics

Panel Indicators, Pilot Lights

**Description** PNL MNT 20MA GREEN W/WIRE 10"

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com

Request a Quote



## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# PM3SGDW10 Specifications

Manufacturer Part Number         PM3SGDW10           Manufacturer         Bivar Inc.           Category         Optoelectronics           Panel Indicators, Pilot Lights           Package         -           Series         PM3           Type         LED           Lamp Color         Green           Lens Color         Green           Lens Transparency         Diffused           Ratings         Vf (Typ), If (Max)           Voltage         2.1V           Current         30mA           Panel Cutout Shape         Round           Panel Cutout Dimensions         0.16" (4.06mm)           Lens Style/Size         Round with Domed Top, 3mm (T-1)           Millicandela Rating         30mcd           Wavelength - Peak         568nm           Viewing Angle         40°           Termination Style         Wire Leads - 10" (254.00mm)           Ingress Protection         -           Features         -           Report errors?		
Category Panel Indicators, Pilot Lights Package Package PM3 Type LED Lamp Color Green Lens Color Diffused Ratings Vf (Typ), If (Max) Voltage 2.1V Current 30mA Panel Cutout Shape Round Panel Cutout Dimensions Lens Style/Size Round with Domed Top, 3mm (T-1) Millicandela Rating Wavelength - Peak Viewing Angle Termination Style Ingress Protection Features Panel Cutout Shape Wire Leads - 10" (254.00mm) Ingress Protection Features	Manufacturer Part Number	PM3SGDW10
Package - Series PM3 Type LED Lamp Color Green Lens Transparency Diffused Ratings Vf (Typ), If (Max) Voltage 2.1V Current 30mA Panel Cutout Shape Round Panel Cutout Dimensions 0.16" (4.06mm) Lens Style/Size Round with Domed Top, 3mm (T-1) Millicandela Rating 30mcd Wavelength - Peak 568mm Viewing Angle 40° Termination Style Wire Leads - 10" (254.00mm) Ingress Protection - Features Features  PM3 Green LED	Manufacturer	Bivar Inc.
Package         -           Series         PM3           Type         LED           Lamp Color         Green           Lens Color         Green           Lens Transparency         Diffused           Ratings         Vf (Typ), If (Max)           Voltage         2.1V           Current         30mA           Panel Cutout Shape         Round           Panel Cutout Dimensions         0.16" (4.06mm)           Lens Style/Size         Round with Domed Top, 3mm (T-1)           Millicandela Rating         30mcd           Wavelength - Peak         568mm           Viewing Angle         40°           Termination Style         Wire Leads - 10" (254.00mm)           Ingress Protection         -           Features         -	Category	Optoelectronics
SeriesPM3TypeLEDLamp ColorGreenLens ColorGreenLens TransparencyDiffusedRatingsVf (Typ), If (Max)Voltage2.1VCurrent30mAPanel Cutout ShapeRoundPanel Cutout Dimensions0.16" (4.06mm)Lens Style/SizeRound with Domed Top, 3mm (T-1)Millicandela Rating30mcdWavelength - Peak568nmViewing Angle40°Termination StyleWire Leads - 10" (254.00mm)Ingress Protection-Features-		Panel Indicators, Pilot Lights
TypeLEDLamp ColorGreenLens ColorGreenLens TransparencyDiffusedRatingsVf (Typ), If (Max)Voltage2.1VCurrent30mAPanel Cutout ShapeRoundPanel Cutout Dimensions0.16" (4.06mm)Lens Style/SizeRound with Domed Top, 3mm (T-1)Millicandela Rating30mcdWavelength - Peak568nmViewing Angle40°Termination StyleWire Leads - 10" (254.00mm)Ingress Protection-Features-	Package	-
Lamp Color Lens Color Creen  Lens Transparency Diffused  Ratings Vf (Typ), If (Max) Voltage 2.1V  Current 30mA  Panel Cutout Shape Round Panel Cutout Dimensions 0.16" (4.06mm)  Lens Style/Size Round with Domed Top, 3mm (T-1) Millicandela Rating 30mcd  Wavelength - Peak 568nm  Viewing Angle 40°  Termination Style Ingress Protection Ingress Protection Features  Green Gree	Series	PM3
Lens ColorGreenLens TransparencyDiffusedRatingsVf (Typ), If (Max)Voltage2.1VCurrent30mAPanel Cutout ShapeRoundPanel Cutout Dimensions0.16" (4.06mm)Lens Style/SizeRound with Domed Top, 3mm (T-1)Millicandela Rating30mcdWavelength - Peak568nmViewing Angle40°Termination StyleWire Leads - 10" (254.00mm)Ingress Protection-Features-	Type	LED
Lens TransparencyDiffusedRatingsVf (Typ), If (Max)Voltage2.1VCurrent30mAPanel Cutout ShapeRoundPanel Cutout Dimensions0.16" (4.06mm)Lens Style/SizeRound with Domed Top, 3mm (T-1)Millicandela Rating30mcdWavelength - Peak568nmViewing Angle40°Termination StyleWire Leads - 10" (254.00mm)Ingress Protection-Features-	Lamp Color	Green
Ratings Vf (Typ), If (Max)  Voltage 2.1V  Current 30mA  Panel Cutout Shape Round Panel Cutout Dimensions 0.16" (4.06mm)  Lens Style/Size Round with Domed Top, 3mm (T-1)  Millicandela Rating 30mcd  Wavelength - Peak 568nm  Viewing Angle 40°  Termination Style Wire Leads - 10" (254.00mm)  Ingress Protection - Features -	Lens Color	Green
Voltage 2.1V Current 30mA Panel Cutout Shape Round Panel Cutout Dimensions 0.16" (4.06mm) Lens Style/Size Round with Domed Top, 3mm (T-1) Millicandela Rating 30mcd Wavelength - Peak 568nm Viewing Angle 40° Termination Style Wire Leads - 10" (254.00mm) Ingress Protection - Features -	Lens Transparency	Diffused
Current 30mA Panel Cutout Shape Round Panel Cutout Dimensions 0.16" (4.06mm) Lens Style/Size Round with Domed Top, 3mm (T-1) Millicandela Rating 30mcd Wavelength - Peak 568nm Viewing Angle 40° Termination Style Wire Leads - 10" (254.00mm) Ingress Protection - Features -	Ratings	Vf (Typ), If (Max)
Panel Cutout Dimensions 0.16" (4.06mm)  Lens Style/Size Round with Domed Top, 3mm (T-1)  Millicandela Rating 30mcd  Wavelength - Peak 568nm  Viewing Angle 40°  Termination Style Wire Leads - 10" (254.00mm)  Ingress Protection -  Features -	Voltage	2.1V
Panel Cutout Dimensions  O.16" (4.06mm)  Lens Style/Size  Round with Domed Top, 3mm (T-1)  Millicandela Rating  30mcd  Wavelength - Peak  568nm  Viewing Angle  Termination Style  Wire Leads - 10" (254.00mm)  Ingress Protection  Features  -	Current	30mA
Lens Style/SizeRound with Domed Top, 3mm (T-1)Millicandela Rating30mcdWavelength - Peak568nmViewing Angle40°Termination StyleWire Leads - 10" (254.00mm)Ingress Protection-Features-	Panel Cutout Shape	Round
Millicandela Rating  Wavelength - Peak  568nm  Viewing Angle  Termination Style  Ingress Protection  Features  30mcd  568nm  40°  Wire Leads - 10" (254.00mm)	Panel Cutout Dimensions	0.16" (4.06mm)
Wavelength - Peak  Viewing Angle  40°  Termination Style  Ingress Protection  Features  568nm  Wire Leads - 10" (254.00mm)  -  -	Lens Style/Size	Round with Domed Top, 3mm (T-1)
Viewing Angle40°Termination StyleWire Leads - 10" (254.00mm)Ingress Protection-Features-	Millicandela Rating	30mcd
Termination Style Wire Leads - 10" (254.00mm)  Ingress Protection -  Features -	Wavelength - Peak	568nm
Ingress Protection - Features -	Viewing Angle	40°
Features -	Termination Style	Wire Leads - 10" (254.00mm)
	Ingress Protection	-
Report errors?	Features	-
		Report errors?

#### **PM3SGDW10** Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## PM3SGDW10 Payment Methods



















## **PM3SGDW10 Shipping Methods**













If you have any question about PM3SGDW10, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com