

PM5-A7B28V Information



For Reference Only

Part Number PM5-A7B28V Manufacturer Bivar Inc.

Category Optoelectronics

Panel Indicators, Pilot Lights

Description PANEL MOUNT ASSEM 8.1MM BLUE

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PM5-A7B28V Specifications

Manufacturer Part Number PM5-A7B28V Manufacturer Bivar Inc. Category Optoelectronics Panel Indicators, Pilot Lights Package - Series PM5 Type LED Lamp Color Blue Lens Color Blue Lens Transparency Fresnel Ratings AC/DC Voltage 12 V ~ 28 V Current 20mA Panel Cutout Shape Round Panel Cutout Dimensions 0.32" (8.13mm) Lens Style/Size Round with Flat Top, 7.00mm Millicandela Rating 400mcd Wavelength - Peak 465mm Viewing Angle 120° Termination Style Quick Connect - 0.110" (2.8mm) Ingress Protection IP67 Features - Report errors?		
CategoryOptoelectronicsPackage-SeriesPM5TypeLEDLamp ColorBlueLens ColorBlueLens TransparencyFresnelRatingsAC/DCVoltage12 V ~ 28 VCurrent20mAPanel Cutout ShapeRoundPanel Cutout Dimensions0.32" (8.13mm)Lens Style/SizeRound with Flat Top, 7.00mmMillicandela Rating400mcdWavelength - Peak465nmViewing Angle120°Termination StyleQuick Connect - 0.110" (2.8mm)Ingress ProtectionIP67Features-	Manufacturer Part Number	PM5-A7B28V
Package - Series PM5 Type LED Lamp Color Blue Lens Transparency Fresnel Ratings AC/DC Voltage 12 V ~ 28 V Current 20mA Panel Cutout Shape Round Panel Cutout Dimensions 0.32" (8.13mm) Lens Style/Size Round with Flat Top, 7.00mm Millicandela Rating 400mcd Wavelength - Peak 465nm Viewing Angle 120° Termination Style Ingress Protection IP67 Features - ACIDC (2.8mm) Fresnel (2.10 Ma) Panel Cutout Dimensions (3.2" (8.13mm)) Lens Style/Size Round with Flat Top, 7.00mm Millicandela Rating 400mcd Viewing Angle 120° Fermination Style Quick Connect - 0.110" (2.8mm) Ingress Protection IP67 Features	Manufacturer	Bivar Inc.
Package - Series PM5 Type LED Lamp Color Blue Lens Color Blue Lens Transparency Fresnel Ratings AC/DC Voltage 12 V ~ 28 V Current 20mA Panel Cutout Shape Round Panel Cutout Dimensions 0.32" (8.13mm) Lens Style/Size Round with Flat Top, 7.00mm Millicandela Rating 400mcd Wavelength - Peak 465nm Viewing Angle 120° Termination Style Quick Connect - 0.110" (2.8mm) Ingress Protection IP67 Features -	Category	Optoelectronics
Series PM5 Type LED Lamp Color Blue Lens Color Blue Lens Transparency Fresnel Ratings AC/DC Voltage 12 V ~ 28 V Current 20mA Panel Cutout Shape Round Panel Cutout Dimensions 0.32" (8.13mm) Lens Style/Size Round with Flat Top, 7.00mm Millicandela Rating 400mcd Wavelength - Peak 465nm Viewing Angle 120° Termination Style Quick Connect - 0.110" (2.8mm) Ingress Protection IP67 Features -		Panel Indicators, Pilot Lights
TypeLEDLamp ColorBlueLens ColorBlueLens TransparencyFresnelRatingsAC/DCVoltage12 V ~ 28 VCurrent20mAPanel Cutout ShapeRoundPanel Cutout Dimensions0.32" (8.13mm)Lens Style/SizeRound with Flat Top, 7.00mmMillicandela Rating400mcdWavelength - Peak465mmViewing Angle120°Termination StyleQuick Connect - 0.110" (2.8mm)Ingress ProtectionIP67Features-	Package	-
Lamp Color Lens Color Blue Lens Transparency Fresnel Ratings AC/DC Voltage 12 V ~ 28 V Current 20mA Panel Cutout Shape Ratings Round Panel Cutout Dimensions Lens Style/Size Round with Flat Top, 7.00mm Millicandela Rating Wavelength - Peak Viewing Angle 120° Termination Style Ingress Protection Features Blue Bue Bue Bue Bue Bue Bue Bue Bue Bue B	Series	PM5
Lens ColorBlueLens TransparencyFresnelRatingsAC/DCVoltage12 V ~ 28 VCurrent20mAPanel Cutout ShapeRoundPanel Cutout Dimensions0.32" (8.13mm)Lens Style/SizeRound with Flat Top, 7.00mmMillicandela Rating400mcdWavelength - Peak465nmViewing Angle120°Termination StyleQuick Connect - 0.110" (2.8mm)Ingress ProtectionIP67Features-	Type	LED
Lens TransparencyFresnelRatingsAC/DCVoltage12 V ~ 28 VCurrent20mAPanel Cutout ShapeRoundPanel Cutout Dimensions0.32" (8.13mm)Lens Style/SizeRound with Flat Top, 7.00mmMillicandela Rating400mcdWavelength - Peak465nmViewing Angle120°Termination StyleQuick Connect - 0.110" (2.8mm)Ingress ProtectionIP67Features-	Lamp Color	Blue
Ratings AC/DC Voltage 12 V ~ 28 V Current 20mA Panel Cutout Shape Round Panel Cutout Dimensions 0.32" (8.13mm) Lens Style/Size Round with Flat Top, 7.00mm Millicandela Rating 400mcd Wavelength - Peak 465nm Viewing Angle 120° Termination Style Quick Connect - 0.110" (2.8mm) Ingress Protection Features -	Lens Color	Blue
Voltage 12 V ~ 28 V Current 20mA Panel Cutout Shape Round Panel Cutout Dimensions 0.32" (8.13mm) Lens Style/Size Round with Flat Top, 7.00mm Millicandela Rating 400mcd Wavelength - Peak 465nm Viewing Angle 120° Termination Style Quick Connect - 0.110" (2.8mm) Ingress Protection IP67 Features -	Lens Transparency	Fresnel
Current 20mA Panel Cutout Shape Round Panel Cutout Dimensions 0.32" (8.13mm) Lens Style/Size Round with Flat Top, 7.00mm Millicandela Rating 400mcd Wavelength - Peak 465nm Viewing Angle 120° Termination Style Quick Connect - 0.110" (2.8mm) Ingress Protection IP67 Features	Ratings	AC/DC
Panel Cutout Dimensions 0.32" (8.13mm) Lens Style/Size Round with Flat Top, 7.00mm Millicandela Rating 400mcd Wavelength - Peak 465nm Viewing Angle 120° Termination Style Quick Connect - 0.110" (2.8mm) Ingress Protection Features -	Voltage	12 V ~ 28 V
Panel Cutout Dimensions 0.32" (8.13mm) Lens Style/Size Round with Flat Top, 7.00mm Millicandela Rating 400mcd Wavelength - Peak 465nm Viewing Angle 120° Termination Style Quick Connect - 0.110" (2.8mm) Ingress Protection Features -	Current	20mA
Lens Style/SizeRound with Flat Top, 7.00mmMillicandela Rating400mcdWavelength - Peak465nmViewing Angle120°Termination StyleQuick Connect - 0.110" (2.8mm)Ingress ProtectionIP67Features-	Panel Cutout Shape	Round
Millicandela Rating Wavelength - Peak Viewing Angle Termination Style Ingress Protection Features 400mcd 400mcd 400mcd 400mcd 400mcd 400mcd Ingress 400mcd Ingress 400mcd Ingress 400mcd Ingress 400mcd Ingress Ingress	Panel Cutout Dimensions	0.32" (8.13mm)
Wavelength - Peak Viewing Angle 120° Termination Style Quick Connect - 0.110" (2.8mm) Ingress Protection IP67 Features -	Lens Style/Size	Round with Flat Top, 7.00mm
Viewing Angle120°Termination StyleQuick Connect - 0.110" (2.8mm)Ingress ProtectionIP67Features-	Millicandela Rating	400mcd
Termination Style Quick Connect - 0.110" (2.8mm) Ingress Protection IP67 Features -	Wavelength - Peak	465nm
Ingress Protection IP67 Features -	Viewing Angle	120°
Features -	Termination Style	Quick Connect - 0.110" (2.8mm)
	Ingress Protection	IP67
Report errors?	Features	-
		Report errors?

PM5-A7B28V Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PM5-A7B28V Payment Methods



















PM5-A7B28V Shipping Methods













If you have any question about PM5-A7B28V, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com