

# PMN50XP,165 Information

WWW. School or Co.

For Reference Only

Part Number PMN50XP,165

Manufacturer NXP

Category Discrete Semiconductor Products

Transistors - FETs, MOSFETs - Single

**Description** MOSFET P-CH 20V 4.8A 6TSOP

Package SC-74, SOT-457

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# PMN50XP,165 Specifications

Manufacturer Part Number         PMN50XP,165           Manufacturer         NXP           Category         Discrete Semiconductor Products           Transistors - FETs, MOSFETs - Single           Package         SC-74, SOT-457           Series         TrenchMOS?           FET Type         P-Channel           Technology         MOSFET (Metal Oxide)           Drain to Source Voltage (Vdss)         20V           Current - Continuous Drain (Id) @ 25°C         4.8A (Tc)           Drive Voltage (Max Rds On, Min Rds On)         2.5V, 4.5V           Vgs(th) (Max) @ Id         950mV @ 250μA           Gate Charge (Qg) (Max) @ Vgs         10nC @ 4.5V           Input Capacitance (Ciss) (Max) @ Vds         1020pF @ 20V           Vgs (Max)         ±12V           FET Feature         -           Power Dissipation (Max)         2.2W (Tc)           Rds On (Max) @ Id, Vgs         60 mOhm @ 2.8A, 4.5V           Operating Temperature         -55°C ~ 150°C (TJ)           Mounting Type         Surface Mount           Supplier Device Package         6-TSOP           Package / Case         SC-74, SOT-457		
Category         Discrete Semiconductor Products           Transistors - FETs, MOSFETs - Single           Package         SC-74, SOT-457           Series         TrenchMOS?           FET Type         P-Channel           Technology         MOSFET (Metal Oxide)           Drain to Source Voltage (Vdss)         20V           Current - Continuous Drain (Id) @ 25°C         4.8A (Tc)           Drive Voltage (Max Rds On, Min Rds On)         2.5V, 4.5V           Vgs(th) (Max) @ Id         950mV @ 250μA           Gate Charge (Qg) (Max) @ Vgs         10nC @ 4.5V           Input Capacitance (Ciss) (Max) @ Vds         1020pF @ 20V           Vgs (Max)         ±12V           FET Feature         -           Power Dissipation (Max)         2.2W (Tc)           Rds On (Max) @ Id, Vgs         60 mOhm @ 2.8A, 4.5V           Operating Temperature         -55°C ~ 150°C (TJ)           Mounting Type         Surface Mount           Supplier Device Package         6-TSOP           Package / Case         SC-74, SOT-457	Manufacturer Part Number	PMN50XP,165
Package         SC-74, SOT-457           Series         TrenchMOS?           FET Type         P-Channel           Technology         MOSFET (Metal Oxide)           Drain to Source Voltage (Vdss)         20V           Current - Continuous Drain (Id) @ 25°C         4.8A (Tc)           Drive Voltage (Max Rds On, Min Rds On)         2.5V, 4.5V           Vgs(th) (Max) @ Id         950mV @ 250μA           Gate Charge (Qg) (Max) @ Vgs         10nC @ 4.5V           Input Capacitance (Ciss) (Max) @ Vds         1020pF @ 20V           Vgs (Max)         ±12V           FET Feature         -           Power Dissipation (Max)         2.2W (Tc)           Rds On (Max) @ Id, Vgs         60 mOhm @ 2.8A, 4.5V           Operating Temperature         -55°C ~ 150°C (TJ)           Mounting Type         Surface Mount           Supplier Device Package         6-TSOP           Package / Case         SC-74, SOT-457	Manufacturer	NXP
Package         SC-74, SOT-457           Series         TrenchMOS?           FET Type         P-Channel           Technology         MOSFET (Metal Oxide)           Drain to Source Voltage (Vdss)         20V           Current - Continuous Drain (Id) @ 25°C         4.8A (Tc)           Drive Voltage (Max Rds On, Min Rds On)         2.5V, 4.5V           Vgs(th) (Max) @ Id         950mV @ 250μA           Gate Charge (Qg) (Max) @ Vgs         10nC @ 4.5V           Input Capacitance (Ciss) (Max) @ Vds         1020pF @ 20V           Vgs (Max)         ±12V           FET Feature         -           Power Dissipation (Max)         2.2W (Tc)           Rds On (Max) @ Id, Vgs         60 mOhm @ 2.8A, 4.5V           Operating Temperature         -55°C ~ 150°C (TJ)           Mounting Type         Surface Mount           Supplier Device Package         6-TSOP           Package / Case         SC-74, SOT-457	Category	Discrete Semiconductor Products
Series         TrenchMOS?           FET Type         P-Channel           Technology         MOSFET (Metal Oxide)           Drain to Source Voltage (Vdss)         20V           Current - Continuous Drain (Id) @ 25°C         4.8A (Tc)           Drive Voltage (Max Rds On, Min Rds On)         2.5V, 4.5V           Vgs(th) (Max) @ Id         950mV @ 250μA           Gate Charge (Qg) (Max) @ Vgs         10nC @ 4.5V           Input Capacitance (Ciss) (Max) @ Vds         1020pF @ 20V           Vgs (Max)         ±12V           FET Feature         -           Power Dissipation (Max)         2.2W (Tc)           Rds On (Max) @ Id, Vgs         60 mOhm @ 2.8A, 4.5V           Operating Temperature         -55°C ~ 150°C (TJ)           Mounting Type         Surface Mount           Supplier Device Package         6-TSOP           Package / Case         SC-74, SOT-457		Transistors - FETs, MOSFETs - Single
FET TypeP-ChannelTechnologyMOSFET (Metal Oxide)Drain to Source Voltage (Vdss)20VCurrent - Continuous Drain (Id) @ 25°C4.8A (Tc)Drive Voltage (Max Rds On, Min Rds On)2.5V, 4.5VVgs(th) (Max) @ Id950mV @ 250μAGate Charge (Qg) (Max) @ Vgs10nC @ 4.5VInput Capacitance (Ciss) (Max) @ Vds1020pF @ 20VVgs (Max)±12VFET Feature-Power Dissipation (Max)2.2W (Tc)Rds On (Max) @ Id, Vgs60 mOhm @ 2.8A, 4.5VOperating Temperature-55°C ~ 150°C (TJ)Mounting TypeSurface MountSupplier Device Package6-TSOPPackage / CaseSC-74, SOT-457	Package	SC-74, SOT-457
TechnologyMOSFET (Metal Oxide)Drain to Source Voltage (Vdss)20VCurrent - Continuous Drain (Id) @ 25°C4.8A (Tc)Drive Voltage (Max Rds On, Min Rds On)2.5V, 4.5VVgs(th) (Max) @ Id950mV @ 250μAGate Charge (Qg) (Max) @ Vgs10nC @ 4.5VInput Capacitance (Ciss) (Max) @ Vds1020pF @ 20VVgs (Max)±12VFET Feature-Power Dissipation (Max)2.2W (Tc)Rds On (Max) @ Id, Vgs60 mOhm @ 2.8A, 4.5VOperating Temperature-55°C ~ 150°C (TJ)Mounting TypeSurface MountSupplier Device Package6-TSOPPackage / CaseSC-74, SOT-457	Series	TrenchMOS?
Drain to Source Voltage (Vdss)20VCurrent - Continuous Drain (Id) @ 25°C4.8A (Tc)Drive Voltage (Max Rds On, Min Rds On)2.5V, 4.5VVgs(th) (Max) @ Id950mV @ 250μAGate Charge (Qg) (Max) @ Vgs10nC @ 4.5VInput Capacitance (Ciss) (Max) @ Vds1020pF @ 20VVgs (Max)±12VFET Feature-Power Dissipation (Max)2.2W (Tc)Rds On (Max) @ Id, Vgs60 mOhm @ 2.8A, 4.5VOperating Temperature-55°C ~ 150°C (TJ)Mounting TypeSurface MountSupplier Device Package6-TSOPPackage / CaseSC-74, SOT-457	FET Type	P-Channel
Current - Continuous Drain (Id) @ 25°C  Drive Voltage (Max Rds On, Min Rds On)  2.5V, 4.5V  Vgs(th) (Max) @ Id  950mV @ 250μA  Gate Charge (Qg) (Max) @ Vgs  10nC @ 4.5V  Input Capacitance (Ciss) (Max) @ Vds  1020pF @ 20V  Vgs (Max)  ±12V  FET Feature  - Power Dissipation (Max)  Rds On (Max) @ Id, Vgs  60 mOhm @ 2.8A, 4.5V  Operating Temperature  -55°C ~ 150°C (TJ)  Mounting Type  Surface Mount  Supplier Device Package  Package / Case  SC-74, SOT-457	Technology	MOSFET (Metal Oxide)
Drive Voltage (Max Rds On, Min Rds On)2.5V, 4.5VVgs(th) (Max) @ Id950mV @ 250μAGate Charge (Qg) (Max) @ Vgs10nC @ 4.5VInput Capacitance (Ciss) (Max) @ Vds1020pF @ 20VVgs (Max)±12VFET Feature-Power Dissipation (Max)2.2W (Tc)Rds On (Max) @ Id, Vgs60 mOhm @ 2.8A, 4.5VOperating Temperature-55°C ~ 150°C (TJ)Mounting TypeSurface MountSupplier Device Package6-TSOPPackage / CaseSC-74, SOT-457	Drain to Source Voltage (Vdss)	20V
Vgs(th) (Max) @ Id  Gate Charge (Qg) (Max) @ Vgs  Input Capacitance (Ciss) (Max) @ Vds  Vgs (Max)  FET Feature  Power Dissipation (Max)  Rds On (Max) @ Id, Vgs  Operating Temperature  Supplier Device Package  Package / Case  950mV @ 250μA  10nC @ 4.5V  1020pF @ 20V  ±12V  £12V  £12V  60 mOhm @ 2.8A, 4.5V  60 mOhm @ 2.8A, 4.5V  55°C ~ 150°C (TJ)  Surface Mount  Supplier Device Package  6-TSOP  Package / Case	Current - Continuous Drain (Id) @ 25°C	4.8A (Tc)
Gate Charge (Qg) (Max) @ Vgs  Input Capacitance (Ciss) (Max) @ Vds  1020pF @ 20V  Vgs (Max)  ±12V  FET Feature  Power Dissipation (Max)  Rds On (Max) @ Id, Vgs  Operating Temperature  -55°C ~ 150°C (TJ)  Mounting Type  Surface Mount  Supplier Device Package  Package / Case  10nC @ 4.5V  1020pF @ 20V  ±12V  5-20V  5-	Drive Voltage (Max Rds On, Min Rds On)	2.5V, 4.5V
Input Capacitance (Ciss) (Max) @ Vds  Vgs (Max)  ET Feature  Power Dissipation (Max)  Rds On (Max) @ Id, Vgs  Operating Temperature  Coperating Type  Surface Mount  Supplier Device Package  Package / Case  1020pF @ 20V  1020pF	Vgs(th) (Max) @ Id	950mV @ 250μA
Vgs (Max) ±12V  FET Feature -  Power Dissipation (Max) 2.2W (Tc)  Rds On (Max) @ Id, Vgs 60 mOhm @ 2.8A, 4.5V  Operating Temperature -55°C ~ 150°C (TJ)  Mounting Type Surface Mount  Supplier Device Package 6-TSOP  Package / Case SC-74, SOT-457	Gate Charge (Qg) (Max) @ Vgs	10nC @ 4.5V
FET Feature - Power Dissipation (Max) 2.2W (Tc) Rds On (Max) @ Id, Vgs 60 mOhm @ 2.8A, 4.5V Operating Temperature -55°C ~ 150°C (TJ) Mounting Type Surface Mount Supplier Device Package 6-TSOP Package / Case SC-74, SOT-457	Input Capacitance (Ciss) (Max) @ Vds	1020pF @ 20V
Power Dissipation (Max)  Rds On (Max) @ Id, Vgs  60 mOhm @ 2.8A, 4.5V  Operating Temperature  -55°C ~ 150°C (TJ)  Mounting Type  Surface Mount  Supplier Device Package  6-TSOP  Package / Case  SC-74, SOT-457	Vgs (Max)	±12V
Rds On (Max) @ Id, Vgs60 mOhm @ 2.8A, 4.5VOperating Temperature-55°C ~ 150°C (TJ)Mounting TypeSurface MountSupplier Device Package6-TSOPPackage / CaseSC-74, SOT-457	FET Feature	-
Operating Temperature  -55°C ~ 150°C (TJ)  Mounting Type  Surface Mount  Supplier Device Package  6-TSOP  Package / Case  SC-74, SOT-457	Power Dissipation (Max)	2.2W (Tc)
Mounting Type Surface Mount Supplier Device Package 6-TSOP Package / Case SC-74, SOT-457	Rds On (Max) @ Id, Vgs	60 mOhm @ 2.8A, 4.5V
Supplier Device Package 6-TSOP Package / Case SC-74, SOT-457	Operating Temperature	-55°C ~ 150°C (TJ)
Package / Case SC-74, SOT-457	Mounting Type	Surface Mount
	Supplier Device Package	6-TSOP
Report errors?	Package / Case	SC-74, SOT-457
		Report errors?

## PMN50XP,165 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# PMN50XP,165 Payment Methods





















## PMN50XP,165 Shipping Methods













If you have any question about PMN50XP,165, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com