



PMT-24V50W1AA Information



For Reference Only

Part Number PMT-24V50W1AA

Manufacturer Delta Electronics

Category Power Supplies - External/Internal (Off-Board)

AC DC Converters

Description AC/DC CONVERTER 24V 50W

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PMT-24V50W1AA Specifications

Manufacturer Part Number PMT-24V50W1AA Manufacturer Delta Electronics Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series PMT Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2.09A Power (Watts) 50W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 86% Operating Temperature -10°C ~ 70°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 3.86" L x 3.86" W x 1.50" H (98.0mm x 98.0mm x 38.0mm)			
Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series PMT Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2.09A Power (Watts) 50W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 86% Operating Temperature -10°C ~ 70°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 3.86" L x 3.86" W x 1.50" H (98.0mm x 98.0mm x 38.0mm)	Manufacturer Part Number	PMT-24V50W1AA	
Package - Series PMT Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2.09A Power (Watts) 50W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 86% Operating Temperature -10°C ~ 70°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 3.86" L x 3.86" W x 1.50" H (98.0mm x 98.0mm x 38.0mm)	Manufacturer	Delta Electronics	
Package - Series PMT Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2.09A Power (Watts) 50W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 86% Operating Temperature -10°C ~ 70°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 3.86" L x 3.86" W x 1.50" H (98.0mm x 98.0mm x 38.0mm)	Category	Power Supplies - External/Internal (Off-Board)	
Series PMT Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2.09A Power (Watts) 50W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 86% Operating Temperature -10°C ~ 70°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 3.86" L x 3.86" W x 1.50" H (98.0mm x 98.0mm x 38.0mm)		AC DC Converters	
Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2.09A Power (Watts) 50W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 86% Operating Temperature -10°C ~ 70°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 3.86" L x 3.86" W x 1.50" H (98.0mm x 98.0mm x 38.0mm)	Package	-	
Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2.09A Power (Watts) 50W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 86% Operating Temperature -10°C ~ 70°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 3.86" L x 3.86" W x 1.50" H (98.0mm x 98.0mm x 38.0mm)	Series	PMT	
Voltage - Input85 ~ 264 VACVoltage - Output 124VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)2.09APower (Watts)50WApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency86%Operating Temperature-10°C ~ 70°C (With Derating)FeaturesAdjustable Output, Universal InputMounting TypeChassis MountSize / Dimension3.86" L x 3.86" W x 1.50" H (98.0mm x 98.0mm x 38.0mm)	Туре	Enclosed	
Voltage - Output 124VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)2.09APower (Watts)50WApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency86%Operating Temperature-10°C ~ 70°C (With Derating)FeaturesAdjustable Output, Universal InputMounting TypeChassis MountSize / Dimension3.86" L x 3.86" W x 1.50" H (98.0mm x 98.0mm x 38.0mm)	Number of Outputs	1	
Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency Operating Temperature -10°C ~ 70°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Size / Dimension	Voltage - Input	85 ~ 264 VAC	
Voltage - Output 3 Voltage - Output 4 Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 86% Operating Temperature -10°C ~ 70°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension	Voltage - Output 1	24V	
Voltage - Output 4 Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 86% Operating Temperature -10°C ~ 70°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension -10°C ~ 3.86" L x 3.86" W x 1.50" H (98.0mm x 98.0mm x 38.0mm)	Voltage - Output 2	-	
Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 86% Operating Temperature -10°C ~ 70°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 2.09A 2.09A 2.09A 2.09A 3kV (3000V) ITE (Commercial) 3kV (3000V) 86% Chassis Mount 3.86" L x 3.86" W x 1.50" H (98.0mm x 98.0mm x 38.0mm)	Voltage - Output 3	-	
Power (Watts) 50W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 86% Operating Temperature -10°C ~ 70°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 3.86" L x 3.86" W x 1.50" H (98.0mm x 98.0mm x 38.0mm)	Voltage - Output 4	-	
$ \begin{array}{llllllllllllllllllllllllllllllllllll$	Current - Output (Max)	2.09A	
Voltage - Isolation $3kV$ (3000V)Efficiency 86% Operating Temperature $-10^{\circ}\text{C} \sim 70^{\circ}\text{C}$ (With Derating)FeaturesAdjustable Output, Universal InputMounting TypeChassis MountSize / Dimension 3.86 " L x 3.86 " W x 1.50 " H (98.0mm x 98.0mm x 38.0mm)	Power (Watts)	50W	
Efficiency 86% Operating Temperature $-10^{\circ}\text{C} \sim 70^{\circ}\text{C}$ (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension $3.86^{\circ}\text{L} \times 3.86^{\circ}\text{W} \times 1.50^{\circ}\text{H}$ (98.0mm x 98.0mm x 38.0mm)	Applications	ITE (Commercial)	
Operating Temperature -10°C ~ 70°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 3.86" L x 3.86" W x 1.50" H (98.0mm x 98.0mm x 38.0mm)	Voltage - Isolation	3kV (3000V)	
Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 3.86" L x 3.86" W x 1.50" H (98.0mm x 98.0mm x 38.0mm)	Efficiency	86%	
Mounting Type Chassis Mount Size / Dimension 3.86" L x 3.86" W x 1.50" H (98.0mm x 98.0mm x 38.0mm)	Operating Temperature	-10° C ~ 70° C (With Derating)	
Size / Dimension 3.86" L x 3.86" W x 1.50" H (98.0mm x 98.0mm x 38.0mm)	Features	Adjustable Output, Universal Input	
	Mounting Type	Chassis Mount	
Report errors?	Size / Dimension	3.86" L x 3.86" W x 1.50" H (98.0mm x 98.0mm x 38.0mm)	
L.			Report errors?

PMT-24V50W1AA Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PMT-24V50W1AA Payment Methods



















PMT-24V50W1AA Shipping Methods













If you have any question about PMT-24V50W1AA, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com