



POE30U-560(G)-HT Information



For Reference Only

Part Number POE30U-560(G)-HT

Manufacturer Phihong USA

Category Power Supplies - External/Internal (Off-Board)

Power over Ethernet (PoE)

Description POE INJECTOR 30W 56V DESKTOP

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









POE30U-560(G)-HT Specifications

Voltage - Output 56V Current - Output 550mA Power (Watts) - Per Port 30W Compliance IEEE802.3af Data Rate 10/100/1000 Mbps Features OCP, OVP, SCP Operating Temperature -20°C ~ 55°C Efficiency 75%	• •		
Voltage - Output 56V Current - Output 550mA Power (Watts) - Per Port 30W Compliance IEEE802.3af Data Rate 10/100/1000 Mbps Features OCP, OVP, SCP Operating Temperature -20°C ~ 55°C Efficiency 75%	Voltage - Input	85 ~ 264 VAC	
Current - Output $550 mA$ Power (Watts) - Per Port $30W$ ComplianceIEEE802.3afData Rate $10/100/1000 Mbps$ FeaturesOCP, OVP, SCPOperating Temperature $-20^{\circ}C \sim 55^{\circ}C$ Efficiency 75%	Number of Ports	1	
Current - Output $550 mA$ Power (Watts) - Per Port $30W$ ComplianceIEEE802.3afData Rate $10/100/1000 Mbps$ FeaturesOCP, OVP, SCPOperating Temperature $-20^{\circ}C \sim 55^{\circ}C$ Efficiency 75%	Voltage - Output	56V	
Power (Watts) - Per Port $30W$ ComplianceIEEE802.3afData Rate $10/100/1000 \text{ Mbps}$ FeaturesOCP, OVP, SCPOperating Temperature $-20^{\circ}\text{C} \sim 55^{\circ}\text{C}$ Efficiency 75%		550mA	
ComplianceIEEE802.3afData Rate $10/100/1000 \text{Mbps}$ FeaturesOCP, OVP, SCPOperating Temperature $-20^{\circ}\text{C} \sim 55^{\circ}\text{C}$ Efficiency 75%	•		
Data Rate $10/100/1000 \text{Mbps}$ FeaturesOCP, OVP, SCPOperating Temperature $-20^{\circ}\text{C} \sim 55^{\circ}\text{C}$ Efficiency 75%	Power (Watts) - Per Port	30W	
Features OCP, OVP, SCP Operating Temperature $-20^{\circ}\text{C} \sim 55^{\circ}\text{C}$ Efficiency 75%	Compliance	IEEE802.3af	
Operating Temperature $-20^{\circ}\text{C} \sim 55^{\circ}\text{C}$ Efficiency 75%	Data Rate	10/100/1000 Mbps	
Efficiency 75%	Features	_	
Efficiency 75%			
·			
Mounting Type Deskton	Efficiency	75%	
Desktop	Mounting Type	Desktop	
Size / Dimension 6.53" L x 3.15" W x 1.73" H (166.0mm x 80.0mm x 44.0mm)	Size / Dimension	6.53" L x 3.15" W x 1.73" H (166.0mm x 80.0mm x 44.0mm)	
Report errors?	2-2, =		

POE30U-560(G)-HT Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

POE30U-560(G)-HT Payment Methods



















POE30U-560(G)-HT Shipping Methods













If you have any question about POE30U-560(G)-HT, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com