



PPPC031KFXC Information

www.helsener.com

For Reference Only

Part Number PPPC031KFXC

ManufacturerSullins Connector SolutionsCategoryConnectors, Interconnects

Rectangular Connectors - Headers, Receptacles,

Female Sockets

Description CONN FEMALE 3POS .1" SMD GOLD

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PPPC031KFXC Specifications

Manufacturer Part Number PPPC031KFXC Manufacturer Sullins Connector Solutions Category Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets Package - Series - Connector Type Header, Top or Bottom Entry Contact Type Female Socket Style Board to Board Number of Positions 3 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Surface Mount Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Flash Insulation Color Black Insulation Height 0.279" (7.10mm) Contact Length - Post - Operating Temperature -40°C ~ 105°C Very strip Results and the strip of the strip		
Category Connectors, Interconnects Package - Series - Connector Type Header, Top or Bottom Entry Contact Type Female Socket Style Board to Board Number of Positions 3 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Surface Mount Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Flash Insulation Color Black Insulation Height 0.279" (7.10mm) Contact Length - Post - Operating Temperature -40°C ~ 105°C	Manufacturer Part Number	PPPC031KFXC
Package - Series - Connector Type Header, Top or Bottom Entry Contact Type Female Socket Style Board to Board Number of Positions 3 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Surface Mount Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Flash Insulation Color Black Insulation Height 0.279" (7.10mm) Contact Length - Post - Operating Temperature -40°C ~ 105°C	Manufacturer	Sullins Connector Solutions
Package - Series - Connector Type Header, Top or Bottom Entry Contact Type Female Socket Style Board to Board Number of Positions 3 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Surface Mount Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Flash Insulation Color Black Insulation Height 0.279" (7.10mm) Contact Length - Post - Operating Temperature -40°C ~ 105°C	Category	Connectors, Interconnects
Series - Connector Type Header, Top or Bottom Entry Contact Type Female Socket Style Board to Board Number of Positions 3 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Surface Mount Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Flash Insulation Color Black Insulation Height 0.279" (7.10mm) Contact Length - Post - Operating Temperature -40°C ~ 105°C		Rectangular Connectors - Headers, Receptacles, Female Sockets
Connector Type Header, Top or Bottom Entry Contact Type Female Socket Style Board to Board Number of Positions 3 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Surface Mount Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Flash Insulation Color Black Insulation Height 0.279" (7.10mm) Contact Length - Post - Operating Temperature -40°C ~ 105°C	Package	-
Contact Type Female Socket Style Board to Board Number of Positions 3 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Surface Mount Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Flash Insulation Color Black Insulation Height 0.279" (7.10mm) Contact Length - Post - Operating Temperature -40°C ~ 105°C	Series	-
Style Board to Board Number of Positions 3 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Surface Mount Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Flash Insulation Color Black Insulation Height 0.279" (7.10mm) Contact Length - Post - Operating Temperature -40°C ~ 105°C	Connector Type	Header, Top or Bottom Entry
Number of Positions 3 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating Mounting Type Surface Mount Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Flash Insulation Color Black Insulation Height 0.279" (7.10mm) Contact Length - Post Operating Temperature -40°C ~ 105°C	Contact Type	Female Socket
Number of Positions Loaded Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Surface Mount Termination Solder Fastening Type Push-Pull Contact Finish - Mating Contact Finish Thickness - Mating Insulation Color Insulation Height O.279" (7.10mm) Contact Length - Post Operating Temperature All O.100" (2.54mm) Surface Mount Surface Mount Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Flash Insulation Color Black Insulation Height O.279" (7.10mm)	Style	Board to Board
Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Surface Mount Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Flash Insulation Color Black Insulation Height 0.279" (7.10mm) Contact Length - Post - Operating Temperature -40°C ~ 105°C	Number of Positions	3
Number of Rows1Row Spacing - Mating-Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingFlashInsulation ColorBlackInsulation Height0.279" (7.10mm)Contact Length - Post-Operating Temperature-40°C ~ 105°C	Number of Positions Loaded	All
Row Spacing - Mating Mounting Type Surface Mount Termination Solder Fastening Type Push-Pull Contact Finish - Mating Contact Finish Thickness - Mating Insulation Color Black Insulation Height O.279" (7.10mm) Contact Length - Post Operating Temperature -40°C ~ 105°C	Pitch - Mating	0.100" (2.54mm)
Mounting Type Surface Mount Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Insulation Color Black Insulation Height 0.279" (7.10mm) Contact Length - Post Operating Temperature -40°C ~ 105°C	Number of Rows	1
Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Flash Insulation Color Black Insulation Height 0.279" (7.10mm) Contact Length - Post - Operating Temperature -40°C ~ 105°C	Row Spacing - Mating	-
Fastening Type Contact Finish - Mating Contact Finish Thickness - Mating Insulation Color Black Insulation Height Contact Length - Post Operating Temperature Push-Pull Gold Cold Flash Flash 1. 0.279" (7.10mm) -40°C ~ 105°C	Mounting Type	Surface Mount
Contact Finish - Mating Contact Finish Thickness - Mating Flash Insulation Color Black Insulation Height 0.279" (7.10mm) Contact Length - Post Operating Temperature -40°C ~ 105°C	Termination	Solder
Contact Finish Thickness - Mating Insulation Color Black Insulation Height 0.279" (7.10mm) Contact Length - Post - Operating Temperature -40°C ~ 105°C	Fastening Type	Push-Pull
Insulation ColorBlackInsulation Height $0.279" (7.10mm)$ Contact Length - Post-Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$	Contact Finish - Mating	Gold
Insulation Height $0.279" (7.10mm)$ Contact Length - Post - Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$	Contact Finish Thickness - Mating	Flash
Contact Length - Post - Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$	Insulation Color	Black
Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$	Insulation Height	0.279" (7.10mm)
	Contact Length - Post	-
Mark 1971 All Park	Operating Temperature	-40°C ~ 105°C
Material Flammability Rating UL94 V-0	Material Flammability Rating	UL94 V-0

Contact Finish - Post	Gold
Mated Stacking Heights	-
Ingress Protection	-
Features	-
	Report errors?

PPPC031KFXC Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PPPC031KFXC Payment Methods



















PPPC031KFXC Shipping Methods













If you have any question about PPPC031KFXC, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com