

PPT0001DRW5VA

PPT0001DRW5VA Information

Heisener.com

Part Number PPT0001DRW5VA

Manufacturer Honeywell Microelectronics & Precision Sensors

Category Sensors, Transducers

Pressure Sensors, Transducers

Description PRESSURE TRANSDUCER

Package Module Cube

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PPT0001DRW5VA Specifications

Manufacturer Part Number PPT0001DRW5VA Manufacturer Honeywell Microelectronics & Precision Sensors Category Sensors, Transducers Package Module Cube Series - Pressure Type Differential Operating Pressure ±1 PSI (±6.89 kPa) Output Type Analog, RS-485 Output 0 V ~ 5 V Accuracy ±0.05% Voltage - Supply 5.5 V ~ 30 V Port Size Male - 0.13" (3.18mm) Tube, Dual Port Style Barbed Features - Termination Style Connector Maximum Pressure ±3 PSI (±20.68 kPa) Operating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package - Report errors?		
CategorySensors, TransducersPackageModule CubeSeries-Pressure TypeDifferentialOperating Pressure±1 PSI (±6.89 kPa)Output TypeAnalog, RS-485Output0 V ~ 5 VAccuracy±0.05%Voltage - Supply5.5 V ~ 30 VPort SizeMale - 0.13" (3.18mm) Tube, DualPort StyleBarbedFeatures-Termination StyleConnectorMaximum Pressure±3 PSI (±20.68 kPa)Operating Temperature-40°C ~ 85°CPackage / CaseModule CubeSupplier Device Package-	Manufacturer Part Number	PPT0001DRW5VA
Package Module Cube Series - Pressure Type Differential Operating Pressure	Manufacturer	Honeywell Microelectronics & Precision Sensors
PackageModule CubeSeries-Pressure TypeDifferentialOperating Pressure±1 PSI (±6.89 kPa)Output TypeAnalog, RS-485Output0 V ~ 5 VAccuracy±0.05%Voltage - Supply5.5 V ~ 30 VPort SizeMale - 0.13" (3.18mm) Tube, DualPort StyleBarbedFeatures-Termination StyleConnectorMaximum Pressure±3 PSI (±20.68 kPa)Operating Temperature-40°C ~ 85°CPackage / CaseModule CubeSupplier Device Package-	Category	Sensors, Transducers
Series - Pressure Type Differential Operating Pressure ±1 PSI (±6.89 kPa) Output Type Analog, RS-485 Output 0 V ~ 5 V Accuracy ±0.05% Voltage - Supply 5.5 V ~ 30 V Port Size Male - 0.13" (3.18mm) Tube, Dual Port Style Barbed Features - Termination Style Connector Maximum Pressure ±3 PSI (±20.68 kPa) Operating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package -		Pressure Sensors, Transducers
Pressure Type Operating Pressure ±1 PSI (±6.89 kPa) Output Type Analog, RS-485 Output 0 V ~ 5 V Accuracy ±0.05% Voltage - Supply 5.5 V ~ 30 V Port Size Male - 0.13" (3.18mm) Tube, Dual Port Style Barbed Features - Termination Style Connector Maximum Pressure ±3 PSI (±20.68 kPa) Operating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package	Package	Module Cube
Operating Pressure $\pm 1 \text{ PSI } (\pm 6.89 \text{ kPa})$ Output Type Analog, RS-485 Output $0 \text{ V} \sim 5 \text{ V}$ Accuracy $\pm 0.05\%$ Voltage - Supply $5.5 \text{ V} \sim 30 \text{ V}$ Port Size Male - 0.13 " (3.18mm) Tube, Dual Port Style Barbed Features - Termination Style Connector Maximum Pressure $\pm 3 \text{ PSI } (\pm 20.68 \text{ kPa})$ Operating Temperature $\pm 40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case Module Cube Supplier Device Package -	Series	-
Output TypeAnalog, RS-485Output $0 \text{ V} \sim 5 \text{ V}$ Accuracy $\pm 0.05\%$ Voltage - Supply $5.5 \text{ V} \sim 30 \text{ V}$ Port SizeMale - 0.13 " (3.18mm) Tube, DualPort StyleBarbedFeatures-Termination StyleConnectorMaximum Pressure $\pm 3 \text{ PSI } (\pm 20.68 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / CaseModule CubeSupplier Device Package-	Pressure Type	Differential
Output $0 \text{ V} \sim 5 \text{ V}$ Accuracy $\pm 0.05\%$ Voltage - Supply $5.5 \text{ V} \sim 30 \text{ V}$ Port SizeMale - 0.13 " (3.18mm) Tube, DualPort StyleBarbedFeatures-Termination StyleConnectorMaximum Pressure $\pm 3 \text{ PSI } (\pm 20.68 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / CaseModule CubeSupplier Device Package-	Operating Pressure	±1 PSI (±6.89 kPa)
Accuracy ±0.05% Voltage - Supply 5.5 V ~ 30 V Port Size Male - 0.13" (3.18mm) Tube, Dual Port Style Barbed Features - Termination Style Connector Maximum Pressure ±3 PSI (±20.68 kPa) Operating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package -	Output Type	Analog, RS-485
Voltage - Supply $5.5 \text{ V} \sim 30 \text{ V}$ Port Size $Male - 0.13'' (3.18 \text{mm}) \text{ Tube, Dual}$ Port Style $Barbed$ Features - Termination Style $Connector$ Maximum Pressure $\pm 3 \text{ PSI } (\pm 20.68 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case $Module \text{ Cube}$ Supplier Device Package $-$	Output	0 V ~ 5 V
Port Size Male - 0.13" (3.18mm) Tube, Dual Port Style Barbed Features - Termination Style Connector Maximum Pressure ±3 PSI (±20.68 kPa) Operating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package -	Accuracy	±0.05%
Port Style Barbed Features - Termination Style Connector Maximum Pressure ±3 PSI (±20.68 kPa) Operating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package -	Voltage - Supply	5.5 V ~ 30 V
Features - Termination Style Connector Maximum Pressure ±3 PSI (±20.68 kPa) Operating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package -	Port Size	Male - 0.13" (3.18mm) Tube, Dual
Termination StyleConnectorMaximum Pressure ± 3 PSI (± 20.68 kPa)Operating Temperature -40° C ~ 85° CPackage / CaseModule CubeSupplier Device Package-	Port Style	Barbed
Maximum Pressure ± 3 PSI (± 20.68 kPa)Operating Temperature -40° C $\sim 85^{\circ}$ CPackage / CaseModule CubeSupplier Device Package-	Features	-
Operating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package -	Termination Style	Connector
Package / Case Module Cube Supplier Device Package -	Maximum Pressure	±3 PSI (±20.68 kPa)
Supplier Device Package -	Operating Temperature	-40°C ~ 85°C
	Package / Case	Module Cube
Report errors?	Supplier Device Package	-
		Report errors?

PPT0001DRW5VA Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PPT0001DRW5VA Payment Methods



















PPT0001DRW5VA Shipping Methods













If you have any question about PPT0001DRW5VA, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com