



PPT0002GFR5VA Information

Heisener.com

Part Number PPT0002GFR5VA

Manufacturer Honeywell Microelectronics & Precision Sensors

Category Sensors, Transducers

Pressure Sensors, Transducers

Description PRESSURE TRANSDUCER

Package Module Cube

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PPT0002GFR5VA Specifications

Manufacturer Part Number PPT0002GFR5VA Manufacturer Honeywell Microelectronics & Precision Sensors Category Sensors, Transducers Package Module Cube Series - Pressure Type Vented Gauge Operating Pressure 2 PSI (13.79 kPa) Output Type Analog, RS-485 Output 0 V ~ 5 V Accuracy ±0.05% Voltage - Supply 5.5 V ~ 30 V Port Size Male - 0.13" (3.18mm) Tube, Filter Port Style Barbed, Filtered Features - Termination Style Connector Maximum Pressure 6 PSI (41.37 kPa) Operating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package - Report errors?		
CategorySensors, TransducersPackageModule CubeSeries-Pressure TypeVented GaugeOperating Pressure2 PSI (13.79 kPa)Output TypeAnalog, RS-485Output0 V ~ 5 VAccuracy±0.05%Voltage - Supply5.5 V ~ 30 VPort SizeMale - 0.13" (3.18mm) Tube, FilterPort StyleBarbed, FilteredFeatures-Termination StyleConnectorMaximum Pressure6 PSI (41.37 kPa)Operating Temperature-40°C ~ 85°CPackage / CaseModule CubeSupplier Device Package-	Manufacturer Part Number	PPT0002GFR5VA
Package Module Cube Series - Pressure Type Vented Gauge Operating Pressure 2 PSI (13.79 kPa) Output Type Analog, RS-485 Output 0 V ~ 5 V Accuracy ±0.05% Voltage - Supply 5.5 V ~ 30 V Port Size Male - 0.13" (3.18mm) Tube, Filter Port Style Barbed, Filtered Features - Termination Style Connector Maximum Pressure 6 PSI (41.37 kPa) Operating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package -	Manufacturer	Honeywell Microelectronics & Precision Sensors
PackageModule CubeSeries-Pressure TypeVented GaugeOperating Pressure2 PSI (13.79 kPa)Output TypeAnalog, RS-485Output0 V ~ 5 VAccuracy±0.05%Voltage - Supply5.5 V ~ 30 VPort SizeMale - 0.13" (3.18mm) Tube, FilterPort StyleBarbed, FilteredFeatures-Termination StyleConnectorMaximum Pressure6 PSI (41.37 kPa)Operating Temperature-40°C ~ 85°CPackage / CaseModule CubeSupplier Device Package-	Category	Sensors, Transducers
Series - Pressure Type Vented Gauge Operating Pressure 2 PSI (13.79 kPa) Output Type Analog, RS-485 Output 0 V ~ 5 V Accuracy ±0.05% Voltage - Supply 5.5 V ~ 30 V Port Size Male - 0.13" (3.18mm) Tube, Filter Port Style Barbed, Filtered Features - Termination Style Connector Maximum Pressure 6 PSI (41.37 kPa) Operating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package -		Pressure Sensors, Transducers
Pressure Type Vented Gauge Operating Pressure 2 PSI (13.79 kPa) Output Type Analog, RS-485 Output 0 V ~ 5 V Accuracy ±0.05% Voltage - Supply 5.5 V ~ 30 V Port Size Male - 0.13" (3.18mm) Tube, Filter Port Style Barbed, Filtered Features - Termination Style Connector Maximum Pressure 6 PSI (41.37 kPa) Operating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package -	Package	Module Cube
Operating Pressure $2 \text{ PSI } (13.79 \text{ kPa})$ Output TypeAnalog, RS-485Output $0 \text{ V} \sim 5 \text{ V}$ Accuracy $\pm 0.05\%$ Voltage - Supply $5.5 \text{ V} \sim 30 \text{ V}$ Port SizeMale - 0.13 " (3.18mm) Tube, FilterPort StyleBarbed, FilteredFeatures-Termination StyleConnectorMaximum Pressure $6 \text{ PSI } (41.37 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / CaseModule CubeSupplier Device Package-	Series	-
Output TypeAnalog, RS-485Output $0 \text{ V} \sim 5 \text{ V}$ Accuracy $\pm 0.05\%$ Voltage - Supply $5.5 \text{ V} \sim 30 \text{ V}$ Port SizeMale - 0.13 " (3.18mm) Tube, FilterPort StyleBarbed, FilteredFeatures-Termination StyleConnectorMaximum Pressure $6 \text{ PSI } (41.37 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / CaseModule CubeSupplier Device Package-	Pressure Type	Vented Gauge
Output $0 \text{ V} \sim 5 \text{ V}$ Accuracy $\pm 0.05\%$ Voltage - Supply $5.5 \text{ V} \sim 30 \text{ V}$ Port SizeMale - 0.13 " (3.18mm) Tube, FilterPort StyleBarbed, FilteredFeatures-Termination StyleConnectorMaximum Pressure $6 \text{ PSI } (41.37 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / CaseModule CubeSupplier Device Package-	Operating Pressure	2 PSI (13.79 kPa)
Accuracy ±0.05% Voltage - Supply 5.5 V ~ 30 V Port Size Male - 0.13" (3.18mm) Tube, Filter Port Style Barbed, Filtered Features - Connector Maximum Pressure 6 PSI (41.37 kPa) Operating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package -	Output Type	Analog, RS-485
Voltage - Supply $5.5 \text{ V} \sim 30 \text{ V}$ Port Size $Male - 0.13'' (3.18 \text{mm})$ Tube, Filter Port Style $Barbed$, Filtered Features - Termination Style $Connector$ Maximum Pressure $Connector$ Maximum Pressure $Connector$ Operating Temperature $Connector$ Package / Case $Connector$ Module Cube Supplier Device Package $Connector$	Output	0 V ~ 5 V
Port Size Male - 0.13" (3.18mm) Tube, Filter Port Style Barbed, Filtered Features - Termination Style Connector Maximum Pressure 6 PSI (41.37 kPa) Operating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package -	Accuracy	±0.05%
Port Style Barbed, Filtered Features - Termination Style Connector Maximum Pressure 6 PSI (41.37 kPa) Operating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package -	Voltage - Supply	5.5 V ~ 30 V
Features - Termination Style Connector Maximum Pressure 6 PSI (41.37 kPa) Operating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package -	Port Size	Male - 0.13" (3.18mm) Tube, Filter
Termination Style Connector Maximum Pressure 6 PSI (41.37 kPa) Operating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package -	Port Style	Barbed, Filtered
Maximum Pressure6 PSI (41.37 kPa)Operating Temperature-40°C ~ 85°CPackage / CaseModule CubeSupplier Device Package-	Features	-
Operating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package -	Termination Style	Connector
Package / Case Module Cube Supplier Device Package -	Maximum Pressure	6 PSI (41.37 kPa)
Supplier Device Package -	Operating Temperature	-40°C ~ 85°C
	Package / Case	Module Cube
Report errors?	Supplier Device Package	-
		Report errors?

PPT0002GFR5VA Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PPT0002GFR5VA Payment Methods



















PPT0002GFR5VA Shipping Methods













If you have any question about PPT0002GFR5VA, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com