



PPT0010DWF2VB Information

Heisener.com

Part Number PPT0010DWF2VB

Manufacturer Honeywell Microelectronics & Precision Sensors

Category Sensors, Transducers

Pressure Sensors, Transducers

Description PRESSURE TRANSDUCER

Package Module Cube

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PPT0010DWF2VB Specifications

Manufacturer PPT0010DWF2VB Manufacturer Honeywell Microelectronics & Precision Sensors Category Sensors, Transducers Package Module Cube Series - Pressure Type Differential Operating Pressure ±10 PSI (±68.95 kPa) Output Type Analog, RS-232 Output 0 V ~ 5 V Accuracy ±0.05% Voltage - Supply 5.5 V ~ 30 V Port Size Male - 0.13" (3.18mm) Tube, Filter Port Style Barbed, Filtered Features - Termination Style Connector Maximum Pressure ±30 PSI (±206.84 kPa) Operating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package -		
CategorySensors, TransducersPackageModule CubeSeries-Pressure TypeDifferentialOperating Pressure±10 PSI (±68.95 kPa)Output TypeAnalog, RS-232Output0 V ~ 5 VAccuracy±0.05%Voltage - Supply5.5 V ~ 30 VPort SizeMale - 0.13" (3.18mm) Tube, FilterPort StyleBarbed, FilteredFeatures-Termination StyleConnectorMaximum Pressure±30 PSI (±206.84 kPa)Operating Temperature+40°C ~ 85°CPackage / CaseModule CubeSupplier Device Package-	Manufacturer Part Number	PPT0010DWF2VB
Package Module Cube Series - Pressure Type Differential Operating Pressure Output Type Analog, RS-232 Output 0 V ~ 5 V Accuracy ±0.05% Voltage - Supply 5.5 V ~ 30 V Port Size Male - 0.13" (3.18mm) Tube, Filter Port Style Barbed, Filtered Features - Termination Style Connector Maximum Pressure ±30 PSI (±206.84 kPa) Operating Temperature +40°C ~ 85°C Package / Case Module Cube Supplier Device Package	Manufacturer	Honeywell Microelectronics & Precision Sensors
Package Module Cube Series - Pressure Type Differential Operating Pressure ±10 PSI (±68.95 kPa) Output Type Analog, RS-232 Output 0 V ~ 5 V Accuracy ±0.05% Voltage - Supply 5.5 V ~ 30 V Port Size Male - 0.13" (3.18mm) Tube, Filter Port Style Barbed, Filtered Features - Termination Style Connector Maximum Pressure ±30 PSI (±206.84 kPa) Operating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package -	Category	Sensors, Transducers
Series - Pressure Type Differential Operating Pressure ±10 PSI (±68.95 kPa) Output Type Analog, RS-232 Output 0 V ~ 5 V Accuracy ±0.05% Voltage - Supply 5.5 V ~ 30 V Port Size Male - 0.13" (3.18mm) Tube, Filter Port Style Barbed, Filtered Features - Termination Style Connector Maximum Pressure ±30 PSI (±206.84 kPa) Operating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package -		Pressure Sensors, Transducers
Pressure Type Differential Operating Pressure ±10 PSI (±68.95 kPa) Output Type Analog, RS-232 Output 0 V ~ 5 V Accuracy ±0.05% Voltage - Supply 5.5 V ~ 30 V Port Size Male - 0.13" (3.18mm) Tube, Filter Port Style Barbed, Filtered Features - Termination Style Connector Maximum Pressure ±30 PSI (±206.84 kPa) Operating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package -	Package	Module Cube
Operating Pressure ± 10 PSI (± 68.95 kPa) Output Type Analog, RS-232 Output $0 \text{ V} \sim 5 \text{ V}$ Accuracy $\pm 0.05\%$ Voltage - Supply $5.5 \text{ V} \sim 30 \text{ V}$ Port Size Male - 0.13 " (3.18 mm) Tube, Filter Port Style Barbed, Filtered Features - Termination Style Connector Maximum Pressure $\pm 30 \text{ PSI}$ ($\pm 206.84 \text{ kPa}$) Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case Module Cube Supplier Device Package $-$	Series	-
Output TypeAnalog, RS-232Output $0 \text{ V} \sim 5 \text{ V}$ Accuracy $\pm 0.05\%$ Voltage - Supply $5.5 \text{ V} \sim 30 \text{ V}$ Port SizeMale - 0.13 " (3.18mm) Tube, FilterPort StyleBarbed, FilteredFeatures-Termination StyleConnectorMaximum Pressure $\pm 30 \text{ PSI } (\pm 206.84 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / CaseModule CubeSupplier Device Package-	Pressure Type	Differential
Output $0 \text{ V} \sim 5 \text{ V}$ Accuracy $\pm 0.05\%$ Voltage - Supply $5.5 \text{ V} \sim 30 \text{ V}$ Port Size $\text{Male - 0.13'' (3.18mm) Tube, Filter}$ Port Style Barbed, Filtered Features - Termination Style Connector Maximum Pressure $\pm 30 \text{ PSI } (\pm 206.84 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case Module Cube Supplier Device Package $-$	Operating Pressure	±10 PSI (±68.95 kPa)
Accuracy ±0.05% Voltage - Supply 5.5 V ~ 30 V Port Size Male - 0.13" (3.18mm) Tube, Filter Port Style Barbed, Filtered Features - Connector Maximum Pressure ±30 PSI (±206.84 kPa) Operating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package -	Output Type	Analog, RS-232
Voltage - Supply $5.5 \text{ V} \sim 30 \text{ V}$ Port Size $\text{Male} - 0.13'' (3.18 \text{mm}) \text{ Tube}, \text{ Filter}$ Port Style $\text{Barbed}, \text{ Filtered}$ Features - Connector Termination Style Connector Maximum Pressure $\pm 30 \text{ PSI} (\pm 206.84 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case Module Cube Supplier Device Package $-$	Output	0 V ~ 5 V
Port Size Male - 0.13" (3.18mm) Tube, Filter Port Style Barbed, Filtered Features - Termination Style Connector Maximum Pressure ±30 PSI (±206.84 kPa) Operating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package -	Accuracy	$\pm 0.05\%$
Port Style Barbed, Filtered Features - Termination Style Connector Maximum Pressure ±30 PSI (±206.84 kPa) Operating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package -	Voltage - Supply	5.5 V ~ 30 V
Features - Connector Maximum Pressure ±30 PSI (±206.84 kPa) Operating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package -	Port Size	Male - 0.13" (3.18mm) Tube, Filter
Termination StyleConnectorMaximum Pressure $\pm 30 \text{ PSI } (\pm 206.84 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / CaseModule CubeSupplier Device Package-	Port Style	Barbed, Filtered
Maximum Pressure $\pm 30 \text{ PSI } (\pm 206.84 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / CaseModule CubeSupplier Device Package-	Features	-
Operating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package -	Termination Style	Connector
Package / Case Module Cube Supplier Device Package -	Maximum Pressure	±30 PSI (±206.84 kPa)
Supplier Device Package -	Operating Temperature	-40°C ~ 85°C
	Package / Case	Module Cube
Report errors?	Supplier Device Package	-
Report circus.		Report errors?

PPT0010DWF2VB Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PPT0010DWF2VB Payment Methods



















PPT0010DWF2VB Shipping Methods













If you have any question about PPT0010DWF2VB, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com