



PPT0010GXX2VB Information

Heisener.com

Part Number PPT0010GXX2VB

Manufacturer Honeywell Microelectronics & Precision Sensors

Category Sensors, Transducers

Pressure Sensors, Transducers

Description PRESSURE TRANSDUCER

Package Module Cube

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PPT0010GXX2VB Specifications

Manufacturer Part Number PPT0010GXX2VB Manufacturer Honeywell Microelectronics & Precision Sensors Category Sensors, Transducers Package Module Cube Series - Pressure Type Vented Gauge Operating Pressure 10 PSI (68.95 kPa) Output Type Analog, RS-232 Output 0 V ~ 5 V Accuracy ±0.05% Voltage - Supply 5.5 V ~ 30 V Port Size Female - 1/8" (3.18mm) Swagelok?, Dual Port Style Threaded Features - Termination Style Connector Maximum Pressure 30 PSI (206.84 kPa) Operating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package - Report errors?		
CategorySensors, TransducersPackageModule CubeSeries-Pressure TypeVented GaugeOperating Pressure10 PSI (68.95 kPa)Output TypeAnalog, RS-232Output0 V ~ 5 VAccuracy±0.05%Voltage - Supply5.5 V ~ 30 VPort SizeFemale - 1/8" (3.18mm) Swagelok?, DualPort StyleThreadedFeatures-Termination StyleConnectorMaximum Pressure30 PSI (206.84 kPa)Operating Temperature-40°C ~ 85°CPackage / CaseModule CubeSupplier Device Package-	Manufacturer Part Number	PPT0010GXX2VB
Package Module Cube Series - Pressure Type Vented Gauge Operating Pressure Output Type Analog, RS-232 Output 0 V ~ 5 V Accuracy ±0.05% Voltage - Supply 5.5 V ~ 30 V Port Size Female - 1/8" (3.18mm) Swagelok?, Dual Port Style Threaded Features - Termination Style Connector Maximum Pressure 30 PSI (206.84 kPa) Operating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package Pressure Sensors, Transducers Module Cube Poessure Sensors, Transducers Module Cube Perssure Sensors, Transducers ### Module Cube Package / Case	Manufacturer	Honeywell Microelectronics & Precision Sensors
Package Module Cube Series - Pressure Type Vented Gauge Operating Pressure 10 PSI (68.95 kPa) Output Type Analog, RS-232 Output 0 V ~ 5 V Accuracy ±0.05% Voltage - Supply 5.5 V ~ 30 V Port Size Female - 1/8" (3.18mm) Swagelok?, Dual Port Style Threaded Features - Termination Style Connector Maximum Pressure 30 PSI (206.84 kPa) Operating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package -	Category	Sensors, Transducers
Series - Pressure Type Vented Gauge Operating Pressure 10 PSI (68.95 kPa) Output Type Analog, RS-232 Output 0 V ~ 5 V Accuracy ±0.05% Voltage - Supply 5.5 V ~ 30 V Port Size Female - 1/8" (3.18mm) Swagelok?, Dual Port Style Threaded Features - Termination Style Connector Maximum Pressure 30 PSI (206.84 kPa) Operating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package -		Pressure Sensors, Transducers
Pressure Type Vented Gauge Operating Pressure 10 PSI (68.95 kPa) Output Type Analog, RS-232 Output 0 V ~ 5 V Accuracy ±0.05% Voltage - Supply 5.5 V ~ 30 V Port Size Female - 1/8" (3.18mm) Swagelok?, Dual Port Style Threaded Features - Termination Style Connector Maximum Pressure 30 PSI (206.84 kPa) Operating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package -	Package	Module Cube
Operating Pressure 10 PSI (68.95 kPa) Output Type Analog, RS-232 Output 0 V ~ 5 V Accuracy ±0.05% Voltage - Supply 5.5 V ~ 30 V Port Size Female - 1/8" (3.18mm) Swagelok?, Dual Port Style Threaded Features - Termination Style Connector Maximum Pressure 30 PSI (206.84 kPa) Operating Temperature -40°C ~ 85°C Package / Case Supplier Device Package - 10 PSI (68.95 kPa) 10 PSI (68.95 kPa) 6 V ~ 5 V Consector Analog, RS-232 10 V 5 V ~ 5 V 40.05% Consector Module Cube Supplier Device Package	Series	-
Output TypeAnalog, RS-232Output $0 \text{ V} \sim 5 \text{ V}$ Accuracy $\pm 0.05\%$ Voltage - Supply $5.5 \text{ V} \sim 30 \text{ V}$ Port SizeFemale - $1/8$ " (3.18mm) Swagelok?, DualPort StyleThreadedFeatures-Termination StyleConnectorMaximum Pressure $30 \text{ PSI } (206.84 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / CaseModule CubeSupplier Device Package-	Pressure Type	Vented Gauge
Output $0 \text{ V} \sim 5 \text{ V}$ Accuracy $\pm 0.05\%$ Voltage - Supply $5.5 \text{ V} \sim 30 \text{ V}$ Port SizeFemale - $1/8$ " (3.18mm) Swagelok?, DualPort StyleThreadedFeatures-Termination StyleConnectorMaximum Pressure $30 \text{ PSI } (206.84 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / CaseModule CubeSupplier Device Package-	Operating Pressure	10 PSI (68.95 kPa)
Accuracy ±0.05% Voltage - Supply 5.5 V ~ 30 V Port Size Female - 1/8" (3.18mm) Swagelok?, Dual Port Style Threaded Features - Connector Maximum Pressure 30 PSI (206.84 kPa) Operating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package -	Output Type	Analog, RS-232
Voltage - Supply $5.5 \text{ V} \sim 30 \text{ V}$ Port SizeFemale - $1/8$ " (3.18mm) Swagelok?, DualPort StyleThreadedFeatures-Termination StyleConnectorMaximum Pressure $30 \text{ PSI } (206.84 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / CaseModule CubeSupplier Device Package-	Output	0 V ~ 5 V
Port Size Female - 1/8" (3.18mm) Swagelok?, Dual Port Style Threaded Features - Termination Style Connector Maximum Pressure 30 PSI (206.84 kPa) Operating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package -	Accuracy	$\pm 0.05\%$
Port Style Threaded Features - Termination Style Connector Maximum Pressure 30 PSI (206.84 kPa) Operating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package -	Voltage - Supply	5.5 V ~ 30 V
Features - Connector Maximum Pressure 30 PSI (206.84 kPa) Operating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package -	Port Size	Female - 1/8" (3.18mm) Swagelok?, Dual
Termination Style Connector Maximum Pressure 30 PSI (206.84 kPa) Operating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package -	Port Style	Threaded
Maximum Pressure30 PSI (206.84 kPa)Operating Temperature-40°C ~ 85°CPackage / CaseModule CubeSupplier Device Package-	Features	-
Operating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package -	Termination Style	Connector
Package / Case Module Cube Supplier Device Package -	Maximum Pressure	30 PSI (206.84 kPa)
Supplier Device Package -	Operating Temperature	-40°C ~ 85°C
	Package / Case	Module Cube
Report errors?	Supplier Device Package	-
		Report errors?

PPT0010GXX2VB Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PPT0010GXX2VB Payment Methods



















PPT0010GXX2VB Shipping Methods













If you have any question about PPT0010GXX2VB, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com