



PPT0020DXF2VB Information

Heisener.com

Part Number PPT0020DXF2VB

Manufacturer Honeywell Microelectronics & Precision Sensors

Category Sensors, Transducers

Pressure Sensors, Transducers

Description PRESSURE TRANSDUCER

Package Module Cube

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PPT0020DXF2VB Specifications

Manufacturer Part NumberPPT0020DXF2VBManufacturerHoneywell Microelectronics & Precision SensorsCategorySensors, TransducersPackageModule CubeSeries-Pressure TypeDifferentialOperating Pressure±20 PSI (±137.9 kPa)Output TypeAnalog, RS-232Output0 V ~ 5 VAccuracy±0.05%Voltage - Supply5.5 V ~ 30 VPort SizeFemale - 1/8" (3.18mm) Swagelok?, FilterPort StyleFiltered, ThreadedFeatures-Termination StyleConnectorMaximum Pressure±60 PSI (±413.69 kPa)Operating Temperature-40°C ~ 85°CPackage / CaseModule CubeSupplier Device Package-		
Category Sensors, Transducers Package Module Cube Series - Pressure Type Differential Operating Pressure ±20 PSI (±137.9 kPa) Output Type Analog, RS-232 Output 0 V ~ 5 V Accuracy ±0.05% Voltage - Supply 5.5 V ~ 30 V Port Size Female - 1/8" (3.18mm) Swagelok?, Filter Port Style Filtered, Threaded Features - Termination Style Connector Maximum Pressure ±60 PSI (±413.69 kPa) Operating Temperature -40°C ~ 85°C Package / Case Module Cube	Manufacturer Part Number	PPT0020DXF2VB
Package Module Cube Series - Pressure Type Differential Operating Pressure	Manufacturer	Honeywell Microelectronics & Precision Sensors
PackageModule CubeSeries-Pressure TypeDifferentialOperating Pressure $\pm 20 \text{ PSI } (\pm 137.9 \text{ kPa})$ Output TypeAnalog, RS-232Output $0 \text{ V} \sim 5 \text{ V}$ Accuracy $\pm 0.05\%$ Voltage - Supply $5.5 \text{ V} \sim 30 \text{ V}$ Port SizeFemale - $1/8$ " (3.18mm) Swagelok?, FilterPort StyleFiltered, ThreadedFeatures-Termination StyleConnectorMaximum Pressure $\pm 60 \text{ PSI } (\pm 413.69 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / CaseModule Cube	Category	Sensors, Transducers
Series-Pressure TypeDifferentialOperating Pressure±20 PSI (±137.9 kPa)Output TypeAnalog, RS-232Output0 V ~ 5 VAccuracy±0.05%Voltage - Supply5.5 V ~ 30 VPort SizeFemale - 1/8" (3.18mm) Swagelok?, FilterPort StyleFiltered, ThreadedFeatures-Termination StyleConnectorMaximum Pressure±60 PSI (±413.69 kPa)Operating Temperature-40°C ~ 85°CPackage / CaseModule Cube		Pressure Sensors, Transducers
Pressure Type Differential Operating Pressure $\pm 20 \text{ PSI } (\pm 137.9 \text{ kPa})$ Output Type Analog, RS-232 Output $0 \text{ V} \sim 5 \text{ V}$ Accuracy $\pm 0.05\%$ Voltage - Supply $5.5 \text{ V} \sim 30 \text{ V}$ Port Size Female - $1/8$ " $(3.18 \text{ mm}) \text{ Swagelok?, Filter}$ Port Style Filtered, Threaded Features - Termination Style Connector Maximum Pressure $\pm 60 \text{ PSI } (\pm 413.69 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case Module Cube	Package	Module Cube
Operating Pressure ± 20 PSI $(\pm 137.9 \text{ kPa})$ Output Type Analog, RS-232 Output $0 \text{ V} \sim 5 \text{ V}$ Accuracy $\pm 0.05\%$ Voltage - Supply $5.5 \text{ V} \sim 30 \text{ V}$ Port Size Female - $1/8$ " (3.18mm) Swagelok?, Filter Port Style Filtered, Threaded Features - Termination Style Connector Maximum Pressure ± 60 PSI $(\pm 413.69 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case Module Cube	Series	-
Output TypeAnalog, RS-232Output $0 \text{ V} \sim 5 \text{ V}$ Accuracy $\pm 0.05\%$ Voltage - Supply $5.5 \text{ V} \sim 30 \text{ V}$ Port SizeFemale - $1/8$ " (3.18mm) Swagelok?, FilterPort StyleFiltered, ThreadedFeatures-Termination StyleConnectorMaximum Pressure $\pm 60 \text{ PSI } (\pm 413.69 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / CaseModule Cube	Pressure Type	Differential
Output $0 \text{ V} \sim 5 \text{ V}$ Accuracy $\pm 0.05\%$ Voltage - Supply $5.5 \text{ V} \sim 30 \text{ V}$ Port SizeFemale - $1/8$ " (3.18mm) Swagelok?, FilterPort StyleFiltered, ThreadedFeatures-Termination StyleConnectorMaximum Pressure $\pm 60 \text{ PSI } (\pm 413.69 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / CaseModule Cube	Operating Pressure	±20 PSI (±137.9 kPa)
Accuracy $\pm 0.05\%$ Voltage - Supply $5.5 \text{ V} \sim 30 \text{ V}$ Port Size Female - $1/8$ " (3.18mm) Swagelok?, Filter Port Style Filtered, Threaded Features - Termination Style Connector Maximum Pressure $\pm 60 \text{ PSI } (\pm 413.69 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case Module Cube	Output Type	Analog, RS-232
Voltage - Supply $5.5 \text{ V} \sim 30 \text{ V}$ Port Size Female - 1/8" (3.18mm) Swagelok?, Filter Port Style Filtered, Threaded Features - Connector Maximum Pressure $\pm 60 \text{ PSI} (\pm 413.69 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case Module Cube	Output	0 V ~ 5 V
Port Size Female - 1/8" (3.18mm) Swagelok?, Filter Port Style Filtered, Threaded - Termination Style Connector Maximum Pressure ±60 PSI (±413.69 kPa) Operating Temperature -40°C ~ 85°C Package / Case Module Cube	Accuracy	±0.05%
Port Style Filtered, Threaded Features - Termination Style Connector Maximum Pressure ±60 PSI (±413.69 kPa) Operating Temperature -40°C ~ 85°C Package / Case Module Cube	Voltage - Supply	5.5 V ~ 30 V
Features - Connector Maximum Pressure $\pm 60 \text{ PSI } (\pm 413.69 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case Module Cube	Port Size	Female - 1/8" (3.18mm) Swagelok?, Filter
Termination Style Connector Maximum Pressure $\pm 60 \text{ PSI } (\pm 413.69 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case Module Cube	Port Style	Filtered, Threaded
Maximum Pressure ± 60 PSI (± 413.69 kPa)Operating Temperature -40° C ~ 85° CPackage / CaseModule Cube	Features	-
Operating Temperature -40°C ~ 85°C Package / Case Module Cube	Termination Style	Connector
Package / Case Module Cube	Maximum Pressure	±60 PSI (±413.69 kPa)
	Operating Temperature	-40°C ~ 85°C
Supplier Device Package -	Package / Case	Module Cube
	Supplier Device Package	-
Report errors?		Report errors?

PPT0020DXF2VB Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PPT0020DXF2VB Payment Methods



















PPT0020DXF2VB Shipping Methods













If you have any question about PPT0020DXF2VB, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com