

# PPT0050GWR5VA

### PPT0050GWR5VA Information

Heisener.com

Part Number PPT0050GWR5VA

Manufacturer Honeywell Microelectronics & Precision Sensors

Category Sensors, Transducers

Pressure Sensors, Transducers

**Description** PRESSURE TRANSDUCER

Package Module Cube

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# PPT0050GWR5VA Specifications

Manufacturer Part NumberPPT0050GWR5VAManufacturerHoneywell Microelectronics & Precision SensorsCategorySensors, TransducersPackageModule CubeSeries-Pressure TypeVented GaugeOperating Pressure50 PSI (344.74 kPa)Output TypeAnalog, RS-485Output0 V ~ 5 VAccuracy±0.05%Voltage - Supply5.5 V ~ 30 VPort SizeMale - 0.13" (3.18mm) Tube, Dual		PT0050GWR5VA
Category  Sensors, Transducers  Package  Module Cube  Series  Pressure Type  Vented Gauge  Operating Pressure  Output Type  Analog, RS-485  Output  Accuracy  Voltage - Supply  Port Size  Sensors, Transducers  Module Cube  Vented Gauge  Vented Gauge  Vented Gauge  50 PSI (344.74 kPa)  Output Analog, RS-485  Output  Male - 0.13" (3.18mm) Tube, Dual		
Pressure Sensors, Transducers           Package         Module Cube           Series         -           Pressure Type         Vented Gauge           Operating Pressure         50 PSI (344.74 kPa)           Output Type         Analog, RS-485           Output         0 V ~ 5 V           Accuracy         ±0.05%           Voltage - Supply         5.5 V ~ 30 V           Port Size         Male - 0.13" (3.18mm) Tube, Dual	ŀ	oneywell Microelectronics & Precision Sensors
PackageModule CubeSeries-Pressure TypeVented GaugeOperating Pressure $50 \text{ PSI } (344.74 \text{ kPa})$ Output TypeAnalog, RS-485Output $0 \text{ V} \sim 5 \text{ V}$ Accuracy $\pm 0.05\%$ Voltage - Supply $5.5 \text{ V} \sim 30 \text{ V}$ Port SizeMale - $0.13$ " $(3.18 \text{mm})$ Tube, Dual	S	ensors, Transducers
Series-Pressure TypeVented GaugeOperating Pressure $50 \text{ PSI } (344.74 \text{ kPa})$ Output TypeAnalog, RS-485Output $0 \text{ V} \sim 5 \text{ V}$ Accuracy $\pm 0.05\%$ Voltage - Supply $5.5 \text{ V} \sim 30 \text{ V}$ Port SizeMale - $0.13$ " $(3.18 \text{mm}) \text{ Tube, Dual}$	F	ressure Sensors, Transducers
Pressure TypeVented GaugeOperating Pressure $50 \text{ PSI } (344.74 \text{ kPa})$ Output TypeAnalog, RS-485Output $0 \text{ V} \sim 5 \text{ V}$ Accuracy $\pm 0.05\%$ Voltage - Supply $5.5 \text{ V} \sim 30 \text{ V}$ Port SizeMale - $0.13$ " $(3.18 \text{mm})$ Tube, Dual	N	odule Cube
Operating Pressure $50 \text{ PSI } (344.74 \text{ kPa})$ Output TypeAnalog, RS-485Output $0 \text{ V} \sim 5 \text{ V}$ Accuracy $\pm 0.05\%$ Voltage - Supply $5.5 \text{ V} \sim 30 \text{ V}$ Port SizeMale - $0.13$ " $(3.18 \text{mm})$ Tube, Dual	-	
Output TypeAnalog, RS-485Output $0 \text{ V} \sim 5 \text{ V}$ Accuracy $\pm 0.05\%$ Voltage - Supply $5.5 \text{ V} \sim 30 \text{ V}$ Port SizeMale - $0.13$ " (3.18mm) Tube, Dual	7	ented Gauge
Output $0 \text{ V} \sim 5 \text{ V}$ Accuracy $\pm 0.05\%$ Voltage - Supply $5.5 \text{ V} \sim 30 \text{ V}$ Port Size Male - $0.13$ " ( $3.18$ mm) Tube, Dual	ire 5	PSI (344.74 kPa)
Accuracy $\pm 0.05\%$ Voltage - Supply $5.5 \text{ V} \sim 30 \text{ V}$ Port Size Male - 0.13" (3.18mm) Tube, Dual		nalog, RS-485
Voltage - Supply $5.5 \text{ V} \sim 30 \text{ V}$ Port Size Male - $0.13$ " ( $3.18$ mm) Tube, Dual	(	V ~ 5 V
Port Size Male - 0.13" (3.18mm) Tube, Dual	=	0.05%
	, 5	5 V ~ 30 V
	N	ale - 0.13" (3.18mm) Tube, Dual
Port Style Barbed	F	arbed
Features -	-	
Termination Style Connector	ie (	onnector
Maximum Pressure 150 PSI (1034.21 kPa)	are 1	50 PSI (1034.21 kPa)
Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$	erature -	0°C ~ 85°C
Package / Case Module Cube	N	odule Cube
Supplier Device Package -	Package -	
Report err		Report errors?

#### PPT0050GWR5VA Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### PPT0050GWR5VA Payment Methods



















## PPT0050GWR5VA Shipping Methods













If you have any question about PPT0050GWR5VA, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com