



PPT0300AFN2VB Information

Heisener.com

Part Number PPT0300AFN2VB

Manufacturer Honeywell Microelectronics & Precision Sensors

Category Sensors, Transducers

Pressure Sensors, Transducers

Description PRESSURE TRANSDUCER

Package Module Cube

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PPT0300AFN2VB Specifications

Manufacturer PPT0300AFN2VB Manufacturer Honeywell Microelectronics & Precision Sensors Category Sensors, Transducers Package Module Cube Series - Pressure Type Absolute Operating Pressure 300 PSI (2068.43 kPa) Output Type Analog, RS-232 Output 0 V ~ 5 V Accuracy ±0.05% Voltage - Supply 5.5 V ~ 30 V Port Size Filter Port Style Filtered Features - Termination Style Connector Maximum Pressure 600 PSI (4136.85 kPa) Operating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package -		
Category Sensors, Transducers Package Module Cube Series - Pressure Type Absolute Operating Pressure 300 PSI (2068.43 kPa) Output Type Analog, RS-232 Output 0 V ~ 5 V Accuracy ±0.05% Voltage - Supply 5.5 V ~ 30 V Port Size Filter Port Style Filtered Features - Termination Style Connector Maximum Pressure 600 PSI (4136.85 kPa) Operating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package -	Manufacturer Part Number	PPT0300AFN2VB
Package Module Cube Series - Pressure Type Absolute Operating Pressure 300 PSI (2068.43 kPa) Output Type Analog, RS-232 Output 0 V ~ 5 V Accuracy ±0.05% Voltage - Supply 5.5 V ~ 30 V Port Size Filter Port Style Filtered Features - Termination Style Connector Maximum Pressure 600 PSI (4136.85 kPa) Operating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package -	Manufacturer	Honeywell Microelectronics & Precision Sensors
Package Module Cube Series - Pressure Type Absolute Operating Pressure 300 PSI (2068.43 kPa) Output Type Analog, RS-232 Output 0 V ~ 5 V Accuracy ±0.05% Voltage - Supply 5.5 V ~ 30 V Port Size Filter Port Style Filtered Features - Termination Style Connector Maximum Pressure 600 PSI (4136.85 kPa) Operating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package -	Category	Sensors, Transducers
Series-Pressure TypeAbsoluteOperating Pressure300 PSI (2068.43 kPa)Output TypeAnalog, RS-232Output0 V ~ 5 VAccuracy±0.05%Voltage - Supply5.5 V ~ 30 VPort SizeFilterPort StyleFilteredFeatures-Termination StyleConnectorMaximum Pressure600 PSI (4136.85 kPa)Operating Temperature-40°C ~ 85°CPackage / CaseModule CubeSupplier Device Package-		Pressure Sensors, Transducers
Pressure TypeAbsoluteOperating Pressure300 PSI (2068.43 kPa)Output TypeAnalog, RS-232Output0 V ~ 5 VAccuracy±0.05%Voltage - Supply5.5 V ~ 30 VPort SizeFilterPort StyleFilteredFeatures-Termination StyleConnectorMaximum Pressure600 PSI (4136.85 kPa)Operating Temperature-40°C ~ 85°CPackage / CaseModule CubeSupplier Device Package-	Package	Module Cube
Operating Pressure 300 PSI (2068.43 kPa) Output Type Analog, RS-232 Output 0 V ~ 5 V Accuracy ±0.05% Voltage - Supply 5.5 V ~ 30 V Port Size Filter Port Style Filtered Features - Termination Style Connector Maximum Pressure 600 PSI (4136.85 kPa) Operating Temperature -40° C ~ 85° C Package / Case Module Cube Supplier Device Package -	Series	-
Output TypeAnalog, RS-232Output $0 \text{ V} \sim 5 \text{ V}$ Accuracy $\pm 0.05\%$ Voltage - Supply $5.5 \text{ V} \sim 30 \text{ V}$ Port SizeFilterPort StyleFilteredFeatures-Termination StyleConnectorMaximum Pressure $600 \text{ PSI } (4136.85 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / CaseModule CubeSupplier Device Package-	Pressure Type	Absolute
Output $0 \text{ V} \sim 5 \text{ V}$ Accuracy $\pm 0.05\%$ Voltage - Supply $5.5 \text{ V} \sim 30 \text{ V}$ Port SizeFilterPort StyleFilteredFeatures-Termination StyleConnectorMaximum Pressure $600 \text{ PSI } (4136.85 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / CaseModule CubeSupplier Device Package-	Operating Pressure	300 PSI (2068.43 kPa)
Accuracy ±0.05% Voltage - Supply 5.5 V ~ 30 V Port Size Filter Port Style Filtered Features - Connector Maximum Pressure 600 PSI (4136.85 kPa) Operating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package -	Output Type	Analog, RS-232
Voltage - Supply 5.5 V ~ 30 V Port Size Filter Port Style Filtered Features - Termination Style Connector Maximum Pressure 600 PSI (4136.85 kPa) Operating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package -	Output	0 V ~ 5 V
Port Size Port Style Filtered Features - Termination Style Connector Maximum Pressure 600 PSI (4136.85 kPa) Operating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package -	Accuracy	$\pm 0.05\%$
Port Style Filtered Features - Termination Style Connector Maximum Pressure 600 PSI (4136.85 kPa) Operating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package -	Voltage - Supply	5.5 V ~ 30 V
Features - Connector Maximum Pressure 600 PSI (4136.85 kPa) Operating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package -	Port Size	Filter
Termination Style Connector Maximum Pressure 600 PSI (4136.85 kPa) Operating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package -	Port Style	Filtered
Maximum Pressure600 PSI (4136.85 kPa)Operating Temperature-40°C ~ 85°CPackage / CaseModule CubeSupplier Device Package-	Features	-
Operating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package -	Termination Style	Connector
Package / Case Module Cube Supplier Device Package -	Maximum Pressure	600 PSI (4136.85 kPa)
Supplier Device Package -	Operating Temperature	-40°C ~ 85°C
	Package / Case	Module Cube
Report errors?	Supplier Device Package	-
		Report errors?

PPT0300AFN2VB Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PPT0300AFN2VB Payment Methods



















PPT0300AFN2VB Shipping Methods













If you have any question about PPT0300AFN2VB, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com