



## PPT0300GFX5VA Information

Heisener.com

Part Number PPT0300GFX5VA

Manufacturer Honeywell Microelectronics & Precision Sensors

**Category** Sensors, Transducers

Pressure Sensors, Transducers

**Description** PRESSURE TRANSDUCER

Package Module Cube

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **PPT0300GFX5VA Specifications**

Manufacturer Part Number       PPT0300GFX5VA         Manufacturer       Honeywell Microelectronics & Precision Sensors         Category       Sensors, Transducers         Package       Module Cube         Series       -         Pressure Type       Vented Gauge         Operating Pressure       300 PSI (2068.43 kPa)         Output Type       Analog, RS-485         Output       0 V ~ 5 V         Accuracy       ±0.05%         Voltage - Supply       5.5 V ~ 30 V         Port Size       Female - 1/8" (3.18mm) Swagelok?, Filter         Port Style       Filtered, Threaded         Features       -         Termination Style       Connector         Maximum Pressure       600 PSI (4136.85 kPa)         Operating Temperature       -40°C ~ 8°C         Package / Case       Module Cube         Supplier Device Package       -         Report errors?		
CategorySensors, TransducersPackageModule CubeSeries-Pressure TypeVented GaugeOperating Pressure300 PSI (2068.43 kPa)Output TypeAnalog, RS-485Output0 V ~ 5 VAccuracy±0.05%Voltage - Supply5.5 V ~ 30 VPort SizeFemale - 1/8" (3.18mm) Swagelok?, FilterPort StyleFiltered, ThreadedFeatures-Termination StyleConnectorMaximum Pressure600 PSI (4136.85 kPa)Operating Temperature-40°C ~ 85°CPackage / CaseModule CubeSupplier Device Package-	Manufacturer Part Number	PPT0300GFX5VA
Package Module Cube  Series - Pressure Type Vented Gauge  Operating Pressure Output Type Analog, RS-485  Output 0 V V S V  Accuracy ±0.05%  Voltage - Supply 5.5 V ~ 30 V  Port Size Female - 1/8" (3.18mm) Swagelok?, Filter  Port Style Filtered, Threaded  Features - Termination Style Connector  Maximum Pressure 600 PSI (4136.85 kPa)  Operating Temperature 40°C ~ 85°C  Package / Case Module Cube  Supplier Device Package	Manufacturer	Honeywell Microelectronics & Precision Sensors
PackageModule CubeSeries-Pressure TypeVented GaugeOperating Pressure300 PSI (2068.43 kPa)Output TypeAnalog, RS-485Output0 V ~ 5 VAccuracy±0.05%Voltage - Supply5.5 V ~ 30 VPort SizeFemale - 1/8" (3.18mm) Swagelok?, FilterPort StyleFiltered, ThreadedFeatures-Termination StyleConnectorMaximum Pressure600 PSI (4136.85 kPa)Operating Temperature-40°C ~ 85°CPackage / CaseModule CubeSupplier Device Package-	Category	Sensors, Transducers
Series-Pressure TypeVented GaugeOperating Pressure300 PSI (2068.43 kPa)Output TypeAnalog, RS-485Output0 V ~ 5 VAccuracy±0.05%Voltage - Supply5.5 V ~ 30 VPort SizeFemale - 1/8" (3.18mm) Swagelok?, FilterPort StyleFiltered, ThreadedFeatures-Termination StyleConnectorMaximum Pressure600 PSI (4136.85 kPa)Operating Temperature-40°C ~ 85°CPackage / CaseModule CubeSupplier Device Package-		Pressure Sensors, Transducers
Pressure Type Vented Gauge Operating Pressure 300 PSI (2068.43 kPa) Output Type Analog, RS-485 Output 0 V ~ 5 V Accuracy ±0.05% Voltage - Supply 5.5 V ~ 30 V Port Size Female - 1/8" (3.18mm) Swagelok?, Filter Port Style Filtered, Threaded Features - Termination Style Connector Maximum Pressure 600 PSI (4136.85 kPa) Operating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package -	Package	Module Cube
Operating Pressure  300 PSI (2068.43 kPa)  Output Type  Analog, RS-485  Output  0 V ~ 5 V  Accuracy  ±0.05%  Voltage - Supply  5.5 V ~ 30 V  Port Size  Female - 1/8" (3.18mm) Swagelok?, Filter  Port Style  Filtered, Threaded  Features  - Termination Style  Connector  Maximum Pressure  600 PSI (4136.85 kPa)  Operating Temperature  -40°C ~ 85°C  Package / Case  Module Cube  Supplier Device Package  -	Series	-
Output TypeAnalog, RS-485Output $0 \text{ V} \sim 5 \text{ V}$ Accuracy $\pm 0.05\%$ Voltage - Supply $5.5 \text{ V} \sim 30 \text{ V}$ Port SizeFemale - $1/8$ " (3.18mm) Swagelok?, FilterPort StyleFiltered, ThreadedFeatures-Termination StyleConnectorMaximum Pressure $600 \text{ PSI } (4136.85 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / CaseModule CubeSupplier Device Package-	Pressure Type	Vented Gauge
Output $0 \text{ V} \sim 5 \text{ V}$ Accuracy $\pm 0.05\%$ Voltage - Supply $5.5 \text{ V} \sim 30 \text{ V}$ Port SizeFemale - $1/8$ " (3.18mm) Swagelok?, FilterPort StyleFiltered, ThreadedFeatures-Termination StyleConnectorMaximum Pressure $600 \text{ PSI (4136.85 kPa)}$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / CaseModule CubeSupplier Device Package-	Operating Pressure	300 PSI (2068.43 kPa)
Accuracy ±0.05%  Voltage - Supply 5.5 V ~ 30 V  Port Size Female - 1/8" (3.18mm) Swagelok?, Filter  Port Style Filtered, Threaded  Features - Connector  Maximum Pressure 600 PSI (4136.85 kPa)  Operating Temperature -40°C ~ 85°C  Package / Case Module Cube  Supplier Device Package -	Output Type	Analog, RS-485
Voltage - Supply $5.5 \text{ V} \sim 30 \text{ V}$ Port Size Female - $1/8$ " (3.18mm) Swagelok?, Filter  Port Style Filtered, Threaded  Features -  Termination Style Connector  Maximum Pressure $600 \text{ PSI } (4136.85 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case Module Cube  Supplier Device Package -	Output	0 V ~ 5 V
Port Size  Female - 1/8" (3.18mm) Swagelok?, Filter  Port Style  Filtered, Threaded  Features  - Termination Style  Connector  Maximum Pressure  600 PSI (4136.85 kPa)  Operating Temperature  -40°C ~ 85°C  Package / Case  Module Cube  Supplier Device Package  -	Accuracy	±0.05%
Port Style Filtered, Threaded  Features -  Termination Style Connector  Maximum Pressure 600 PSI (4136.85 kPa)  Operating Temperature -40°C ~ 85°C  Package / Case Module Cube  Supplier Device Package -	Voltage - Supply	5.5 V ~ 30 V
Features - Connector  Maximum Pressure 600 PSI (4136.85 kPa)  Operating Temperature -40°C ~ 85°C  Package / Case Module Cube  Supplier Device Package -	Port Size	Female - 1/8" (3.18mm) Swagelok?, Filter
Termination Style Connector  Maximum Pressure 600 PSI (4136.85 kPa)  Operating Temperature -40°C ~ 85°C  Package / Case Module Cube  Supplier Device Package -	Port Style	Filtered, Threaded
Maximum Pressure600 PSI (4136.85 kPa)Operating Temperature-40°C ~ 85°CPackage / CaseModule CubeSupplier Device Package-	Features	-
Operating Temperature -40°C ~ 85°C  Package / Case Module Cube  Supplier Device Package -	Termination Style	Connector
Package / Case Module Cube Supplier Device Package -	Maximum Pressure	600 PSI (4136.85 kPa)
Supplier Device Package -	Operating Temperature	-40°C ~ 85°C
	Package / Case	Module Cube
Report errors?	Supplier Device Package	-
		Report errors?

#### PPT0300GFX5VA Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# PPT0300GFX5VA Payment Methods





















### PPT0300GFX5VA Shipping Methods













If you have any question about PPT0300GFX5VA, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com