



PPT0500AXN2VA Information

Heisener.com

Part Number PPT0500AXN2VA

Manufacturer Honeywell Microelectronics & Precision Sensors

Category Sensors, Transducers

Pressure Sensors, Transducers

Description PRESSURE TRANSDUCER

Package Module Cube

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PPT0500AXN2VA Specifications

| Manufacturer Part NumberPPT0500AXN2VAManufacturerHoneywell Microelectronics & Precision SensorsCategorySensors, TransducersPackageModule CubeSeries-Pressure TypeAbsoluteOperating Pressure500 PSI (3447.38 kPa)Output TypeAnalog, RS-232Output0 V ~ 5 VAccuracy±0.05%Voltage - Supply5.5 V ~ 30 VPort SizeFemale - 1/8" (3.18mm) Swagelok?Port StyleThreadedFeatures-Termination StyleConnector | | |
|--|--------------------------|--|
| Category Sensors, Transducers Pressure Sensors, Transducers Package Module Cube Series - Pressure Type Absolute Operating Pressure 500 PSI (3447.38 kPa) Output Type Analog, RS-232 Output 0 V ~ 5 V Accuracy ±0.05% Voltage - Supply 5.5 V ~ 30 V Port Size Female - 1/8" (3.18mm) Swagelok? Port Style Threaded Features - Termination Style Connector | Manufacturer Part Number | PPT0500AXN2VA |
| Package Module Cube Series - Pressure Type Absolute Operating Pressure 500 PSI (3447.38 kPa) Output Type Analog, RS-232 Output 0 V ~ 5 V Accuracy ±0.05% Voltage - Supply 5.5 V ~ 30 V Port Size Female - 1/8" (3.18mm) Swagelok? Port Style Threaded Features - Termination Style Connector | Manufacturer | Honeywell Microelectronics & Precision Sensors |
| PackageModule CubeSeries-Pressure TypeAbsoluteOperating Pressure500 PSI (3447.38 kPa)Output TypeAnalog, RS-232Output0 V ~ 5 VAccuracy±0.05%Voltage - Supply5.5 V ~ 30 VPort SizeFemale - 1/8" (3.18mm) Swagelok?Port StyleThreadedFeatures-Termination StyleConnector | Category | Sensors, Transducers |
| Series-Pressure TypeAbsoluteOperating Pressure $500 \text{ PSI } (3447.38 \text{ kPa})$ Output TypeAnalog, RS-232Output $0 \text{ V} \sim 5 \text{ V}$ Accuracy $\pm 0.05\%$ Voltage - Supply $5.5 \text{ V} \sim 30 \text{ V}$ Port SizeFemale - $1/8$ " $(3.18 \text{mm}) \text{ Swagelok}$?Port StyleThreadedFeatures-Termination StyleConnector | | Pressure Sensors, Transducers |
| Pressure Type Operating Pressure 500 PSI (3447.38 kPa) Output Type Analog, RS-232 Output 0 V ~ 5 V Accuracy ±0.05% Voltage - Supply Port Size Female - 1/8" (3.18mm) Swagelok? Port Style Threaded Features - Termination Style Absolute 500 PSI (3447.38 kPa) Analog, RS-232 0 V ~ 5 V Female - 1/8" (3.18mm) Swagelok? Threaded Connector | Package | Module Cube |
| Operating Pressure 500 PSI (3447.38 kPa) Output Type Analog, RS-232 Output 0 V ~ 5 V Accuracy ±0.05% Voltage - Supply 5.5 V ~ 30 V Port Size Female - 1/8" (3.18mm) Swagelok? Port Style Threaded Features - Termination Style Connector | Series | - |
| Output TypeAnalog, RS-232Output $0 \text{ V} \sim 5 \text{ V}$ Accuracy $\pm 0.05\%$ Voltage - Supply $5.5 \text{ V} \sim 30 \text{ V}$ Port SizeFemale - $1/8$ " (3.18mm) Swagelok?Port StyleThreadedFeatures-Termination StyleConnector | Pressure Type | Absolute |
| Output $0 \text{ V} \sim 5 \text{ V}$ Accuracy $\pm 0.05\%$ Voltage - Supply $5.5 \text{ V} \sim 30 \text{ V}$ Port SizeFemale - $1/8$ " (3.18mm) Swagelok?Port StyleThreadedFeatures-Termination StyleConnector | Operating Pressure | 500 PSI (3447.38 kPa) |
| Accuracy $\pm 0.05\%$ Voltage - Supply $5.5 \text{ V} \sim 30 \text{ V}$ Port Size Female - $1/8$ " (3.18mm) Swagelok? Port Style Threaded Features - Termination Style Connector | Output Type | Analog, RS-232 |
| Voltage - Supply 5.5 V ~ 30 V Port Size Female - 1/8" (3.18mm) Swagelok? Port Style Threaded Features - Termination Style Connector | Output | 0 V ~ 5 V |
| Port Size Female - 1/8" (3.18mm) Swagelok? Port Style Threaded Features - Termination Style Connector | Accuracy | ±0.05% |
| Port Style Threaded Features - Termination Style Connector | Voltage - Supply | 5.5 V ~ 30 V |
| Features - Termination Style Connector | Port Size | Female - 1/8" (3.18mm) Swagelok? |
| Termination Style Connector | Port Style | Threaded |
| · | Features | - |
| | Termination Style | Connector |
| Maximum Pressure 600 PSI (4136.85 kPa) | Maximum Pressure | 600 PSI (4136.85 kPa) |
| Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ | Operating Temperature | -40°C ~ 85°C |
| Package / Case Module Cube | Package / Case | Module Cube |
| Supplier Device Package - | Supplier Device Package | - |
| Report errors? | | Report errors? |

PPT0500AXN2VA Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PPT0500AXN2VA Payment Methods



















PPT0500AXN2VA Shipping Methods













If you have any question about PPT0500AXN2VA, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com