



### PPT2-0001DGF2VS Information

Heisener.com

Part Number PPT2-0001DGF2VS

Manufacturer Honeywell Microelectronics & Precision Sensors

Category Sensors, Transducers

Pressure Sensors, Transducers

**Description** PRESSURE TRANSDUCER

Package Module Cube

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## PPT2-0001DGF2VS Specifications

Manufacturer Part Number       PPT2-0001DGF2VS         Manufacturer       Honeywell Microelectronics & Precision Sensors         Category       Sensors, Transducers         Package       Module Cube         Series       PPT2         Pressure Type       Differential         Operating Pressure       ±1 PSI (±6.89 kPa)         Output Type       Analog, RS-232         Output       0 V ~ 5 V         Accuracy       ±0.0375%         Voltage - Supply       6 V ~ 34 V         Port Size       Female - 1/8" (3.18mm) Swagelok?, Filter         Port Style       Filtered, Threaded         Features       -         Termination Style       Connector         Maximum Pressure       ±3 PSI (±20.68 kPa)         Operating Temperature       -40°C ~ 85°C         Package / Case       Module Cube         Supplier Device Package       -         Report errors?		
CategorySensors, TransducersPackageModule CubeSeriesPPT2Pressure TypeDifferentialOperating Pressure±1 PSI (±6.89 kPa)Output TypeAnalog, RS-232Output0 V ~ 5 VAccuracy±0.0375%Voltage - Supply6 V ~ 34 VPort SizeFemale - 1/8" (3.18mm) Swagelok?, FilterPort StyleFiltered, ThreadedFeatures-Termination StyleConnectorMaximum Pressure±3 PSI (±20.68 kPa)Operating Temperature-40°C ~ 85°CPackage / CaseModule CubeSupplier Device Package-	Manufacturer Part Number	PPT2-0001DGF2VS
Package Module Cube Series PPT2 Pressure Type Differential Operating Pressure	Manufacturer	Honeywell Microelectronics & Precision Sensors
PackageModule CubeSeriesPPT2Pressure TypeDifferentialOperating Pressure±1 PSI (±6.89 kPa)Output TypeAnalog, RS-232Output0 V ~ 5 VAccuracy±0.0375%Voltage - Supply6 V ~ 34 VPort SizeFemale - 1/8" (3.18mm) Swagelok?, FilterPort StyleFiltered, ThreadedFeatures-Termination StyleConnectorMaximum Pressure±3 PSI (±20.68 kPa)Operating Temperature-40°C ~ 85°CPackage / CaseModule CubeSupplier Device Package-	Category	Sensors, Transducers
SeriesPPT2Pressure TypeDifferentialOperating Pressure±1 PSI (±6.89 kPa)Output TypeAnalog, RS-232Output0 V ~ 5 VAccuracy±0.0375%Voltage - Supply6 V ~ 34 VPort SizeFemale - 1/8" (3.18mm) Swagelok?, FilterPort StyleFiltered, ThreadedFeatures-Termination StyleConnectorMaximum Pressure±3 PSI (±20.68 kPa)Operating Temperature-40°C ~ 85°CPackage / CaseModule CubeSupplier Device Package-		Pressure Sensors, Transducers
Pressure Type Differential Operating Pressure ±1 PSI (±6.89 kPa) Output Type Analog, RS-232 Output 0 V ~ 5 V Accuracy ±0.0375% Voltage - Supply 6 V ~ 34 V Port Size Female - 1/8" (3.18mm) Swagelok?, Filter Port Style Filtered, Threaded Features - Termination Style Connector Maximum Pressure ±3 PSI (±20.68 kPa) Operating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package -	Package	Module Cube
Operating Pressure $\pm 1 \text{ PSI } (\pm 6.89 \text{ kPa})$ Output Type Analog, RS-232 Output $0 \text{ V} \sim 5 \text{ V}$ Accuracy $\pm 0.0375\%$ Voltage - Supply $6 \text{ V} \sim 34 \text{ V}$ Port Size Female - $1/8$ " $(3.18 \text{mm}) \text{ Swagelok?}$ , Filter Port Style Filtered, Threaded Features - Termination Style Connector Maximum Pressure $\pm 3 \text{ PSI } (\pm 20.68 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case Module Cube Supplier Device Package	Series	PPT2
Output TypeAnalog, RS-232Output $0 \text{ V} \sim 5 \text{ V}$ Accuracy $\pm 0.0375\%$ Voltage - Supply $6 \text{ V} \sim 34 \text{ V}$ Port SizeFemale - $1/8$ " (3.18mm) Swagelok?, FilterPort StyleFiltered, ThreadedFeatures-Termination StyleConnectorMaximum Pressure $\pm 3 \text{ PSI } (\pm 20.68 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / CaseModule CubeSupplier Device Package-	Pressure Type	Differential
Output $0 \text{ V} \sim 5 \text{ V}$ Accuracy $\pm 0.0375\%$ Voltage - Supply $6 \text{ V} \sim 34 \text{ V}$ Port Size Female - $1/8$ " $(3.18\text{mm})$ Swagelok?, Filter  Port Style Filtered, Threaded  Features -  Termination Style Connector  Maximum Pressure $\pm 3 \text{ PSI } (\pm 20.68 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case Module Cube  Supplier Device Package -	Operating Pressure	±1 PSI (±6.89 kPa)
Accuracy ±0.0375%  Voltage - Supply 6 V ~ 34 V  Port Size Female - 1/8" (3.18mm) Swagelok?, Filter  Port Style Filtered, Threaded  Features - Connector  Maximum Pressure ±3 PSI (±20.68 kPa)  Operating Temperature -40°C ~ 85°C  Package / Case Module Cube  Supplier Device Package -	Output Type	Analog, RS-232
Voltage - Supply  6 V ~ 34 V  Port Size  Female - 1/8" (3.18mm) Swagelok?, Filter  Port Style  Filtered, Threaded  Features  -  Termination Style  Connector  Maximum Pressure  ±3 PSI (±20.68 kPa)  Operating Temperature  -40°C ~ 85°C  Package / Case  Module Cube  Supplier Device Package  -	Output	0 V ~ 5 V
Port Size  Female - 1/8" (3.18mm) Swagelok?, Filter  Port Style  Filtered, Threaded  Features  - Termination Style  Connector  Maximum Pressure  ±3 PSI (±20.68 kPa)  Operating Temperature  -40°C ~ 85°C  Package / Case  Module Cube  Supplier Device Package  -	Accuracy	±0.0375%
Port Style Filtered, Threaded  Features -  Termination Style Connector  Maximum Pressure ±3 PSI (±20.68 kPa)  Operating Temperature -40°C ~ 85°C  Package / Case Module Cube  Supplier Device Package -	Voltage - Supply	6 V ~ 34 V
Features - Connector  Maximum Pressure ±3 PSI (±20.68 kPa)  Operating Temperature -40°C ~ 85°C  Package / Case Module Cube  Supplier Device Package -	Port Size	Female - 1/8" (3.18mm) Swagelok?, Filter
Termination StyleConnectorMaximum Pressure $\pm 3$ PSI ( $\pm 20.68$ kPa)Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / CaseModule CubeSupplier Device Package-	Port Style	Filtered, Threaded
Maximum Pressure $\pm 3$ PSI ( $\pm 20.68$ kPa)Operating Temperature $-40^{\circ}$ C $\sim 85^{\circ}$ CPackage / CaseModule CubeSupplier Device Package-	Features	-
Operating Temperature -40°C ~ 85°C  Package / Case Module Cube  Supplier Device Package -	Termination Style	Connector
Package / Case Module Cube Supplier Device Package -	Maximum Pressure	±3 PSI (±20.68 kPa)
Supplier Device Package -	Operating Temperature	-40°C ~ 85°C
	Package / Case	Module Cube
Report errors?	Supplier Device Package	-
		Report errors?

#### **PPT2-0001DGF2VS Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### PPT2-0001DGF2VS Payment Methods



















### **PPT2-0001DGF2VS Shipping Methods**













If you have any question about PPT2-0001DGF2VS, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com