



### PPT2-0005DXX2VS Information

Heisener.com

Part Number PPT2-0005DXX2VS

Manufacturer Honeywell Microelectronics & Precision Sensors

**Category** Sensors, Transducers

Pressure Sensors, Transducers

**Description** PRESSURE TRANSDUCER

Package Module Cube

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## PPT2-0005DXX2VS Specifications

Manufacturer Part NumberPPT2-0005DXX2VSManufacturerHoneywell Microelectronics & Precision SensorsCategorySensors, TransducersPackageModule CubeSeriesPPT2Pressure TypeDifferentialOperating Pressure±5 PSI (±34.47 kPa)Output TypeAnalog, RS-232Output0 V ~ 5 VAccuracy±0.0375%Voltage - Supply6 V ~ 34 VPort SizeFemale - 1/8" (3.18mm) Swagelok?, DualPort StyleThreadedFeatures-Tormination StyleConnectors		
CategorySensors, TransducersPackageModule CubeSeriesPPT2Pressure TypeDifferentialOperating Pressure±5 PSI (±34.47 kPa)Output TypeAnalog, RS-232Output0 V ~ 5 VAccuracy±0.0375%Voltage - Supply6 V ~ 34 VPort SizeFemale - 1/8" (3.18mm) Swagelok?, DualPort StyleThreadedFeatures-	Manufacturer Part Number	PPT2-0005DXX2VS
PackageModule CubeSeriesPPT2Pressure TypeDifferentialOperating Pressure $\pm 5$ PSI ( $\pm 34.47$ kPa)Output TypeAnalog, RS-232Output $0 \text{ V} \sim 5 \text{ V}$ Accuracy $\pm 0.0375\%$ Voltage - Supply $6 \text{ V} \sim 34 \text{ V}$ Port SizeFemale - $1/8$ " ( $3.18$ mm) Swagelok?, DualPort StyleThreadedFeatures-	Manufacturer	Honeywell Microelectronics & Precision Sensors
PackageModule CubeSeriesPPT2Pressure TypeDifferentialOperating Pressure±5 PSI (±34.47 kPa)Output TypeAnalog, RS-232Output0 V ~ 5 VAccuracy±0.0375%Voltage - Supply6 V ~ 34 VPort SizeFemale - 1/8" (3.18mm) Swagelok?, DualPort StyleThreadedFeatures-	Category	Sensors, Transducers
SeriesPPT2Pressure TypeDifferentialOperating Pressure $\pm 5$ PSI ( $\pm 34.47$ kPa)Output TypeAnalog, RS-232Output $0 \text{ V} \sim 5 \text{ V}$ Accuracy $\pm 0.0375\%$ Voltage - Supply $6 \text{ V} \sim 34 \text{ V}$ Port SizeFemale - $1/8$ " ( $3.18$ mm) Swagelok?, DualPort StyleThreadedFeatures-		Pressure Sensors, Transducers
Pressure Type Differential Operating Pressure $\pm 5 \text{ PSI } (\pm 34.47 \text{ kPa})$ Output Type Analog, RS-232 Output $0 \text{ V} \sim 5 \text{ V}$ Accuracy $\pm 0.0375\%$ Voltage - Supply $6 \text{ V} \sim 34 \text{ V}$ Port Size Female - $1/8$ " (3.18mm) Swagelok?, Dual Port Style Threaded Features -	Package	Module Cube
Operating Pressure $\pm 5$ PSI ( $\pm 34.47$ kPa)  Output Type Analog, RS-232  Output $0 \text{ V} \sim 5 \text{ V}$ Accuracy $\pm 0.0375\%$ Voltage - Supply $6 \text{ V} \sim 34 \text{ V}$ Port Size Female - $1/8$ " ( $3.18$ mm) Swagelok?, Dual  Port Style Threaded  Features -	Series	PPT2
Output TypeAnalog, RS-232Output $0 \text{ V} \sim 5 \text{ V}$ Accuracy $\pm 0.0375\%$ Voltage - Supply $6 \text{ V} \sim 34 \text{ V}$ Port SizeFemale - $1/8$ " (3.18mm) Swagelok?, DualPort StyleThreadedFeatures-	Pressure Type	Differential
Output $0 \text{ V} \sim 5 \text{ V}$ Accuracy $\pm 0.0375\%$ Voltage - Supply $6 \text{ V} \sim 34 \text{ V}$ Port Size Female - $1/8$ " (3.18mm) Swagelok?, Dual  Port Style Threaded  Features -	Operating Pressure	±5 PSI (±34.47 kPa)
Accuracy $\pm 0.0375\%$ Voltage - Supply $6 \text{ V} \sim 34 \text{ V}$ Port Size Female - $1/8$ " (3.18mm) Swagelok?, Dual  Port Style Threaded  Features -	Output Type	Analog, RS-232
Voltage - Supply  6 V ~ 34 V  Port Size  Female - 1/8" (3.18mm) Swagelok?, Dual  Port Style  Threaded  Features  -	Output	0 V ~ 5 V
Port Size Female - 1/8" (3.18mm) Swagelok?, Dual Port Style Threaded Features -	Accuracy	±0.0375%
Port Style Threaded Features -	Voltage - Supply	6 V ~ 34 V
Features -	Port Size	Female - 1/8" (3.18mm) Swagelok?, Dual
	Port Style	Threaded
Tormination Style	Features	-
Connector	Termination Style	Connector
Maximum Pressure $\pm 15 \text{ PSI } (\pm 103.42 \text{ kPa})$	Maximum Pressure	±15 PSI (±103.42 kPa)
Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$	Operating Temperature	-40°C ~ 85°C
Package / Case Module Cube	Package / Case	Module Cube
Supplier Device Package -	Supplier Device Package	-
Report errors?		Report errors?

### PPT2-0005DXX2VS Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## PPT2-0005DXX2VS Payment Methods



















## PPT2-0005DXX2VS Shipping Methods













If you have any question about PPT2-0005DXX2VS, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com