



PPT2-0010DFK5VS Information

Heisener.com

Part Number PPT2-0010DFK5VS

Manufacturer Honeywell Microelectronics & Precision Sensors

Category Sensors, Transducers

Pressure Sensors, Transducers

Description PRESSURE TRANSDUCER

Package Module Cube

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PPT2-0010DFK5VS Specifications

Manufacturer Part NumberPPT2-0010DFK5VSManufacturerHoneywell Microelectronics & Precision SensorsCategorySensors, TransducersPressure Sensors, TransducersPackageModule CubeSeriesPPT2Pressure TypeDifferentialOperating Pressure±10 PSI (±68.95 kPa)Output TypeAnalog, RS-485Output0 V ~ 5 V
Category Sensors, Transducers Pressure Sensors, Transducers Module Cube Series PPT2 Pressure Type Differential Operating Pressure ±10 PSI (±68.95 kPa) Output Type Analog, RS-485 Output 0 V ~ 5 V
Pressure Sensors, Transducers Package Module Cube Series PPT2 Pressure Type Differential Operating Pressure
PackageModule CubeSeriesPPT2Pressure TypeDifferentialOperating Pressure $\pm 10 \text{ PSI } (\pm 68.95 \text{ kPa})$ Output TypeAnalog, RS-485Output $0 \text{ V} \sim 5 \text{ V}$
SeriesPPT2Pressure TypeDifferentialOperating Pressure $\pm 10 \text{ PSI } (\pm 68.95 \text{ kPa})$ Output TypeAnalog, RS-485Output $0 \text{ V} \sim 5 \text{ V}$
Pressure Type Differential Operating Pressure $\pm 10 \text{ PSI } (\pm 68.95 \text{ kPa})$ Output Type Analog, RS-485 Output $\pm 10 \text{ V} \sim 5 \text{ V}$
Operating Pressure ± 10 PSI (± 68.95 kPa) Output Type Analog, RS-485 Output 0 V ~ 5 V
Output Type Analog, RS-485 Output $0 \text{ V} \sim 5 \text{ V}$
Output $0 \text{ V} \sim 5 \text{ V}$
Accuracy $\pm 0.0375\%$
Voltage - Supply $6 \text{ V} \sim 34 \text{ V}$
Port Size Male - 1/8" (3.18mm) Swagelok?, Filter
Port Style Filtered, Threaded
Features -
Termination Style Connector
Maximum Pressure $\pm 30 \text{ PSI } (\pm 206.84 \text{ kPa})$
Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$
Package / Case Module Cube
Supplier Device Package -
Report errors

PPT2-0010DFK5VS Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PPT2-0010DFK5VS Payment Methods



















PPT2-0010DFK5VS Shipping Methods













If you have any question about PPT2-0010DFK5VS, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com