

PPT2-0010DXR5VS

PPT2-0010DXR5VS Information

Contract levels date they	 PPT2-0010DXR5VS Honeywell Microelectronics & Precision Sensors Sensors, Transducers Pressure Sensors, Transducers PRESSURE TRANSDUCER Module Cube For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



PPT2-0010DXR5VS Specifications

Manufacturer Honeywell Microelectronics & Precision Sensors Category Sensors, Transducers Package Module Cube Series PPT2 Pressure Type Differential Operating Pressure 10 PSI (±68.95 kPa) Output Type Analog, RS-485 Output 0 V ~ 5 V Accuracy ±0.0375% Voltage - Supply 6 V ~ 34 V Port Size Barbed, Threaded Features - Termination Style Connector Maximum Pressure 30 PSI (±206.84 kPa) Operating Femperature -40°C ~ 85°C Package / Case Module Cube			
CategorySensors, TransducersPressure Sensors, TransducersPackageModule CubeSeriesPPT2Pressure TypeDifferentialOperating Pressure±10 PSI (±68.95 kPa)Output TypeAnalog, RS-485Output Type0 V ~ 5 VAccuracy±0.0375%Voltage - Supply6 V ~ 34 VPort SizeFemale - 1/8" (3.18mm) Swagelok?, Male - 0.13" (3.18mm) TubePort StyleBarbed, ThreadedFeatures-Termination StyleConnectorMaximum Pressure±30 PSI (±206.84 kPa)Operating Temperature+40°C ~ 85°CPackage / Case.Supplier Device Package-	Manufacturer Part Number	PPT2-0010DXR5VS	
Pressure Sensors, TransducersPackageModule CubeSeriesPPT2Pressure TypeDifferentialOperating Pressure±10 PSI (±68.95 kPa)Output TypeAnalog, RS-485Output0 V ~ 5 VAccuracy±0.0375%Voltage - Supply6 V ~ 34 VPort SizeFemale - 1/8" (3.18mm) Swagelok?, Male - 0.13" (3.18mm) TubePort StyleBarbed, ThreadedFeatures-Termination StyleConnectorMaximum Pressure±30 PSI (±206.84 kPa)Operating Temperature-40°C ~ 85°CPackage / Case.Supplier Device Package-	Manufacturer	Honeywell Microelectronics & Precision Sensors	
PackageModule CubeSeriesPPT2Pressure TypeDifferentialOperating Pressure±10 PSI (±68.95 kPa)Output TypeAnalog, RS-485Output Output0 V ~ 5 VAccuracy±0.0375%Voltage - Supply6 V ~ 34 VPort SizeFemale - 1/8" (3.18mm) Swagelok?, Male - 0.13" (3.18mm) TubePort SyleSarbed, ThreadedFeatures-Termination StyleConnectorMaximum Pressure±30 PSI (±206.84 kPa)Operating Temperature40°C ~ 85°CPackage / CaseModule CubeSupplier Device Package-	Category	Sensors, Transducers	
Series PPT2 Pressure Type Differential Operating Pressure ±10 PSI (±68.95 kPa) Output Type Analog, RS-485 Output 0 V ~ 5 V Accuracy ±0.0375% Voltage - Supply 6 V ~ 34 V Port Size Female - 1/8" (3.18mm) Swagelok?, Male - 0.13" (3.18mm) Tube Port Syle Barbed, Threaded Features - Termination Style Connector Maximum Pressure ±30 PSI (±206.84 kPa) Operating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package -		Pressure Sensors, Transducers	
Pressure TypeDifferentialOperating Pressure±10 PSI (±68.95 kPa)Output TypeAnalog, RS-485Output0 V ~ 5 VAccuracy±0.0375%Voltage - Supply6 V ~ 34 VPort SizeFemale - 1/8" (3.18mm) Swagelok?, Male - 0.13" (3.18mm) TubePort StyleBarbed, ThreadedFeatures-Termination StyleConnectorMaximum Pressure±30 PSI (±206.84 kPa)Operating Temperature-40°C ~ 85°CPackage / CaseModule CubeSupplier Device Package-	Package	Module Cube	
DefensionEntreminationOperating Pressure±10 PSI (±68.95 kPa)Output TypeAnalog, RS-485Output0 V ~ 5 VAccuracy±0.0375%Voltage - Supply6 V ~ 34 VPort SizeFemale - 1/8" (3.18mm) Swagelok?, Male - 0.13" (3.18mm) TubePort StyleBarbed, ThreadedFeatures-Termination StyleConnectorMaximum Pressure±30 PSI (±206.84 kPa)Operating Temperature-40°C ~ 85°CPackage / CaseModule CubeSupplier Device Package-	Series	PPT2	
Output TypeAnalog, RS-485Output0 V ~ 5 VAccuracy±0.0375%Voltage - Supply6 V ~ 34 VPort SizeFemale - 1/8" (3.18mm) Swagelok?, Male - 0.13" (3.18mm) TubePort StyleBarbed, ThreadedFeatures-Termination StyleConnectorMaximum Pressure±30 PSI (±206.84 kPa)Operating Temperature-40°C ~ 85°CPackage / CaseModule CubeSupplier Device Package-	Pressure Type	Differential	
Output0 V ~ 5 VAccuracy±0.0375%Voltage - Supply6 V ~ 34 VPort SizeFemale - 1/8" (3.18mm) Swagelok?, Male - 0.13" (3.18mm) TubePort StyleBarbed, ThreadedFeatures-Termination StyleConnectorMaximum Pressure±30 PSI (±206.84 kPa)Operating Temperature-40°C ~ 85°CPackage / CaseModule CubeSupplier Device Package-	Operating Pressure	±10 PSI (±68.95 kPa)	
Accuracy±0.0375%Accuracy±0.0375%Voltage - Supply6 V ~ 34 VPort SizeFemale - 1/8" (3.18mm) Swagelok?, Male - 0.13" (3.18mm) TubePort StyleBarbed, ThreadedFeatures-Termination StyleConnectorMaximum Pressure±30 PSI (±206.84 kPa)Operating Temperature-40°C ~ 85°CPackage / CaseModule CubeSupplier Device Package-	Output Type	Analog, RS-485	
Voltage - Supply6 V ~ 34 VPort SizeFemale - 1/8" (3.18mm) Swagelok?, Male - 0.13" (3.18mm) TubePort StyleBarbed, ThreadedFeatures-Termination StyleConnectorMaximum Pressure±30 PSI (±206.84 kPa)Operating Temperature-40°C ~ 85°CPackage / CaseModule CubeSupplier Device Package-	Output	0 V ~ 5 V	
Port SizeFemale - 1/8" (3.18mm) Swagelok?, Male - 0.13" (3.18mm) TubePort StyleBarbed, ThreadedFeatures-Termination StyleConnectorMaximum Pressure±30 PSI (±206.84 kPa)Operating Temperature-40°C ~ 85°CPackage / CaseModule CubeSupplier Device Package-	Accuracy	±0.0375%	
Port StyleBarbed, ThreadedFeatures-Termination StyleConnectorMaximum Pressure±30 PSI (±206.84 kPa)Operating Temperature-40°C ~ 85°CPackage / CaseModule CubeSupplier Device Package-	Voltage - Supply	6 V ~ 34 V	
Features-Termination StyleConnectorMaximum Pressure±30 PSI (±206.84 kPa)Operating Temperature-40°C ~ 85°CPackage / CaseModule CubeSupplier Device Package-	Port Size	Female - 1/8" (3.18mm) Swagelok?, Male - 0.13" (3.18mm) Tube	
Termination StyleConnectorMaximum Pressure±30 PSI (±206.84 kPa)Operating Temperature-40°C ~ 85°CPackage / CaseModule CubeSupplier Device Package-	Port Style	Barbed, Threaded	
Maximum Pressure±30 PSI (±206.84 kPa)Operating Temperature-40°C ~ 85°CPackage / CaseModule CubeSupplier Device Package-	Features	-	
Operating Temperature-40°C ~ 85°CPackage / CaseModule CubeSupplier Device Package-	Termination Style	Connector	
Package / Case Module Cube Supplier Device Package -	Maximum Pressure	±30 PSI (±206.84 kPa)	
Supplier Device Package -	Operating Temperature	-40°C ~ 85°C	
	Package / Case	Module Cube	
Report errors?	Supplier Device Package	-	
			Report errors?

PPT2-0010DXR5VS Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

PPT2-0010DXR5VS Payment Methods



PPT2-0010DXR5VS Shipping Methods



If you have any question about PPT2-0010DXR5VS, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com