



PPT2-0010GFG2VS Information

Heisener.com

Part Number PPT2-0010GFG2VS

Manufacturer Honeywell Microelectronics & Precision Sensors

Category Sensors, Transducers

Pressure Sensors, Transducers

Description PRESSURE TRANSDUCER

Package Module Cube

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PPT2-0010GFG2VS Specifications

Manufacturer Part Number PPT2-0010GFG2VS Manufacturer Honeywell Microelectronics & Precision Sensors Category Sensors, Transducers Package Module Cube Series PPT2 Pressure Type Vented Gauge Operating Pressure 10 PSI (68.95 kPa) Output Type Analog, RS-232 Output 0 V ~ 5 V Accuracy ±0.0375% Voltage - Supply 6 V ~ 34 V Port Size Female - 1/8" (3.18mm) Swagelok?, Filter Port Style Filtered, Threaded Features - Termination Style Connector Maximum Pressure 30 PSI (206.84 kPa) Operating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package - Report errors?		
Category Sensors, Transducers Package Module Cube Series PPT2 Pressure Type Vented Gauge Operating Pressure 10 PSI (68.95 kPa) Output Type Analog, RS-232 Output 0 V ~ 5 V Accuracy ±0.0375% Voltage - Supply 6 V ~ 34 V Port Size Female - 1/8" (3.18mm) Swagelok?, Filter Port Style Filtered, Threaded Features - Termination Style Connector Maximum Pressure 30 PSI (206.84 kPa) Operating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package -	Manufacturer Part Number	PPT2-0010GFG2VS
Package Module Cube Series PPT2 Pressure Type Vented Gauge Operating Pressure Output Type Analog, RS-232 Output 0 V ~ 5 V Accuracy ±0.0375% Voltage - Supply 6 V ~ 34 V Port Size Female - 1/8" (3.18mm) Swagelok?, Filter Port Style Filtered, Threaded Features - Termination Style Connector Maximum Pressure 30 PSI (206.84 kPa) Operating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package	Manufacturer	Honeywell Microelectronics & Precision Sensors
Package Module Cube Series PPT2 Pressure Type Vented Gauge Operating Pressure 10 PSI (68.95 kPa) Output Type Analog, RS-232 Output 0 V ~ 5 V Accuracy ±0.0375% Voltage - Supply 6 V ~ 34 V Port Size Female - 1/8" (3.18mm) Swagelok?, Filter Port Style Filtered, Threaded Features - Termination Style Connector Maximum Pressure 30 PSI (206.84 kPa) Operating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package -	Category	Sensors, Transducers
SeriesPPT2Pressure TypeVented GaugeOperating Pressure10 PSI (68.95 kPa)Output TypeAnalog, RS-232Output0 V ~ 5 VAccuracy±0.0375%Voltage - Supply6 V ~ 34 VPort SizeFemale - 1/8" (3.18mm) Swagelok?, FilterPort StyleFiltered, ThreadedFeatures-Termination StyleConnectorMaximum Pressure30 PSI (206.84 kPa)Operating Temperature-40°C ~ 85°CPackage / CaseModule CubeSupplier Device Package-		Pressure Sensors, Transducers
Pressure Type Vented Gauge Operating Pressure 10 PSI (68.95 kPa) Output Type Analog, RS-232 Output 0 V ~ 5 V Accuracy ±0.0375% Voltage - Supply 6 V ~ 34 V Port Size Female - 1/8" (3.18mm) Swagelok?, Filter Port Style Filtered, Threaded Features - Termination Style Connector Maximum Pressure 30 PSI (206.84 kPa) Operating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package -	Package	Module Cube
Operating Pressure 10 PSI (68.95 kPa) Output Type Analog, RS-232 Output 0 V ~ 5 V Accuracy ±0.0375% Voltage - Supply 6 V ~ 34 V Port Size Female - 1/8" (3.18mm) Swagelok?, Filter Port Style Filtered, Threaded Features - Termination Style Connector Maximum Pressure 30 PSI (206.84 kPa) Operating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package - 10 PSI (68.95 kPa) Analog, RS-232 Analog, RS-232 Cov C ~ 85°C Module Cube Supplier Device Package - 10 PSI (68.95 kPa) Analog, RS-232 Analog, RS-232 Analog, RS-232 Cov C ~ 85°C Module Cube Supplier Device Package	Series	PPT2
Output TypeAnalog, RS-232Output $0 \text{ V} \sim 5 \text{ V}$ Accuracy $\pm 0.0375\%$ Voltage - Supply $6 \text{ V} \sim 34 \text{ V}$ Port SizeFemale - $1/8$ " (3.18mm) Swagelok?, FilterPort StyleFiltered, ThreadedFeatures-Termination StyleConnectorMaximum Pressure $30 \text{ PSI } (206.84 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / CaseModule CubeSupplier Device Package-	Pressure Type	Vented Gauge
Output $0 \text{ V} \sim 5 \text{ V}$ Accuracy $\pm 0.0375\%$ Voltage - Supply $6 \text{ V} \sim 34 \text{ V}$ Port Size Female - $1/8$ " (3.18mm) Swagelok?, Filter Port Style Filtered, Threaded Features - Termination Style Connector Maximum Pressure $30 \text{ PSI } (206.84 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case Module Cube Supplier Device Package -	Operating Pressure	10 PSI (68.95 kPa)
Accuracy ±0.0375% Voltage - Supply 6 V ~ 34 V Port Size Female - 1/8" (3.18mm) Swagelok?, Filter Port Style Filtered, Threaded Features - Connector Maximum Pressure 30 PSI (206.84 kPa) Operating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package -	Output Type	Analog, RS-232
Voltage - Supply 6 V ~ 34 V Port Size Female - 1/8" (3.18mm) Swagelok?, Filter Port Style Filtered, Threaded Features - Termination Style Connector Maximum Pressure 30 PSI (206.84 kPa) Operating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package -	Output	0 V ~ 5 V
Port Size Female - 1/8" (3.18mm) Swagelok?, Filter Port Style Filtered, Threaded Features - Termination Style Connector Maximum Pressure 30 PSI (206.84 kPa) Operating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package -	Accuracy	±0.0375%
Port Style Filtered, Threaded Features - Termination Style Connector Maximum Pressure 30 PSI (206.84 kPa) Operating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package -	Voltage - Supply	6 V ~ 34 V
Features - Connector Maximum Pressure 30 PSI (206.84 kPa) Operating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package -	Port Size	Female - 1/8" (3.18mm) Swagelok?, Filter
Termination Style Connector Maximum Pressure 30 PSI (206.84 kPa) Operating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package -	Port Style	Filtered, Threaded
Maximum Pressure30 PSI (206.84 kPa)Operating Temperature-40°C ~ 85°CPackage / CaseModule CubeSupplier Device Package-	Features	-
Operating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package -	Termination Style	Connector
Package / Case Module Cube Supplier Device Package -	Maximum Pressure	30 PSI (206.84 kPa)
Supplier Device Package -	Operating Temperature	-40°C ~ 85°C
	Package / Case	Module Cube
Report errors?	Supplier Device Package	-
		Report errors?

PPT2-0010GFG2VS Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PPT2-0010GFG2VS Payment Methods



















PPT2-0010GFG2VS Shipping Methods













If you have any question about PPT2-0010GFG2VS, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com