

PPT2-0010GRK2VS

Quote

PPT2-0010GRK2VS Information

Heisener.com	Part Number	PPT2-0010GRK2VS	
	Manufacturer	Honeywell Microelectronics & Precision Sensors	61520
	Category	Sensors, Transducers Pressure Sensors, Transducers	
	Description	PRESSURE TRANSDUCER	
	Package	Module Cube	
		For the pricing/inventory/lead time, please contact	El constante.
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a
		·	

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



PPT2-0010GRK2VS Specifications

ManufacturerHoneywell Microelectronics & Precision SensorsCategorySensors, TransducersPressure Sensors, TransducersPackageModule CubeSeriesPPT2Pressure TypeVented GaugeOperating Pressure10 PSI (68.95 kPa)Output TypeAnalog, RS-232Output0 V ~ 5 VAccuracy±0.0375%Voltage - Supply6 V ~ 34 VPort SizeBarbed, ThreadedFeatures-Termination Style0.09 SI (206.84 kPa)Operating Temperature-40°C ~ 85°CPackage / CaseModule Cube			
CategorySensors, TransducersPackageModule CubePackagePPT2Pressure TypeVented GaugeOperating Pressure10 PSI (68.95 kPa)Output TypeAnalog, RS-232Output Type0 V ~ 5 VAccuracy±0.0375%Voltage - Supply6 V ~ 34 VPort SizeMale - 1/8" (3.18mm) Swagelok?, Male - 0.13" (3.18mm) TubePeatures-Termination StyleConnectorMaximum Pressure30 PSI (206.84 kPa)Operating Temperature-40°C ~ 85°CPackage / Case-Supplier Device Package-	Manufacturer Part Number	PPT2-0010GRK2VS	
Pressure Sensors, TransducersPackageModule CubeSeriesPPT2Pressure TypeVented GaugeOperating Pressure10 PSI (68.95 kPa)Output TypeAnalog, RS-232Output0 V ~ 5 VAccuracy±0.0375%Voltage - Supply6 V ~ 34 VPort SizeMale - 1/8" (3.18mm) Swagelok?, Male - 0.13" (3.18mm) TubePort StyleBarbed, ThreadedFeatures-Termination StyleConnectorMaximum Pressure30 PSI (206.84 kPa)Operating Temperature+00°C ~ 85°CPackage / CaseModule CubeSupplier Device Package-	Manufacturer	Honeywell Microelectronics & Precision Sensors	
PackageModule CubeSeriesPPT2Pressure TypeVented GaugeOperating Pressure10 PSI (68.95 kPa)Output TypeAnalog, RS-232Output0 V ~ 5 VAccuracy40.0375%Voltage - Supply6 V ~ 34 VPort SizeMale - 1/8" (3.18mm) Swagelok?, Male - 0.13" (3.18mm) TubePort SyleSarbed, ThreadedFeatures-Acman Syle0.0951(206.84 kPa)Operating Temperature-40°C ~ 85°CPackage / Case.Supplier Device Package-Supplier Device Package-	Category	Sensors, Transducers	
Series PPT2 Pressure Type Vented Gauge Operating Pressure 10 PSI (68.95 kPa) Output Type Analog, RS-232 Output Output 0 V ~ 5 V Accuracy ±0.0375% Voltage - Supply 6 V ~ 34 V Port Size Male - 1/8" (3.18mm) Swagelok?, Male - 0.13" (3.18mm) Tube Port Syle Barbed, Threaded Features - Termination Style Connector Maximum Pressure 30 PSI (206.84 kPa) Operating Temperature +40°C ~ 85°C Package / Case Module Cube Supplier Device Package -		Pressure Sensors, Transducers	
Pressure TypeVented GaugeOperating Pressure10 PSI (68.95 kPa)Output TypeAnalog, RS-232Output0 V ~ 5 VAccuracy±0.0375%Voltage - Supply6 V ~ 34 VPort SizeMale - 1/8" (3.18mm) Swagelok?, Male - 0.13" (3.18mm) TubePort StyleBarbed, ThreadedFeatures-Termination StyleConnectorMaximum Pressure30 PSI (206.84 kPa)Operating Temperature+40°C ~ 85°CPackage / CaseModule CubeSupplier Device Package-	Package	Module Cube	
Operating Pressure10 PSI (68.95 kPa)Output TypeAnalog, RS-232Output0 V ~ 5 VAccuracy±0.0375%Voltage - Supply6 V ~ 34 VPort SizeMale - 1/8" (3.18mm) Swagelok?, Male - 0.13" (3.18mm) TubePort StyleBarbed, ThreadedFeatures-Termination StyleConnectorMaximum Pressure30 PSI (206.84 kPa)Operating Temperature-40°C ~ 85°CPackage / CaseModule CubeSupplier Device Package-	Series	PPT2	
Analog, RS-232Output0 V ~ 5 VAccuracy±0.0375%Voltage - Supply6 V ~ 34 VPort SizeMale - 1/8" (3.18mm) Swagelok?, Male - 0.13" (3.18mm) TubePort StyleBarbed, ThreadedFeatures-Termination StyleConnectorMaximum Pressure30 PSI (206.84 kPa)Operating Temperature-40°C ~ 85°CPackage / CaseModule CubeSupplier Device Package-	Pressure Type	Vented Gauge	
Output0 V ~ 5 VAccuracy±0.0375%Voltage - Supply6 V ~ 34 VPort SizeMale - 1/8" (3.18mm) Swagelok?, Male - 0.13" (3.18mm) TubePort StyleBarbed, ThreadedFeatures-Termination StyleConnectorMaximum Pressure30 PSI (206.84 kPa)Operating Temperature-40°C ~ 85°CPackage / CaseModule CubeSupplier Device Package-	Operating Pressure	10 PSI (68.95 kPa)	
Accuracy±0.0375%Accuracy±0.0375%Voltage - Supply6 V ~ 34 VPort SizeMale - 1/8" (3.18mm) Swagelok?, Male - 0.13" (3.18mm) TubePort StyleBarbed, ThreadedFeatures-Termination StyleConnectorMaximum Pressure30 PSI (206.84 kPa)Operating Temperature-40°C ~ 85°CPackage / CaseModule CubeSupplier Device Package-	Output Type	Analog, RS-232	
Voltage - Supply6 V ~ 34 VPort SizeMale - 1/8" (3.18mm) Swagelok?, Male - 0.13" (3.18mm) TubePort StyleBarbed, ThreadedFeatures-Termination StyleConnectorMaximum Pressure30 PSI (206.84 kPa)Operating Temperature-40°C ~ 85°CPackage / CaseModule CubeSupplier Device Package-	Output	0 V ~ 5 V	
Port SizeMale - 1/8" (3.18mm) Swagelok?, Male - 0.13" (3.18mm) TubePort StyleBarbed, ThreadedFeatures-Termination StyleConnectorMaximum Pressure30 PSI (206.84 kPa)Operating Temperature-40°C ~ 85°CPackage / CaseModule CubeSupplier Device Package-	Accuracy	$\pm 0.0375\%$	
Port StyleBarbed, ThreadedFeatures-Termination StyleConnectorMaximum Pressure30 PSI (206.84 kPa)Operating Temperature-40°C ~ 85°CPackage / CaseModule CubeSupplier Device Package-	Voltage - Supply	6 V ~ 34 V	
Features-Termination StyleConnectorMaximum Pressure30 PSI (206.84 kPa)Operating Temperature-40°C ~ 85°CPackage / CaseModule CubeSupplier Device Package-	Port Size	Male - 1/8" (3.18mm) Swagelok?, Male - 0.13" (3.18mm) Tube	
Termination StyleConnectorMaximum Pressure30 PSI (206.84 kPa)Operating Temperature-40°C ~ 85°CPackage / CaseModule CubeSupplier Device Package-	Port Style	Barbed, Threaded	
Maximum Pressure30 PSI (206.84 kPa)Operating Temperature-40°C ~ 85°CPackage / CaseModule CubeSupplier Device Package-	Features	-	
Operating Temperature-40°C ~ 85°CPackage / CaseModule CubeSupplier Device Package-	Termination Style	Connector	
Package / Case Module Cube Supplier Device Package -	Maximum Pressure	30 PSI (206.84 kPa)	
Supplier Device Package -	Operating Temperature	-40°C ~ 85°C	
	Package / Case	Module Cube	
Report errors?	Supplier Device Package	-	
		Report errors?	

PPT2-0010GRK2VS Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

PPT2-0010GRK2VS Payment Methods



PPT2-0010GRK2VS Shipping Methods



If you have any question about PPT2-0010GRK2VS, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com