



### PPT2-0020DFG2VS Information

Heisener.com

Part Number PPT2-0020DFG2VS

Manufacturer Honeywell Microelectronics & Precision Sensors

**Category** Sensors, Transducers

Pressure Sensors, Transducers

**Description** PRESSURE TRANSDUCER

Package Module Cube

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## PPT2-0020DFG2VS Specifications

Manufacturer Part NumberPPT2-0020DFG2VSManufacturerHoneywell Microelectronics & Precision SensorsCategorySensors, TransducersPressure Sensors, TransducersPackageModule CubeSeriesPPT2Pressure TypeDifferentialOperating Pressure±20 PSI (±137.9 kPa)Output TypeAnalog, RS-232Output0 V ~ 5 VAccuracy±0.0375%
Category Sensors, Transducers  Pressure Sensors, Transducers  Package Module Cube Series PPT2  Pressure Type Differential Operating Pressure ±20 PSI (±137.9 kPa)  Output Type Analog, RS-232  Output  Output
Pressure Sensors, Transducers  Package Module Cube  Series PPT2  Pressure Type Differential  Operating Pressure  ±20 PSI (±137.9 kPa)  Output Type Analog, RS-232  Output 0 V ~ 5 V
PackageModule CubeSeriesPPT2Pressure TypeDifferentialOperating Pressure±20 PSI (±137.9 kPa)Output TypeAnalog, RS-232Output0 V ~ 5 V
SeriesPPT2Pressure TypeDifferentialOperating Pressure $\pm 20$ PSI ( $\pm 137.9$ kPa)Output TypeAnalog, RS-232Output $0$ V ~ $5$ V
Pressure Type Differential  Operating Pressure $\pm 20 \text{ PSI } (\pm 137.9 \text{ kPa})$ Output Type Analog, RS-232  Output $\pm 20 \text{ V} \sim 5 \text{ V}$
Operating Pressure $\pm 20$ PSI ( $\pm 137.9$ kPa)  Output Type Analog, RS-232  Output $0 \text{ V} \sim 5 \text{ V}$
Output Type Analog, RS-232 $0 \text{ V} \sim 5 \text{ V}$
Output $0 \text{ V} \sim 5 \text{ V}$
Accuracy +0.0375%
10.031370
Voltage - Supply 6 V ~ 34 V
Port Size Female - 1/8" (3.18mm) Swagelok?, Filter
Port Style Filtered, Threaded
Features -
Termination Style Connector
Maximum Pressure $\pm 60 \text{ PSI } (\pm 413.69 \text{ kPa})$
Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$
Package / Case Module Cube
Supplier Device Package -
Report errors

#### **PPT2-0020DFG2VS Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## PPT2-0020DFG2VS Payment Methods



















### PPT2-0020DFG2VS Shipping Methods













If you have any question about PPT2-0020DFG2VS, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com