

# PPT2-0020GKG2VS

#### **PPT2-0020GKG2VS Information**

Heisener.com	 PPT2-0020GKG2VS Honeywell Microelectronics & Precision Sensors Sensors, Transducers Pressure Sensors, Transducers PRESSURE TRANSDUCER Module Cube For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## **PPT2-0020GKG2VS Specifications**

Manufacturer Part NumberPPT2-0020GKG2VSManufacturerHoneywell Microelectronics & Precision SensorsCategorySensors, TransducersPackageModule CubeSeriesPPT2Pressure TypeVented GaugeOperating Pressure20 PS1 (137.9 kPa)Output TypeAnalog, RS-232Output0 V ~ 5 VAccuracy±0.0375%Yoltage - SupplyFenale - 1/8" (3.18mm) Swagelok?, Male - 1/8" (3.18mm) Swagelok?Port Syle-Fentures-Termination Style60 PSI (413.69 kPa)Operating Tenseure60 PSI (413.69 kPa)Operating Tenseure-Port SyleAndoc Case S°CPackage / CaseModule CubePackage / CasePackage / Case <th></th> <th></th> <th></th>				
CategorySensors, TransducersPackageModule CubeSeriesPPT2Pressure TypeVented GaugeOperating Pressure20 PSI (137.9 kPa)Output TypeAnalog, RS-232Output0 V ~ 5 VAccuracy±0.0375%Voltage - Supply6 V ~ 34 VPort SizeFemale - 1/8" (3.18mm) Swagelok?, Male - 1/8" (3.18mm) Swagelok?Port StyleConnectorMaximum Pressure60 PSI (413.69 kPa)Operating Temperature-40°C ~ 85°CPackage / Case-Supplier Device Package-	Manufacturer Part Number	PPT2-0020GKG2VS		
PackagePressure Sensors, TransducersPackageModule CubeSeriesPPT2Pressure TypeVented GaugeOperating Pressure20 PSI (137.9 kPa)Output TypeAnalog, RS-232Output0 V ~ 5 VAccuracy±0.0375%Voltage - Supply6 V ~ 34 VPort SizeFenale - 1/8" (3.18mm) Swagelok?, Male - 1/8" (3.18mm) Swagelok?Port StyleConnectorTermination Style6 O PSI (413.69 kPa)Operating Temperature-40°C ~ 85°CPackage / Case.Supplier Device Package-	Manufacturer	Honeywell Microelectronics & Precision Sensors		
PackageModule CubeSeriesPPT2Pressure TypeVented GaugeOperating Pressure20 PSI (137.9 kPa)Output TypeAnalog, RS-232Output0 V ~ 5 VAccuracy±0.0375%Voltage - Supply6 V ~ 34 VPort SizeFemale - 1/8" (3.18mm) Swagelok?, Male - 1/8" (3.18mm) Swagelok?Port Style-Features-Maximum Pressure60 PSI (413.69 kPa)Operating Temperature40°C ~ 85°CPackage / Case-Supplier Device Package-	Category	Sensors, Transducers		
SeriesPPT2Pressure TypeVented GaugeOperating Pressure20 PSI (137.9 kPa)Output TypeAnalog, RS-232Output0 V ~ 5 VAccuracy±0.0375%Voltage - Supply6 V ~ 34 VPort SizeFemale - 1/8" (3.18mm) Swagelok?, Male - 1/8" (3.18mm) Swagelok?Port Style-Features-Termination Style60 PSI (413.69 kPa)Operating Temperature-40°C ~ 85°CPackage / CaseModule CubeSupplier Device Package-		Pressure Sensors, Transducers		
Pressure TypeVented GaugeOperating Pressure20 PSI (137.9 kPa)Output TypeAnalog, RS-232Output0 V ~ 5 VAccuracy±0.0375%Voltage - Supply6 V ~ 34 VPort SizeFemale - 1/8" (3.18mm) Swagelok?, Male - 1/8" (3.18mm) Swagelok?Port Style-Features-Termination Style60 PSI (413.69 kPa)Operating Temperature60 PSI (413.69 kPa)Operating Temperatures-Package / CaseModule CubeSupplier Device Package-	Package	Module Cube		
Operating Pressure20 PSI (137.9 kPa)Output TypeAnalog, RS-232Output0 V ~ 5 VAccuracy±0.0375%Voltage - Supply6 V ~ 34 VPort SizeFemale - 1/8" (3.18mm) Swagelok?, Male - 1/8" (3.18mm) Swagelok?Port StyleThreadedFeatures-Termination Style60 PSI (413.69 kPa)Operating Temperature-40°C ~ 85°CPackage / CaseModule CubeSupplier Device Package-	Series	PPT2		
Output TypeAnalog, RS-232Output0 V ~ 5 VAccuracy±0.0375%Voltage - Supply6 V ~ 34 VPort SizeFemale - 1/8" (3.18mm) Swagelok?, Male - 1/8" (3.18mm) Swagelok?Port StyleThreadedFeatures-Termination StyleConnectorMaximum Pressure60 PSI (413.69 kPa)Operating Temperature-40°C ~ 85°CPackage / CaseModule CubeSupplier Device Package-	Pressure Type	Vented Gauge		
Output0 V ~ 5 VAccuracy±0.0375%Voltage - Supply6 V ~ 34 VPort SizeFemale - 1/8" (3.18mm) Swagelok?, Male - 1/8" (3.18mm) Swagelok?Port StyleThreadedFeatures-Termination StyleConnectorMaximum Pressure60 PSI (413.69 kPa)Operating Temperature-40°C ~ 85°CPackage / CaseModule CubeSupplier Device Package-	Operating Pressure	20 PSI (137.9 kPa)		
Accuracy±0.0375%Voltage - Supply6 V ~ 34 VPort SizeFemale - 1/8" (3.18mm) Swagelok?, Male - 1/8" (3.18mm) Swagelok?Port StyleThreadedFeatures-Termination StyleConnectorMaximum Pressure60 PSI (413.69 kPa)Operating Temperature-40°C ~ 85°CPackage / CaseModule CubeSupplier Device Package-	Output Type	Analog, RS-232		
Voltage - Supply6 V ~ 34 VPort SizeFemale - 1/8" (3.18mm) Swagelok?, Male - 1/8" (3.18mm) Swagelok?Port StyleThreadedFeatures-Termination StyleConnectorMaximum Pressure60 PSI (413.69 kPa)Operating Temperature-40°C ~ 85°CPackage / CaseModule CubeSupplier Device Package-	Output	0 V ~ 5 V		
Port SizeFemale - 1/8" (3.18mm) Swagelok?, Male - 1/8" (3.18mm) Swagelok?Port StyleThreadedFeatures-Termination StyleConnectorMaximum Pressure60 PSI (413.69 kPa)Operating Temperature-40°C ~ 85°CPackage / CaseModule CubeSupplier Device Package-	Accuracy	$\pm 0.0375\%$		
Port StyleThreadedFeatures-Termination StyleConnectorMaximum Pressure60 PSI (413.69 kPa)Operating Temperature-40°C ~ 85°CPackage / CaseModule CubeSupplier Device Package-	Voltage - Supply	6 V ~ 34 V		
Features-Features-Termination StyleConnectorMaximum Pressure60 PSI (413.69 kPa)Operating Temperature-40°C ~ 85°CPackage / CaseModule CubeSupplier Device Package-	Port Size	Female - 1/8" (3.18mm) Swagelok?, Male - 1/8" (3.18mm) Swagelok?		
Termination StyleConnectorMaximum Pressure60 PSI (413.69 kPa)Operating Temperature-40°C ~ 85°CPackage / CaseModule CubeSupplier Device Package-	Port Style	Threaded		
Maximum Pressure60 PSI (413.69 kPa)Operating Temperature-40°C ~ 85°CPackage / CaseModule CubeSupplier Device Package-	Features	-		
Operating Temperature-40°C ~ 85°CPackage / CaseModule CubeSupplier Device Package-	Termination Style	Connector		
Package / Case Module Cube   Supplier Device Package -	Maximum Pressure	60 PSI (413.69 kPa)		
Supplier Device Package -	Operating Temperature	$-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$		
	Package / Case	Module Cube		
Description	Supplier Device Package	-		
Report errors			Report errors?	

#### **PPT2-0020GKG2VS Guarantees**



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE BUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

# **PPT2-0020GKG2VS Payment Methods**



### **PPT2-0020GKG2VS Shipping Methods**



If you have any question about PPT2-0020GKG2VS, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com