



PPT2-0100GFG5VS Information

Heisener.com

Part Number PPT2-0100GFG5VS

Manufacturer Honeywell Microelectronics & Precision Sensors

Category Sensors, Transducers

Pressure Sensors, Transducers

Description PRESSURE TRANSDUCER

Package Module Cube

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PPT2-0100GFG5VS Specifications

Manufacturer Part Number PPT2-0100GFG5VS Manufacturer Honeywell Microelectronics & Precision Sensors Category Sensors, Transducers Package Module Cube Series PPT2 Pressure Type Vented Gauge Operating Pressure 100 PSI (689.48 kPa) Output Type Analog, RS-485 Output 0 V ~ 5 V Accuracy ±0.0375% Voltage - Supply 6 V ~ 34 V Port Size Female - 1/8" (3.18mm) Swagelok?, Filter Port Style Filtered, Threaded Features - Termination Style Connector Maximum Pressure 300 PSI (2068.43 kPa) Operating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package - Report errors?			
CategorySensors, TransducersPackageModule CubeSeriesPPT2Pressure TypeVented GaugeOperating Pressure100 PSI (689.48 kPa)Output TypeAnalog, RS-485Output0 V ~ 5 VAccuracy±0.0375%Voltage - Supply6 V ~ 34 VPort SizeFemale - 1/8" (3.18mm) Swagelok?, FilterPort StyleFiltered, ThreadedFeatures-Termination StyleConnectorMaximum Pressure300 PSI (2068.43 kPa)Operating Temperature-40°C ~ 85°CPackage / CaseModule CubeSupplier Device Package-	Manufacturer Part Number	PPT2-0100GFG5VS	
Package Module Cube Series PPT2 Pressure Type Vented Gauge Operating Pressure Oortout Oor	Manufacturer	Honeywell Microelectronics & Precision Sensors	
PackageModule CubeSeriesPPT2Pressure TypeVented GaugeOperating Pressure100 PSI (689.48 kPa)Output TypeAnalog, RS-485Output0 V ~ 5 VAccuracy±0.0375%Voltage - Supply6 V ~ 34 VPort SizeFemale - 1/8" (3.18mm) Swagelok?, FilterPort StyleFiltered, ThreadedFeatures-Termination StyleConnectorMaximum Pressure300 PSI (2068.43 kPa)Operating Temperature-40°C ~ 85°CPackage / CaseModule CubeSupplier Device Package-	Category	Sensors, Transducers	
PPT2 Pressure Type Vented Gauge Operating Pressure 100 PSI (689.48 kPa) Output Type Analog, RS-485 Output 0 V ~ 5 V Accuracy ±0.0375% Voltage - Supply 6 V ~ 34 V Port Size Female - 1/8" (3.18mm) Swagelok?, Filter Port Style Filtered, Threaded Features - Termination Style Connector Maximum Pressure 300 PSI (2068.43 kPa) Operating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package -		Pressure Sensors, Transducers	
Pressure TypeVented GaugeOperating Pressure100 PSI (689.48 kPa)Output TypeAnalog, RS-485Output0 V ~ 5 VAccuracy±0.0375%Voltage - Supply6 V ~ 34 VPort SizeFemale - 1/8" (3.18mm) Swagelok?, FilterPort StyleFiltered, ThreadedFeatures-Termination StyleConnectorMaximum Pressure300 PSI (2068.43 kPa)Operating Temperature-40°C ~ 85°CPackage / CaseModule CubeSupplier Device Package-	Package	Module Cube	
Operating Pressure $100 \text{ PSI } (689.48 \text{ kPa})$ Output Type $Analog, RS-485$ Output $0 \text{ V} \sim 5 \text{ V}$ Accuracy $\pm 0.0375\%$ Voltage - Supply $6 \text{ V} \sim 34 \text{ V}$ Port Size $Female - 1/8$ " $(3.18 \text{mm}) \text{ Swagelok?}$, Filter Port Style $Filtered, Threaded$ Features - Termination Style $Connector$ Maximum Pressure $Connector$ Maximum Pressure $Connector$ Maximum Pressure $Connector$ Package / Case $Connector$ Module Cube Supplier Device Package $Connector$	Series	PPT2	
Output TypeAnalog, RS-485Output $0 \text{ V} \sim 5 \text{ V}$ Accuracy $\pm 0.0375\%$ Voltage - Supply $6 \text{ V} \sim 34 \text{ V}$ Port SizeFemale - $1/8$ " (3.18mm) Swagelok?, FilterPort StyleFiltered, ThreadedFeatures-Termination StyleConnectorMaximum Pressure $300 \text{ PSI } (2068.43 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / CaseModule CubeSupplier Device Package-	Pressure Type	Vented Gauge	
Output $0 \text{ V} \sim 5 \text{ V}$ Accuracy $\pm 0.0375\%$ Voltage - Supply $6 \text{ V} \sim 34 \text{ V}$ Port SizeFemale - $1/8$ " (3.18mm) Swagelok?, FilterPort StyleFiltered, ThreadedFeatures-Termination StyleConnectorMaximum Pressure $300 \text{ PSI } (2068.43 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / CaseModule CubeSupplier Device Package-	Operating Pressure	100 PSI (689.48 kPa)	
Accuracy ±0.0375% Voltage - Supply 6 V ~ 34 V Port Size Female - 1/8" (3.18mm) Swagelok?, Filter Port Style Filtered, Threaded Features - Connector Maximum Pressure 300 PSI (2068.43 kPa) Operating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package -	Output Type	Analog, RS-485	
Voltage - Supply 6 V ~ 34 V Port Size Female - 1/8" (3.18mm) Swagelok?, Filter Port Style Filtered, Threaded Features - Termination Style Connector Maximum Pressure 300 PSI (2068.43 kPa) Operating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package -	Output	0 V ~ 5 V	
Port Size Female - 1/8" (3.18mm) Swagelok?, Filter Port Style Filtered, Threaded Features - Termination Style Connector Maximum Pressure 300 PSI (2068.43 kPa) Operating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package -	Accuracy	±0.0375%	
Port Style Filtered, Threaded Features - Termination Style Connector Maximum Pressure 300 PSI (2068.43 kPa) Operating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package -	Voltage - Supply	6 V ~ 34 V	
Features - Connector Maximum Pressure 300 PSI (2068.43 kPa) Operating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package -	Port Size	Female - 1/8" (3.18mm) Swagelok?, Filter	
Termination Style Connector Maximum Pressure 300 PSI (2068.43 kPa) Operating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package -	Port Style	Filtered, Threaded	
Maximum Pressure300 PSI (2068.43 kPa)Operating Temperature-40°C ~ 85°CPackage / CaseModule CubeSupplier Device Package-	Features	-	
Operating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package -	Termination Style	Connector	
Package / Case Module Cube Supplier Device Package -	Maximum Pressure	300 PSI (2068.43 kPa)	
Supplier Device Package -	Operating Temperature	-40°C ~ 85°C	
	Package / Case	Module Cube	
Report errors?	Supplier Device Package	-	
		Report error	s?

PPT2-0100GFG5VS Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PPT2-0100GFG5VS Payment Methods



















PPT2-0100GFG5VS Shipping Methods













If you have any question about PPT2-0100GFG5VS, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com