

PPT2-0100GKX2VS

Quote

PPT2-0100GKX2VS Information

	Part Number	PPT2-0100GKX2VS	
		Honeywell Microelectronics & Precision Sensors	(CI 977)
(A) Heisener.com	Category	Sensors, Transducers Pressure Sensors, Transducers	
Gittal service parts rais	Description	PRESSURE TRANSDUCER	
	Package	Module Cube	
		For the pricing/inventory/lead time, please contact	E10576
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



PPT2-0100GKX2VS Specifications

Manufacturer Part NumberPPT2-0100GKX2VSManufacturerHoneywell Microelectronics & Precision SensorsCategorySensors, TransducersPackageModule CubePackageModule CubeSeriesPPT2Pressure TypeVented GaugeOutput TypeJoD PSI (689.48 kPa)Output0V ~ 5 VAccuracy±0.0375%Voltage - Supply6 V ~ 34 VPort SizeFemale - 1/8" (3.18mm) Swagelok?, Male - 1/8" (3.18mm) Swagelok?
CategorySensors, TransducersPressure Sensors, TransducersPackageModule CubeSeriesPPT2Pressure TypeVented GaugeOperating Pressure100 PSI (689.48 kPa)Output TypeAnalog, RS-232Output0 V ~ 5 VAccuracy±0.0375%Voltage - Supply6 V ~ 34 V
Pressure Sensors, TransducersPackageModule CubeSeriesPPT2Pressure TypeVented GaugeOperating Pressure100 PSI (689.48 kPa)Output TypeAnalog, RS-232Output0 V ~ 5 VAccuracy±0.0375%Voltage - Supply6 V ~ 34 V
PackageModule CubeSeriesPPT2Pressure TypeVented GaugeOperating Pressure100 PSI (689.48 kPa)Output TypeAnalog, RS-232Output0 V ~ 5 VAccuracy±0.0375%Voltage - Supply6 V ~ 34 V
SeriesPPT2Pressure TypeVented GaugeOperating Pressure100 PSI (689.48 kPa)Output TypeAnalog, RS-232Output0 V ~ 5 VAccuracy±0.0375%Voltage - Supply6 V ~ 34 V
Pressure TypeVented GaugeOperating Pressure100 PSI (689.48 kPa)Output TypeAnalog, RS-232Output0 V ~ 5 VAccuracy±0.0375%Voltage - Supply6 V ~ 34 V
Operating Pressure 100 PSI (689.48 kPa) Output Type Analog, RS-232 Output 0 V ~ 5 V Accuracy ±0.0375% Voltage - Supply 6 V ~ 34 V
Output TypeAnalog, RS-232Output0 V ~ 5 VAccuracy±0.0375%Voltage - Supply6 V ~ 34 V
Output0 V ~ 5 VAccuracy±0.0375%Voltage - Supply6 V ~ 34 V
Accuracy±0.0375%Voltage - Supply6 V ~ 34 V
Voltage - Supply 6 V ~ 34 V
Port Size Female - 1/8" (3.18mm) Swagelok?, Male - 1/8" (3.18mm) Swagelok?
Port Style Threaded
Features -
Termination Style Connector
Maximum Pressure300 PSI (2068.43 kPa)
Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$
Package / Case Module Cube
Supplier Device Package -
Report err

PPT2-0100GKX2VS Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

PPT2-0100GKX2VS Payment Methods



PPT2-0100GKX2VS Shipping Methods



If you have any question about PPT2-0100GKX2VS, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com