



# PPT2-0500GXF2VS Information

Heisener.com

Part Number PPT2-0500GXF2VS

Manufacturer Honeywell Microelectronics & Precision Sensors

Category Sensors, Transducers

Pressure Sensors, Transducers

**Description** PRESSURE TRANSDUCER

Package Module Cube

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# PPT2-0500GXF2VS Specifications

Manufacturer Part Number       PPT2-0500GXF2VS         Manufacturer       Honeywell Microelectronics & Precision Sensors         Category       Sensors, Transducers         Package       Module Cube         Series       PPT2         Pressure Type       Vented Gauge         Operating Pressure       500 PSI (3447.38 kPa)         Output Type       Analog, RS-232         Output       0 V ~ 5 V         Accuracy       ±0.0375%         Voltage - Supply       6 V ~ 34 V         Port Size       Female - 1/8" (3.18mm) Swagelok?, Filter         Port Style       Filtered, Threaded         Features       -         Termination Style       Connector         Maximum Pressure       600 PSI (4136.85 kPa)         Operating Temperature       -40°C ~ 85°C         Package / Case       Module Cube         Supplier Device Package       -         Report errors?		
Category         Sensors, Transducers           Package         Module Cube           Series         PPT2           Pressure Type         Vented Gauge           Operating Pressure         500 PSI (3447.38 kPa)           Output Type         Analog, RS-232           Output         0 V ~ 5 V           Accuracy         ±0.0375%           Voltage - Supply         6 V ~ 34 V           Port Size         Female - 1/8" (3.18mm) Swagelok?, Filter           Port Style         Filtered, Threaded           Features         -           Termination Style         Connector           Maximum Pressure         600 PSI (4136.85 kPa)           Operating Temperature         -40°C ~ 85°C           Package / Case         Module Cube           Supplier Device Package         -	Manufacturer Part Number	PPT2-0500GXF2VS
Package Module Cube Series PPT2 Pressure Type Vented Gauge Operating Pressure 500 PSI (3447.38 kPa) Output Type Analog, RS-232 Output 0 V ~ 5 V Accuracy ±0.0375% Voltage - Supply 6 V ~ 34 V Port Size Female - 1/8" (3.18mm) Swagelok?, Filter Port Style Filtered, Threaded Features - Termination Style Connector Maximum Pressure 600 PSI (4136.85 kPa) Operating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package	Manufacturer	Honeywell Microelectronics & Precision Sensors
Package         Module Cube           Series         PPT2           Pressure Type         Vented Gauge           Operating Pressure         500 PSI (3447.38 kPa)           Output Type         Analog, RS-232           Output         0 V ~ 5 V           Accuracy         ±0.0375%           Voltage - Supply         6 V ~ 34 V           Port Size         Female - 1/8" (3.18mm) Swagelok?, Filter           Port Style         Filtered, Threaded           Features         -           Termination Style         Connector           Maximum Pressure         600 PSI (4136.85 kPa)           Operating Temperature         -40°C ~ 85°C           Package / Case         Module Cube           Supplier Device Package         -	Category	Sensors, Transducers
SeriesPPT2Pressure TypeVented GaugeOperating Pressure500 PSI (3447.38 kPa)Output TypeAnalog, RS-232Output0 V ~ 5 VAccuracy±0.0375%Voltage - Supply6 V ~ 34 VPort SizeFemale - 1/8" (3.18mm) Swagelok?, FilterPort StyleFiltered, ThreadedFeatures-Termination StyleConnectorMaximum Pressure600 PSI (4136.85 kPa)Operating Temperature-40°C ~ 85°CPackage / CaseModule CubeSupplier Device Package-		Pressure Sensors, Transducers
Pressure Type Vented Gauge Operating Pressure 500 PSI (3447.38 kPa) Output Type Analog, RS-232 Output 0 V ~ 5 V Accuracy ±0.0375% Voltage - Supply 6 V ~ 34 V Port Size Female - 1/8" (3.18mm) Swagelok?, Filter Port Style Filtered, Threaded Features - Termination Style Connector Maximum Pressure 600 PSI (4136.85 kPa) Operating Temperature -40°C ~ 85°C Package / Case Module Cube Supplier Device Package -	Package	Module Cube
Operating Pressure  500 PSI (3447.38 kPa)  Output Type  Analog, RS-232  Output  0 V ~ 5 V  Accuracy  ±0.0375%  Voltage - Supply  6 V ~ 34 V  Port Size  Female - 1/8" (3.18mm) Swagelok?, Filter  Port Style  Filtered, Threaded  Features  - Termination Style  Connector  Maximum Pressure  600 PSI (4136.85 kPa)  Operating Temperature  -40°C ~ 85°C  Package / Case  Module Cube  Supplier Device Package  -  100 PSI (436.85 kPa)  Analog, RS-232  0 V ~ 5 V  Analog, RS-232  0 V ~ 5 V  Analog, RS-232  0 V ~ 5 V  Analog, RS-232  60 V ~ 34 V  Female - 1/8" (3.18mm) Swagelok?, Filter  Filtered, Threaded  Features  -40°C ~ 85°C  Module Cube  Supplier Device Package	Series	PPT2
Output TypeAnalog, RS-232Output $0 \text{ V} \sim 5 \text{ V}$ Accuracy $\pm 0.0375\%$ Voltage - Supply $6 \text{ V} \sim 34 \text{ V}$ Port SizeFemale - $1/8$ " (3.18mm) Swagelok?, FilterPort StyleFiltered, ThreadedFeatures-Termination StyleConnectorMaximum Pressure $600 \text{ PSI } (4136.85 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / CaseModule CubeSupplier Device Package-	Pressure Type	Vented Gauge
Output $0 \text{ V} \sim 5 \text{ V}$ Accuracy $\pm 0.0375\%$ Voltage - Supply $6 \text{ V} \sim 34 \text{ V}$ Port Size Female - $1/8$ " $(3.18\text{mm})$ Swagelok?, Filter  Port Style Filtered, Threaded  Features -  Termination Style Connector  Maximum Pressure $600 \text{ PSI } (4136.85 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case Module Cube  Supplier Device Package -	Operating Pressure	500 PSI (3447.38 kPa)
Accuracy ±0.0375%  Voltage - Supply 6 V ~ 34 V  Port Size Female - 1/8" (3.18mm) Swagelok?, Filter  Port Style Filtered, Threaded  Features - Connector  Maximum Pressure 600 PSI (4136.85 kPa)  Operating Temperature -40°C ~ 85°C  Package / Case Module Cube  Supplier Device Package -	Output Type	Analog, RS-232
Voltage - Supply  6 V ~ 34 V  Port Size  Female - 1/8" (3.18mm) Swagelok?, Filter  Port Style  Filtered, Threaded  Features  - Termination Style  Connector  Maximum Pressure  600 PSI (4136.85 kPa)  Operating Temperature  -40°C ~ 85°C  Package / Case  Module Cube  Supplier Device Package  -	Output	0 V ~ 5 V
Port Size  Female - 1/8" (3.18mm) Swagelok?, Filter  Port Style  Filtered, Threaded  Features  - Termination Style  Connector  Maximum Pressure  600 PSI (4136.85 kPa)  Operating Temperature  -40°C ~ 85°C  Package / Case  Module Cube  Supplier Device Package  -	Accuracy	±0.0375%
Port Style Filtered, Threaded  Features -  Termination Style Connector  Maximum Pressure 600 PSI (4136.85 kPa)  Operating Temperature -40°C ~ 85°C  Package / Case Module Cube  Supplier Device Package -	Voltage - Supply	6 V ~ 34 V
Features - Termination Style Connector  Maximum Pressure 600 PSI (4136.85 kPa)  Operating Temperature -40°C ~ 85°C  Package / Case Module Cube  Supplier Device Package -	Port Size	Female - 1/8" (3.18mm) Swagelok?, Filter
Termination Style  Connector  Maximum Pressure  600 PSI (4136.85 kPa)  Operating Temperature  -40°C ~ 85°C  Package / Case  Module Cube  Supplier Device Package  -	Port Style	Filtered, Threaded
Maximum Pressure600 PSI (4136.85 kPa)Operating Temperature-40°C ~ 85°CPackage / CaseModule CubeSupplier Device Package-	Features	-
Operating Temperature -40°C ~ 85°C  Package / Case Module Cube  Supplier Device Package -	Termination Style	Connector
Package / Case Module Cube Supplier Device Package -	Maximum Pressure	600 PSI (4136.85 kPa)
Supplier Device Package -	Operating Temperature	-40°C ~ 85°C
	Package / Case	Module Cube
Report errors?	Supplier Device Package	-
		Report errors?

#### PPT2-0500GXF2VS Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# PPT2-0500GXF2VS Payment Methods





















### PPT2-0500GXF2VS Shipping Methods













If you have any question about PPT2-0500GXF2VS, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com