

# PPT2-0500GXK2VS

Quote

#### **PPT2-0500GXK2VS Information**

Heisener.com	Part Number	PPT2-0500GXK2VS	
	Manufacturer	Honeywell Microelectronics & Precision Sensors	TELL PRO
	Category	Sensors, Transducers Pressure Sensors, Transducers	
	Description	PRESSURE TRANSDUCER	- 9.21
	Package	Module Cube	
		For the pricing/inventory/lead time, please contact	
For Reference Only		us	
		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



### **PPT2-0500GXK2VS Specifications**

Manufacturer Part NumberPPT2-0500GXK2VSManufacturerHoneywell Microelectronics & Precision SensorsCategorySensors, TransducersPackageModule CubePackagePPT2Perseure Sensors, TransducersPressure Sensors, TransducersOperating PressureVented GaugeOutput TypeAnalog, RS-232Output0V ~ 5 VAccuracy600/375%Voltage - Supply61 × 34 VPort SizeFenale - 1/8" (3.18mm) Swagelok?, Male - 1/8" (3.18mm) Swagelok?Port Style.Features.ComectorGonectorMaximum Pressure600 PSI (436.85 kPa)Operating Temperature.40°C ~ 85°C.				
CategorySensors, TransducersPackageModule CubeSeriesPPT2Pressure TypeVented GaugeOperating Pressure500 PSI (3447.38 kPa)Output TypeAnalog, RS-232Output0 V ~ 5 VAccuracy±0.0375%Voltage - SupplyFemale - 1/8" (3.18mm) Swagelok?, Male - 1/8" (3.18mm) Swagelok?Port Style-Feratures-Termination StyleG00 PSI (4136.85 kPa)Operating Temperature40°C ~ 85°C	Manufacturer Part Number	PPT2-0500GXK2VS		
PackagePressure Sensors, TransducersPackageModule CubeSeriesPPT2Pressure TypeVented GaugeOperating Pressure500 PSI (3447.38 kPa)Output TypeAnalog, RS-232Output0 V ~ 5 VAccuracy±0.0375%Voltage - Supply6 V ~ 34 VPort SizeFemale - 1/8" (3.18mm) Swagelok?, Male - 1/8" (3.18mm) Swagelok?Port Style-Feratures-Termination StyleConnectorMaximum Pressure600 PSI (4136.85 kPa)Operating Temperature-40°C ~ 85°C	Manufacturer	Honeywell Microelectronics & Precision Sensors		
PackageModule CubeSeriesPPT2Pressure TypeVented GaugeOperating Pressure500 PSI (3447.38 kPa)Output TypeAnalog, RS-232Output0 V ~ 5 VAccuracy±0.0375%Voltage - Supply6 V ~ 34 VPort SizeFemale - 1/8" (3.18mm) Swagelok?, Male - 1/8" (3.18mm) Swagelok?Port Style.Features.Termination StyleConnectorMaximum Pressure600 PSI (4136.85 kPa)Operating Temperature40°C ~ 85°C	Category	Sensors, Transducers		
Series PPT2   Pressure Type Vented Gauge   Operating Pressure 500 PSI (3447.38 kPa)   Output Type Analog, RS-232   Output 0 V ~ 5 V   Accuracy ±0.0375%   Voltage - Supply 6 V ~ 34 V   Port Size Female - 1/8" (3.18mm) Swagelok?, Male - 1/8" (3.18mm) Swagelok?   Port Style Threaded   Features -   Termination Style Gonector   Maximum Pressure 600 PSI (4136.85 kPa)   Operating Temperature -40°C ~ 85°C		Pressure Sensors, Transducers		
Pressure TypeVented GaugeOperating Pressure500 PSI (3447.38 kPa)Output TypeAnalog, RS-232Output0 V ~ 5 VAccuracy±0.0375%Voltage - Supply6 V ~ 34 VPort SizeFemale - 1/8" (3.18mm) Swagelok?, Male - 1/8" (3.18mm) Swagelok?Port Style-Features-Termination StyleConnectorMaximum Pressure600 PSI (4136.85 kPa)Operating Temperature-40°C ~ 85°C	Package	Module Cube		
Operating Pressure500 PSI (3447.38 kPa)Output TypeAnalog, RS-232Output0 V ~ 5 VAccuracy±0.0375%Voltage - Supply6 V ~ 34 VPort SizeFemale - 1/8" (3.18mm) Swagelok?, Male - 1/8" (3.18mm) Swagelok?Port StyleThreadedFeatures-Termination Style600 PSI (4136.85 kPa)Operating Temperature-40°C ~ 85°C	Series	PPT2		
Output TypeAnalog, RS-232Output0 V ~ 5 VAccuracy±0.0375%Voltage - Supply6 V ~ 34 VPort SizeFemale - 1/8" (3.18mm) Swagelok?, Male - 1/8" (3.18mm) Swagelok?Port StyleThreadedFeatures-Termination StyleConnectorMaximum Pressure600 PSI (4136.85 kPa)Operating Temperature-40°C ~ 85°C	Pressure Type	Vented Gauge		
Output $0 \vee 5 \vee$ Accuracy $\pm 0.0375\%$ Voltage - Supply $6 \vee 34 \vee$ Port Size Female - 1/8" (3.18mm) Swagelok?, Male - 1/8" (3.18mm) Swagelok?   Port Style Threaded   Features -   Termination Style Connector   Maximum Pressure $600 \operatorname{PSI}(4136.85 \operatorname{kPa})$ Operating Temperature $40^\circ$ C ~ 85°C	Operating Pressure	500 PSI (3447.38 kPa)		
Accuracy±0.0375%Voltage - Supply6 V ~ 34 VPort SizeFemale - 1/8" (3.18mm) Swagelok?, Male - 1/8" (3.18mm) Swagelok?Port StyleThreadedFeatures-Termination StyleConnectorMaximum Pressure600 PSI (4136.85 kPa)Operating Temperature-40°C ~ 85°C	Output Type	Analog, RS-232		
Voltage - Supply6 V ~ 34 VPort SizeFemale - 1/8" (3.18mm) Swagelok?, Male - 1/8" (3.18mm) Swagelok?Port StyleThreadedFeatures-Termination StyleConnectorMaximum Pressure600 PSI (4136.85 kPa)Operating Temperature-40°C ~ 85°C	Output	0 V ~ 5 V		
Port SizeFemale - 1/8" (3.18mm) Swagelok?, Male - 1/8" (3.18mm) Swagelok?Port StyleThreadedFeatures-Termination StyleConnectorMaximum Pressure600 PSI (4136.85 kPa)Operating Temperature-40°C ~ 85°C	Accuracy	$\pm 0.0375\%$		
Port StyleThreadedFeatures-Termination StyleConnectorMaximum Pressure600 PSI (4136.85 kPa)Operating Temperature-40°C ~ 85°C	Voltage - Supply	6 V ~ 34 V		
Features-Termination StyleConnectorMaximum Pressure600 PSI (4136.85 kPa)Operating Temperature-40°C ~ 85°C	Port Size	Female - 1/8" (3.18mm) Swagelok?, Male - 1/8" (3.18mm) Swagelok?		
Termination StyleConnectorMaximum Pressure600 PSI (4136.85 kPa)Operating Temperature-40°C ~ 85°C	Port Style	Threaded		
Maximum Pressure600 PSI (4136.85 kPa)Operating Temperature-40°C ~ 85°C	Features	-		
Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$	Termination Style	Connector		
	Maximum Pressure	600 PSI (4136.85 kPa)		
	Operating Temperature	$-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$		
Package / Case Module Cube	Package / Case	Module Cube		
Supplier Device Package -	Supplier Device Package	-		
Report error			Report errors?	

#### **PPT2-0500GXK2VS Guarantees**



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE BUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### PPT2-0500GXK2VS Payment Methods



#### **PPT2-0500GXK2VS Shipping Methods**



If you have any question about PPT2-0500GXK2VS, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com