



PPTC072KFMS Information

www.helsener.com

For Reference Only

Part Number PPTC072KFMS

ManufacturerSullins Connector SolutionsCategoryConnectors, Interconnects

Rectangular Connectors - Headers, Receptacles,

Female Sockets

Description CONN FEMALE 14POS DL .1" TIN SMD

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PPTC072KFMS Specifications

Manufacturer Part Number PPTC072KFMS Manufacturer Sullins Connector Solutions Category Connectors, Interconnects Package - Series - Connector Type Header Contact Type Female Socket Style Board to Board Number of Positions 14 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 2 Row Spacing - Mating 0.100" (2.54mm) Mounting Type Surface Mount Termination Solder Fastening Type Push-Pull Contact Finish - Mating - Contact Finish Thickness - Mating - Insulation Color Black Insulation Height 0.299" (7.60mm) Contact Length - Post - Operating Temperature -40°C ~ 125°C Material Flammability Rating UL94 V-0					
Category Connectors, Interconnects Package - Series - Connector Type Header Contact Type Female Socket Style Board to Board Number of Positions 14 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 2 Row Spacing - Mating 0.100" (2.54mm) Mounting Type Surface Mount Termination Solder Fastening Type Push-Pull Contact Finish - Mating Tin Contact Finish Thickness - Mating - Insulation Color Black Insulation Height 0.299" (7.60mm) Contact Length - Post - Operating Temperature -40°C ~ 125°C	Manufacturer Part Number	PPTC072KFMS			
Package-Series-Connector TypeHeaderContact TypeFemale SocketStyleBoard to BoardNumber of Positions14Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - Mating-Contact Finish Thickness - Mating-Insulation ColorBlackInsulation Height0.299" (7.60mm)Contact Length - Post-Operating Temperature-40°C ~ 125°C	Manufacturer	Sullins Connector Solutions			
Package - Series - Connector Type Header Contact Type Female Socket Style Board to Board Number of Positions 14 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 2 Row Spacing - Mating 0.100" (2.54mm) Mounting Type Surface Mount Termination Solder Fastening Type Push-Pull Contact Finish - Mating Tin Contact Finish Thickness - Mating - Insulation Color Black Insulation Height 0.299" (7.60mm) Contact Length - Post - Operating Temperature -40°C ~ 125°C	Category	Connectors, Interconnects			
Series - Connector Type Header Contact Type Female Socket Style Board to Board Number of Positions 14 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 2 Row Spacing - Mating 0.100" (2.54mm) Mounting Type Surface Mount Termination Solder Fastening Type Push-Pull Contact Finish - Mating Tin Contact Finish Thickness - Mating - Insulation Color Black Insulation Height 0.299" (7.60mm) Contact Length - Post - Operating Temperature -40°C ~ 125°C		Rectangular Connectors - Headers, Receptacles, Female Sockets			
Connector TypeHeaderContact TypeFemale SocketStyleBoard to BoardNumber of Positions14Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingTinContact Finish Thickness - Mating-Insulation ColorBlackInsulation Height0.299" (7.60mm)Contact Length - Post-Operating Temperature-40°C ~ 125°C	Package	-			
Contact TypeFemale SocketStyleBoard to BoardNumber of Positions14Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingTinContact Finish Thickness - Mating-Insulation ColorBlackInsulation Height0.299" (7.60mm)Contact Length - Post-Operating Temperature-40°C ~ 125°C	Series	-			
Style Board to Board Number of Positions 14 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 2 Row Spacing - Mating 0.100" (2.54mm) Mounting Type Surface Mount Termination Solder Fastening Type Push-Pull Contact Finish - Mating Tin Contact Finish Thickness - Mating - Insulation Color Black Insulation Height 0.299" (7.60mm) Contact Length - Post - Operating Temperature -40°C ~ 125°C	Connector Type	Header			
Number of Positions 14 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 2 Row Spacing - Mating 0.100" (2.54mm) Mounting Type Surface Mount Termination Solder Fastening Type Push-Pull Contact Finish - Mating Tin Contact Finish Thickness - Mating - Insulation Color Black Insulation Height 0.299" (7.60mm) Contact Length - Post - Operating Temperature -40°C ~ 125°C	Contact Type	Female Socket			
Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingTinContact Finish Thickness - Mating-Insulation ColorBlackInsulation Height0.299" (7.60mm)Contact Length - Post-Operating Temperature-40°C ~ 125°C	Style	Board to Board			
Pitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingTinContact Finish Thickness - Mating-Insulation ColorBlackInsulation Height0.299" (7.60mm)Contact Length - Post-Operating Temperature-40°C ~ 125°C	Number of Positions	14			
Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingTinContact Finish Thickness - Mating-Insulation ColorBlackInsulation Height0.299" (7.60mm)Contact Length - Post-Operating Temperature-40°C ~ 125°C	Number of Positions Loaded	All			
Row Spacing - Mating0.100" (2.54mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingTinContact Finish Thickness - Mating-Insulation ColorBlackInsulation Height0.299" (7.60mm)Contact Length - Post-Operating Temperature-40°C ~ 125°C	Pitch - Mating	0.100" (2.54mm)			
Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingTinContact Finish Thickness - Mating-Insulation ColorBlackInsulation Height0.299" (7.60mm)Contact Length - Post-Operating Temperature-40°C ~ 125°C	Number of Rows	2			
Termination Solder Fastening Type Push-Pull Contact Finish - Mating Tin Contact Finish Thickness - Mating - Insulation Color Black Insulation Height 0.299" (7.60mm) Contact Length - Post - Operating Temperature -40°C ~ 125°C	Row Spacing - Mating	0.100" (2.54mm)			
Fastening Type Push-Pull Contact Finish - Mating Tin Contact Finish Thickness - Mating - Insulation Color Black Insulation Height 0.299" (7.60mm) Contact Length - Post - Operating Temperature -40°C ~ 125°C	Mounting Type	Surface Mount			
Contact Finish - Mating Contact Finish Thickness - Mating Insulation Color Black Insulation Height 0.299" (7.60mm) Contact Length - Post Operating Temperature -40°C ~ 125°C	Termination	Solder			
Contact Finish Thickness - Mating Insulation Color Black Insulation Height 0.299" (7.60mm) Contact Length - Post - Operating Temperature -40°C ~ 125°C	Fastening Type	Push-Pull			
Insulation ColorBlackInsulation Height $0.299" (7.60mm)$ Contact Length - Post-Operating Temperature -40 °C ~ 125 °C	Contact Finish - Mating	Tin			
Insulation Height 0.299" (7.60mm) Contact Length - Post - Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Contact Finish Thickness - Mating	-			
Contact Length - Post - $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Insulation Color	Black			
Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Insulation Height	0.299" (7.60mm)			
	Contact Length - Post	-			
Material Flammability Rating UL94 V-0	Operating Temperature	-40°C ~ 125°C			
	Material Flammability Rating	UL94 V-0			

Contact Finish - Post	Tin		
Mated Stacking Heights	-		
Ingress Protection	-		
Features	-		
			Report errors?

PPTC072KFMS Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PPTC072KFMS Payment Methods

































If you have any question about PPTC072KFMS, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com