

PRD-3AH0-120 Information

Heisener.com

Part Number PRD-3AH0-120

Manufacturer TE Connectivity Potter & Brumfield Relays

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE SPST 20A 120V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PRD-3AH0-120 Specifications

Manufacturer Part Number PRD-3AH0-120 Manufacturer TE Connectivity Potter & Brumfield Relays Category Relays Power Relays, Over 2 Amps Package - Series PRD Relay Type General Purpose Coil Type Non Latching Coil Current 85mA Coil Voltage 120VAC Contact Form SPST-NO (1 Form X) Contact Rating (Current) 20A Switching Voltage 600VAC, 125VDC - Max Turn On Voltage (Max) 102 VAC Turn Off Voltage (Min) 12 VAC Operate Time 40ms Release Time 20ms Features Insulation - Class B Mounting Type Chassis Mount Termination Style Screw Terminal		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesPRDRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current85mACoil Voltage120VACContact FormSPST-NO (1 Form X)Contact Rating (Current)20ASwitching Voltage600VAC, 125VDC - MaxTurn On Voltage (Max)102 VACTurn Off Voltage (Min)12 VACOperate Time40msRelease Time20msFeaturesInsulation - Class BMounting TypeChassis MountTermination StyleScrew Terminal	Manufacturer Part Number	PRD-3AH0-120
Package - Series PRD Relay Type General Purpose Coil Type Non Latching Coil Current 85mA Coil Voltage 120VAC Contact Form SPST-NO (1 Form X) Contact Rating (Current) 20A Switching Voltage 600VAC, 125VDC - Max Turn On Voltage (Max) 102 VAC Turn Off Voltage (Min) 12 VAC Operate Time 40ms Release Time 20ms Features Insulation - Class B Mounting Type Chassis Mount Termination Style Screw Terminal	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package-SeriesPRDRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current85mACoil Voltage120VACContact FormSPST-NO (1 Form X)Contact Rating (Current)20ASwitching Voltage600VAC, 125VDC - MaxTurn On Voltage (Max)102 VACTurn Off Voltage (Min)12 VACOperate Time40msRelease Time20msFeaturesInsulation - Class BMounting TypeChassis MountTermination StyleScrew Terminal	Category	Relays
SeriesPRDRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current85mACoil Voltage120VACContact FormSPST-NO (1 Form X)Contact Rating (Current)20ASwitching Voltage600VAC, 125VDC - MaxTurn On Voltage (Max)102 VACTurn Off Voltage (Min)12 VACOperate Time40msRelease Time20msFeaturesInsulation - Class BMounting TypeChassis MountTermination StyleScrew Terminal		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 85mA Coil Voltage 120VAC Contact Form SPST-NO (1 Form X) Contact Rating (Current) 20A Switching Voltage 600VAC, 125VDC - Max Turn On Voltage (Max) 102 VAC Turn Off Voltage (Min) 12 VAC Operate Time 40ms Release Time 20ms Features Insulation - Class B Mounting Type Chassis Mount Termination Style Semantic Semantic Semantic Semantic Semantic Series Series Series Series Terminal	Package	-
Coil Type Non Latching Coil Current 85mA Coil Voltage 120VAC Contact Form SPST-NO (1 Form X) Contact Rating (Current) 20A Switching Voltage 600VAC, 125VDC - Max Turn On Voltage (Max) 102 VAC Turn Off Voltage (Min) 12 VAC Operate Time 40ms Release Time 20ms Features Insulation - Class B Mounting Type Chassis Mount Termination Style SPST-NO (1 Form X) SPS	Series	PRD
Coil Current85mACoil Voltage120VACContact FormSPST-NO (1 Form X)Contact Rating (Current)20ASwitching Voltage600VAC, 125VDC - MaxTurn On Voltage (Max)102 VACTurn Off Voltage (Min)12 VACOperate Time40msRelease Time20msFeaturesInsulation - Class BMounting TypeChassis MountTermination StyleScrew Terminal	Relay Type	General Purpose
Coil Voltage 120VAC Contact Form SPST-NO (1 Form X) Contact Rating (Current) 20A Switching Voltage 600VAC, 125VDC - Max Turn On Voltage (Max) 102 VAC Turn Off Voltage (Min) 12 VAC Operate Time 40ms Release Time 20ms Features Insulation - Class B Mounting Type Chassis Mount Termination Style SPST-NO (1 Form X) SPST-NO (1 Form X) 20A 20A 20B 102 VAC 102 VAC 103 VAC 104 VAC 105 VAC 107 Voltage (Min) 12 VAC 108 VAC 109 VAC	Coil Type	Non Latching
Contact Form SPST-NO (1 Form X) Contact Rating (Current) 20A Switching Voltage 600VAC, 125VDC - Max Turn On Voltage (Max) 102 VAC Turn Off Voltage (Min) 12 VAC Operate Time 40ms Release Time 20ms Features Insulation - Class B Mounting Type Chassis Mount Termination Style SPST-NO (1 Form X) 20A	Coil Current	85mA
Contact Rating (Current) Switching Voltage 600VAC, 125VDC - Max Turn On Voltage (Max) 102 VAC Turn Off Voltage (Min) 12 VAC Operate Time 40ms Release Time 20ms Features Insulation - Class B Mounting Type Chassis Mount Termination Style Screw Terminal	Coil Voltage	120VAC
Switching Voltage 600VAC, 125VDC - Max Turn On Voltage (Max) 102 VAC Turn Off Voltage (Min) 12 VAC Operate Time 40ms Release Time 20ms Features Insulation - Class B Mounting Type Chassis Mount Termination Style Screw Terminal	Contact Form	SPST-NO (1 Form X)
Turn On Voltage (Max) 102 VAC Turn Off Voltage (Min) 12 VAC Operate Time 40ms Release Time 20ms Features Insulation - Class B Mounting Type Chassis Mount Termination Style Screw Terminal	Contact Rating (Current)	20A
Turn Off Voltage (Min) 12 VAC Operate Time 40ms Release Time 20ms Features Insulation - Class B Mounting Type Chassis Mount Termination Style Screw Terminal	Switching Voltage	600VAC, 125VDC - Max
Operate Time40msRelease Time20msFeaturesInsulation - Class BMounting TypeChassis MountTermination StyleScrew Terminal	Turn On Voltage (Max)	102 VAC
Release Time 20ms Features Insulation - Class B Mounting Type Chassis Mount Termination Style Screw Terminal	Turn Off Voltage (Min)	12 VAC
Features Insulation - Class B Mounting Type Chassis Mount Termination Style Screw Terminal	Operate Time	40ms
Mounting Type Chassis Mount Termination Style Screw Terminal	Release Time	20ms
Termination Style Screw Terminal	Features	Insulation - Class B
	Mounting Type	Chassis Mount
Report errors?	Termination Style	Screw Terminal
L L		Report errors?

PRD-3AH0-120 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PRD-3AH0-120 Payment Methods





















PRD-3AH0-120 Shipping Methods













If you have any question about PRD-3AH0-120, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com