

### PRD-5AY1-120 Information



For Reference Only

Part Number PRD-5AY1-120

Manufacturer TE Connectivity Potter & Brumfield Relays

Category Relays

Power Relays, Over 2 Amps

**Description** RELAY GEN PURPOSE SPDT 25A 120V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## PRD-5AY1-120 Specifications

Manufacturer Part Number         PRD-5AY1-120           Manufacturer         TE Connectivity Potter & Brumfield Relays           Category         Relays           Power Relays, Over 2 Amps           Package         -           Series         PRD           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         85mA           Coil Voltage         120VAC           Contact Form         SPDT (1 Form C)           Contact Rating (Current)         25A           Switching Voltage         600VAC, 125VDC - Max           Turn On Voltage (Max)         102 VAC           Turn Off Voltage (Min)         12 VAC           Operate Time         40ms           Release Time         20ms           Features         Insulation - Class B           Mounting Type         Chassis Mount           Termination Style         Quick Connect - 0.250" (6.3mm)    Report errors?		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesPRDRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current85mACoil Voltage120VACContact FormSPDT (1 Form C)Contact Rating (Current)25ASwitching Voltage600VAC, 125VDC - MaxTurn On Voltage (Max)102 VACTurn Off Voltage (Min)12 VACOperate Time40msRelease Time20msFeaturesInsulation - Class BMounting TypeChassis MountTermination StyleQuick Connect - 0.250" (6.3mm)	Manufacturer Part Number	PRD-5AY1-120
Package         -           Series         PRD           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         85mA           Coil Voltage         120VAC           Contact Form         SPDT (1 Form C)           Contact Rating (Current)         25A           Switching Voltage         600VAC, 125VDC - Max           Turn On Voltage (Max)         102 VAC           Turn Off Voltage (Min)         12 VAC           Operate Time         40ms           Release Time         20ms           Features         Insulation - Class B           Mounting Type         Chassis Mount           Termination Style         Quick Connect - 0.250" (6.3mm)	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package         -           Series         PRD           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         85mA           Coil Voltage         120VAC           Contact Form         SPDT (1 Form C)           Contact Rating (Current)         25A           Switching Voltage         600VAC, 125VDC - Max           Turn On Voltage (Max)         102 VAC           Turn Off Voltage (Min)         12 VAC           Operate Time         40ms           Release Time         20ms           Features         Insulation - Class B           Mounting Type         Chassis Mount           Termination Style         Quick Connect - 0.250" (6.3mm)	Category	Relays
SeriesPRDRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current85mACoil Voltage120VACContact FormSPDT (1 Form C)Contact Rating (Current)25ASwitching Voltage600VAC, 125VDC - MaxTurn On Voltage (Max)102 VACTurn Off Voltage (Min)12 VACOperate Time40msRelease Time20msFeaturesInsulation - Class BMounting TypeChassis MountTermination StyleQuick Connect - 0.250" (6.3mm)		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 85mA Coil Voltage 120VAC Contact Form SPDT (1 Form C) Contact Rating (Current) 25A Switching Voltage 600VAC, 125VDC - Max Turn On Voltage (Max) 102 VAC Turn Off Voltage (Min) 12 VAC Operate Time 40ms Release Time 20ms Features Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Package	-
Coil Type Non Latching Coil Current 85mA  Coil Voltage 120VAC  Contact Form SPDT (1 Form C)  Contact Rating (Current) 25A  Switching Voltage 600VAC, 125VDC - Max  Turn On Voltage (Max) 102 VAC  Turn Off Voltage (Min) 12 VAC  Operate Time 40ms  Release Time 20ms  Features Insulation - Class B  Mounting Type Chassis Mount  Termination Style Quick Connect - 0.250" (6.3mm)	Series	PRD
Coil Current Coil Voltage 120VAC  Contact Form SPDT (1 Form C) Contact Rating (Current) 25A Switching Voltage 600VAC, 125VDC - Max Turn On Voltage (Max) 102 VAC Turn Off Voltage (Min) 12 VAC Operate Time 40ms Release Time 20ms Features Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Relay Type	General Purpose
Coil Voltage 120VAC Contact Form SPDT (1 Form C) Contact Rating (Current) 25A Switching Voltage 600VAC, 125VDC - Max Turn On Voltage (Max) 102 VAC Turn Off Voltage (Min) 12 VAC Operate Time 40ms Release Time 20ms Features Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Coil Type	Non Latching
Contact Form SPDT (1 Form C)  Contact Rating (Current)  25A  Switching Voltage 600VAC, 125VDC - Max  Turn On Voltage (Max)  102 VAC  Turn Off Voltage (Min)  12 VAC  Operate Time 40ms  Release Time 20ms  Release Time 20ms  Features Insulation - Class B  Mounting Type Chassis Mount  Termination Style Quick Connect - 0.250" (6.3mm)	Coil Current	85mA
Contact Rating (Current)  Switching Voltage  600VAC, 125VDC - Max  Turn On Voltage (Max)  102 VAC  Turn Off Voltage (Min)  12 VAC  Operate Time  40ms  Release Time  20ms  Features  Insulation - Class B  Mounting Type  Chassis Mount  Termination Style  Quick Connect - 0.250" (6.3mm)	Coil Voltage	120VAC
Switching Voltage 600VAC, 125VDC - Max  Turn On Voltage (Max) 102 VAC  Turn Off Voltage (Min) 12 VAC  Operate Time 40ms  Release Time 20ms  Features Insulation - Class B  Mounting Type Chassis Mount  Termination Style Quick Connect - 0.250" (6.3mm)	Contact Form	SPDT (1 Form C)
Turn On Voltage (Max)  102 VAC  Turn Off Voltage (Min)  12 VAC  Operate Time  40ms  Release Time  20ms  Features  Insulation - Class B  Mounting Type  Chassis Mount  Termination Style  Quick Connect - 0.250" (6.3mm)	Contact Rating (Current)	25A
Turn Off Voltage (Min)  12 VAC  Operate Time  40ms  Release Time  20ms  Features  Insulation - Class B  Mounting Type  Chassis Mount  Termination Style  Quick Connect - 0.250" (6.3mm)	Switching Voltage	600VAC, 125VDC - Max
Operate Time 40ms  Release Time 20ms  Features Insulation - Class B  Mounting Type Chassis Mount  Termination Style Quick Connect - 0.250" (6.3mm)	Turn On Voltage (Max)	102 VAC
Release Time 20ms  Features Insulation - Class B  Mounting Type Chassis Mount  Termination Style Quick Connect - 0.250" (6.3mm)	Turn Off Voltage (Min)	12 VAC
Features Insulation - Class B  Mounting Type Chassis Mount  Termination Style Quick Connect - 0.250" (6.3mm)	Operate Time	40ms
Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Release Time	20ms
Termination Style Quick Connect - 0.250" (6.3mm)	Features	Insulation - Class B
	Mounting Type	Chassis Mount
Report errors?	Termination Style	Quick Connect - 0.250" (6.3mm)
		Report errors?

#### PRD-5AY1-120 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## PRD-5AY1-120 Payment Methods



















### PRD-5AY1-120 Shipping Methods













If you have any question about PRD-5AY1-120, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com