

#### PRD-7AY0-480 Information



For Reference Only

Part Number PRD-7AY0-480

Manufacturer TE Connectivity Potter & Brumfield Relays

Category Relays

Power Relays, Over 2 Amps

**Description** RELAY GEN PURPOSE DPST 25A 480V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## PRD-7AY0-480 Specifications

Manufacturer Part Number         PRD-7AY0-480           Manufacturer         TE Connectivity Potter & Brumfield Relays           Category         Relays           Power Relays, Over 2 Amps           Package         -           Series         PRD           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         22mA           Coil Voltage         480VAC           Contact Form         DPST (2 Form A)           Contact Rating (Current)         25A           Switching Voltage         600VAC, 125VDC - Max           Turn On Voltage (Max)         408 VAC           Turn Off Voltage (Min)         48 VAC           Operate Time         40ms           Release Time         20ms           Features         Insulation - Class B           Mounting Type         Chassis Mount           Termination Style         Screw Terminal		
CategoryRelaysPackage-SeriesPRDRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current22mACoil Voltage480VACContact FormDPST (2 Form A)Contact Rating (Current)25ASwitching Voltage600VAC, 125VDC - MaxTurn On Voltage (Max)408 VACTurn Off Voltage (Min)48 VACOperate Time40msRelease Time20msFeaturesInsulation - Class BMounting TypeChassis Mount	Manufacturer Part Number	PRD-7AY0-480
Package         -           Series         PRD           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         22mA           Coil Voltage         480VAC           Contact Form         DPST (2 Form A)           Contact Rating (Current)         25A           Switching Voltage         600VAC, 125VDC - Max           Turn On Voltage (Max)         408 VAC           Turn Off Voltage (Min)         48 VAC           Operate Time         40ms           Release Time         20ms           Features         Insulation - Class B           Mounting Type         Chassis Mount	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package-SeriesPRDRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current22mACoil Voltage480VACContact FormDPST (2 Form A)Contact Rating (Current)25ASwitching Voltage600VAC, 125VDC - MaxTurn On Voltage (Max)408 VACTurn Off Voltage (Min)48 VACOperate Time40msRelease Time20msFeaturesInsulation - Class BMounting TypeChassis Mount	Category	Relays
SeriesPRDRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current22mACoil Voltage480VACContact FormDPST (2 Form A)Contact Rating (Current)25ASwitching Voltage600VAC, 125VDC - MaxTurn On Voltage (Max)408 VACTurn Off Voltage (Min)48 VACOperate Time40msRelease Time20msFeaturesInsulation - Class BMounting TypeChassis Mount		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 22mA Coil Voltage 480VAC Contact Form DPST (2 Form A) Contact Rating (Current) 25A Switching Voltage 600VAC, 125VDC - Max Turn On Voltage (Max) 408 VAC Turn Off Voltage (Min) 48 VAC Operate Time 40ms Release Time 20ms Features Insulation - Class B Mounting Type Chassis Mount	Package	-
Coil Type Non Latching Coil Current 22mA Coil Voltage 480VAC Contact Form DPST (2 Form A) Contact Rating (Current) 25A Switching Voltage 600VAC, 125VDC - Max Turn On Voltage (Max) 408 VAC Turn Off Voltage (Min) 48 VAC Operate Time 40ms Release Time 20ms Release Time 20ms Features Insulation - Class B Mounting Type Chassis Mount	Series	PRD
Coil Current 22mA Coil Voltage 480VAC Contact Form DPST (2 Form A) Contact Rating (Current) 25A Switching Voltage 600VAC, 125VDC - Max Turn On Voltage (Max) 408 VAC Turn Off Voltage (Min) 48 VAC Operate Time 40ms Release Time 20ms Features Insulation - Class B Mounting Type Chassis Mount	Relay Type	General Purpose
Coil Voltage 480VAC  Contact Form DPST (2 Form A)  Contact Rating (Current) 25A  Switching Voltage 600VAC, 125VDC - Max  Turn On Voltage (Max) 408 VAC  Turn Off Voltage (Min) 48 VAC  Operate Time 40ms  Release Time 20ms  Features Insulation - Class B  Mounting Type Chassis Mount	Coil Type	Non Latching
Contact Form DPST (2 Form A)  Contact Rating (Current) 25A  Switching Voltage 600VAC, 125VDC - Max  Turn On Voltage (Max) 408 VAC  Turn Off Voltage (Min) 48 VAC  Operate Time 40ms  Release Time 20ms  Features Insulation - Class B  Mounting Type Chassis Mount	Coil Current	22mA
Contact Rating (Current)  Switching Voltage  600VAC, 125VDC - Max  Turn On Voltage (Max)  408 VAC  Turn Off Voltage (Min)  48 VAC  Operate Time  40ms  Release Time  20ms  Features  Insulation - Class B  Mounting Type  Chassis Mount	Coil Voltage	480VAC
Switching Voltage 600VAC, 125VDC - Max  Turn On Voltage (Max) 408 VAC  Turn Off Voltage (Min) 48 VAC  Operate Time 40ms  Release Time 20ms  Features Insulation - Class B  Mounting Type Chassis Mount	Contact Form	DPST (2 Form A)
Turn On Voltage (Max)  408 VAC  Turn Off Voltage (Min)  48 VAC  Operate Time  40ms  Release Time  20ms  Features  Insulation - Class B  Mounting Type  Chassis Mount	Contact Rating (Current)	25A
Turn Off Voltage (Min)  48 VAC  Operate Time  40ms  Release Time  20ms  Features  Insulation - Class B  Mounting Type  Chassis Mount	Switching Voltage	600VAC, 125VDC - Max
Operate Time40msRelease Time20msFeaturesInsulation - Class BMounting TypeChassis Mount	Turn On Voltage (Max)	408 VAC
Release Time 20ms Features Insulation - Class B Mounting Type Chassis Mount	Turn Off Voltage (Min)	48 VAC
Features Insulation - Class B  Mounting Type Chassis Mount	Operate Time	40ms
Mounting Type Chassis Mount	Release Time	20ms
	Features	Insulation - Class B
Termination Style Screw Terminal	Mounting Type	Chassis Mount
	Termination Style	Screw Terminal
Report errors?		Report errors?

#### PRD-7AY0-480 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## PRD-7AY0-480 Payment Methods





















## PRD-7AY0-480 Shipping Methods













If you have any question about PRD-7AY0-480, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com