

PSA.2E.302.CLLC40

PSA.2E.302.CLLC40 Information

Heisener.com	Part Number Manufacturer Category Description Package	PSA.2E.302.CLLC40 LEMO Connectors, Interconnects Circular Connectors RCPT PNL MNT 2POS SLD CUP - For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



PSA.2E.302.CLLC40 Specifications

ManufacturerLEMOCategoryConnectors, InterconnectsCircular ConnectorsPackage-Series2EConnector TypeReceptacle, Female Sockets and Male PinsNumber of Positions2Shell Size - Insert302Shell Size, MIL-Mounting TypeFree Hanging (In-Line); Panel Mount, Bulkhead - Rear Side NutFerminationSolder CupFastening TypePush-Pull, Detent LockIngress ProtectionHe6/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishGoldContact FinishGoldFeaturesShieldedVoltage - Rated-				
CategoryConnectors, InterconnectsCircular ConnectorsPackage-Series2EConnector TypeReceptacle, Female Sockets and Male PinsNumber of Positions2Shell Size - Insert302Shell Size, MIL-Mounting TypeFree Hanging (In-Line); Panel Mount, Bulkhead - Rear Side NutPerminationSolder CupFastening TypePush-Pull, Detent LockDrientationKeyedIngress ProtectionBrass, Chrome PlatedShell Material, FinishGoldFeaturesShieldedVoltage - Rated-Current Rating20A	Manufacturer Part Number	PSA.2E.302.CLLC40		
Circular ConnectorsPackage-Series2EConnector TypeReceptacle, Female Sockets and Male PinsNumber of Positions2Shell Size - Insert302Shell Size, MIL-Mounting TypeFree Hanging (In-Line); Panel Mount, Bulkhead - Rear Side NutFerminationSolder CupFastening TypePush-Pull, Detent LockOrientationKeyedIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating20A	Manufacturer	LEMO		
Package-Series2EConnector TypeReceptacle, Female Sockets and Male PinsNumber of Positions2Shell Size - Insert302Shell Size, MIL-Mounting TypeFree Hanging (In-Line); Panel Mount, Bulkhead - Rear Side NutFerminationSolder CupFastening TypePush-Pull, Detent LockDrientationHeodé - Dust Tight, Water Resistant, WaterproofShell Material, FinishBrass, Chrome PlatedShell Material, FinishGoldFeaturesShieldedVoltage - Rated.Current Rating20A	Category	Connectors, Interconnects		
Series2EConnector TypeReceptacle, Female Sockets and Male PinsNumber of Positions2Shell Size - Insert302Shell Size, MIL-Mounting TypeFree Hanging (In-Line); Panel Mount, Bulkhead - Rear Side NutFerminationSolder CupFastening TypePush-Pull, Detent LockOrientationKeyedIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishBrass, Chrome PlatedContact FinishSoldelFeaturesShieldedVoltage - Rated-Current Rating20A		Circular Connectors		
Connector TypeReceptacle, Female Sockets and Male PinsNumber of Positions2Shell Size - Insert302Shell Size, MIL-Mounting TypeFree Hanging (In-Line); Panel Mount, Bulkhead - Rear Side NutFerminationSolder CupFastening TypePush-Pull, Detent LockOrientationKeyedIngress ProtectionBrass, Chrome PlatedShell Material, FinishGoldFeaturesShieldedVoltage - Rated2Orient Rating2Otage - Rated2Otage - Rated2Otage - Rated2Otage - Rated20A	Package	-		
Number of Positions2Shell Size - Insert302Shell Size, MIL-Mounting TypeFree Hanging (In-Line); Panel Mount, Bulkhead - Rear Side NutFerminationSolder CupFastening TypePush-Pull, Detent LockOrientationKeyedIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating20A	Series	2E		
Shell Size - Insert302Shell Size, MIL-Mounting TypeFree Hanging (In-Line); Panel Mount, Bulkhead - Rear Side NutForminationSolder CupFastening TypePush-Pull, Detent LockOrientationKeyedIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating20A	Connector Type	Receptacle, Female Sockets and Male Pins		
Shell Size, MIL-Mounting TypeFree Hanging (In-Line); Panel Mount, Bulkhead - Rear Side NutFerminationSolder CupFastening TypePush-Pull, Detent LockOrientationKeyedIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating20A	Number of Positions	2		
Mounting TypeFree Hanging (In-Line); Panel Mount, Bulkhead - Rear Side NutFerminationSolder CupFastening TypePush-Pull, Detent LockOrientationKeyedIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Zurrent Rating20A	Shell Size - Insert	302		
TerminationSolder CupFastening TypePush-Pull, Detent LockOrientationKeyedIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating20A	Shell Size, MIL	-		
Fastening TypePush-Pull, Detent LockOrientationKeyedIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating20A	Mounting Type	Free Hanging (In-Line); Panel Mount, Bulkhead - Rear Side Nut		
OrientationKeyedIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating20A	Termination	Solder Cup		
Ingress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating20A	Fastening Type	Push-Pull, Detent Lock		
Shell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating20A	Orientation	Keyed		
Contact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating20A	Ingress Protection	IP66/68 - Dust Tight, Water Resistant, Waterproof		
FeaturesShieldedVoltage - Rated-Current Rating20A	Shell Material, Finish	Brass, Chrome Plated		
Voltage - Rated-Current Rating20A	Contact Finish	Gold		
Current Rating 20A	Features	Shielded		
-	Voltage - Rated	-		
Report errors?	Current Rating	20A		
			Report errors?	

PSA.2E.302.CLLC40 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

PSA.2E.302.CLLC40 Payment Methods



PSA.2E.302.CLLC40 Shipping Methods



If you have any question about PSA.2E.302.CLLC40, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com