

PSA110-115

PSA110-115 Information

in Elo	Part Number Manufacturer Category Description Package	PSA110-115 Phihong USA Power Supplies - External/Internal (Off-Board) AC DC Converters AC/DC CONVERTER 15V 110W - For the pricing/inventory/lead time, please contact us	
For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



PSA110-115 Specifications

Power Supplies - External/Internal (Off-Board) AC DC Converters Package Package Series PSA110 Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Voltage - Solation TFE (Commercial) Voltage - Isolation - Voltage - Isolation - Voltage - Solation - Voltage - Isolation - Voltage - Isolation - Operating Temperature Over Co°C Featu				
Power Supplies - External/Internal (Off-Board) AC DC Converters Package Package Series PSA110 Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Voltage - Solation TFE (Commercial) Voltage - Isolation - Voltage - Isolation - Voltage - Solation - Voltage - Isolation - Voltage - Isolation - Operating Temperature Over Co°C Featu				
AC DC ConvertersPackage-SeriesPSA110TypeOpen FrameNumber of Outputs1Voltage - Input90 ~ 264 VACVoltage - Output 115VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)7APower (Watts)110WApplicationsTE (Commercial)Voltage - Isolation-Efficiency0% C ~ 50°CFeaturesUniversal InputMounting TypeChassis Mount	Manufacturer	Phihong USA		
Package-SeriesPSA110TypeOpen FrameNumber of Outputs1Voltage - Input90 ~ 264 VACVoltage - Output 15VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Voltage - Output 4-Voltage - Output 47APower (Watts)ITE (Commercial)Voltage - Isolation-Efficiency0°C ~ 50°CPourting TypeChasis Mount	Category	Power Supplies - External/Internal (Off-Board)		
YerPSA110TypeOpen FrameNumber of Outputs1Voltage - Input90 ~ 264 VACVoltage - Output 115VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Voltage - Output 4-Power (Watts)110WApplications-Voltage - Isolation-Current - Gupture0%Operating Temperature0°C ~ 50°CFeaturesUniversal InputMounting TypeChasis Mount		AC DC Converters		
TypeOpen FrameNumber of Outputs1Voltage - Input90 ~ 264 VACVoltage - Output 115VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Voltage - Output 4-Power (Wats)7APower (Wats)-Voltage - Isolation-Voltage - Isolation-Poperating Temperature0°C ~ 50°CFeaturesUniversal InputMounting TypeChassis Mount	Package	-		
Number of Outputs1Voltage - Input90 ~ 264 VACVoltage - Output 115VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Voltage - Output 4-Voltage - Output 47APower (Wats)110WApplications-Voltage - Isolation-Efficiency0%Operating Temperature0°C ~ 50°CFeaturesUniversal InputMounting TypeChasis Mount	Series	PSA110		
Voltage - Input90 ~ 264 VACVoltage - Output 115VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)7APower (Watts)110WApplicationsTE (Commercial)Voltage - Isolation-Efficiency70%Operating Temperature0°C ~ 50°CFeaturesUniversal InputMounting TypeChassis Mount	Туре	Open Frame		
Voltage - Output 115VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)7APower (Watts)110WApplicationsITE (Commercial)Voltage - Isolation-Efficiency0%Operating Temperature0°C ~ 50°CFeaturesUniversal InputMounting TypeChassis Mount	Number of Outputs	1		
Voltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)7APower (Watts)110WApplicationsITE (Commercial)Voltage - Isolation-Efficiency70%Operating Temperature0°C ~ 50°CFeaturesUniversal InputMounting TypeChassis Mount	Voltage - Input	90 ~ 264 VAC		
Voltage - Output 3-Voltage - Output 4-Current - Output (Max)7APower (Watts)110WApplicationsITE (Commercial)Voltage - Isolation-Efficiency70%Operating Temperature0°C ~ 50°CFeaturesUniversal InputMounting TypeChassis Mount	Voltage - Output 1	15V		
Voltage - Output 4-Current - Output (Max)7APower (Watts)110WApplicationsITE (Commercial)Voltage - Isolation-Efficiency70%Operating Temperature0°C ~ 50°CFeaturesUniversal InputMounting TypeChassis Mount	Voltage - Output 2	-		
Current - Output (Max)7APower (Watts)110WApplicationsITE (Commercial)Voltage - Isolation-Efficiency70%Operating Temperature0°C ~ 50°CFeaturesUniversal InputMounting TypeChassis Mount	Voltage - Output 3	-		
Power (Watts)110WApplicationsITE (Commercial)Voltage - Isolation-Efficiency70%Operating Temperature0°C ~ 50°CFeaturesUniversal InputMounting TypeChassis Mount	Voltage - Output 4	-		
ApplicationsITE (Commercial)Voltage - Isolation-Efficiency70%Operating Temperature0°C ~ 50°CFeaturesUniversal InputMounting TypeChassis Mount	Current - Output (Max)	7A		
Voltage - Isolation-Efficiency70%Operating Temperature0°C ~ 50°CFeaturesUniversal InputMounting TypeChassis Mount	Power (Watts)	110W		
Efficiency70%Operating Temperature0°C ~ 50°CFeaturesUniversal InputMounting TypeChassis Mount	Applications	ITE (Commercial)		
Operating Temperature0°C ~ 50°CFeaturesUniversal InputMounting TypeChassis Mount	Voltage - Isolation	-		
Features Universal Input Mounting Type Chassis Mount	Efficiency	70%		
Mounting Type Chassis Mount	Operating Temperature	0°C ~ 50°C		
	Features	Universal Input		
Size / Dimension 6.81" L x 3.70" W x 1.70" H (172.7mm x 93.5mm x 43.6mm)	Mounting Type	Chassis Mount		
	Size / Dimension	6.81" L x 3.70" W x 1.70" H (172.7mm x 93.5mm x 43.6mm)		
Report errors ²		Report errors?		

PSA110-115 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about PSA110-115, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com