



PSA15R-060PV-R-C5 Information



For Reference Only

Part Number PSA15R-060PV-R-C5

Manufacturer Phihong USA

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC WALL MOUNT ADAPTER 6V 15W

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PSA15R-060PV-R-C5 Specifications

Manufacturer Part Number PSA15R-060PV-R-C5 Manufacturer Phihong USA Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series PSA15R Region Utilized International Form Wall Mount Input Type Multi-Blade (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 6V Current - Output (Max) 2.5A Power (Watts) 15W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 0.7mm I.D. x 2.5mm O.D. x 10.0mm Size / Dimension 2.82" L x 1.97" W x 1.31" H (71.7mm x 50.0mm x 33.2mm)		
CategoryPower Supplies - External/Internal (Off-Board)AC DC Desktop, Wall AdaptersPackage-SeriesPSA15RRegion UtilizedInternationalFormWall MountInput TypeMulti-Blade (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output6VCurrent - Output (Max)2.5APower (Watts)15WNo Load Power Consumption300mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 0.7mm I.D. x 2.5mm O.D. x 10.0mmSize / Dimension2.82" L x 1.97" W x 1.31" H (71.7mm x 50.0mm x 33.2mm)	Manufacturer Part Number	PSA15R-060PV-R-C5
Package-SeriesPSA15RRegion UtilizedInternationalFormWall MountInput TypeMulti-Blade (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output6VCurrent - Output (Max)2.5APower (Watts)15WNo Load Power Consumption300mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 0.7mm I.D. x 2.5mm O.D. x 10.0mmSize / Dimension2.82" L x 1.97" W x 1.31" H (71.7mm x 50.0mm x 33.2mm)	Manufacturer	Phihong USA
Package-SeriesPSA15RRegion UtilizedInternationalFormWall MountInput TypeMulti-Blade (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output6VCurrent - Output (Max)2.5APower (Watts)15WNo Load Power Consumption300mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 0.7mm I.D. x 2.5mm O.D. x 10.0mmSize / Dimension2.82" L x 1.97" W x 1.31" H (71.7mm x 50.0mm x 33.2mm)	Category	Power Supplies - External/Internal (Off-Board)
SeriesPSA15RRegion UtilizedInternationalFormWall MountInput TypeMulti-Blade (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output6VCurrent - Output (Max)2.5APower (Watts)15WNo Load Power Consumption300mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 0.7mm I.D. x 2.5mm O.D. x 10.0mmSize / Dimension2.82" L x 1.97" W x 1.31" H (71.7mm x 50.0mm x 33.2mm)		AC DC Desktop, Wall Adapters
Region Utilized International Form Wall Mount Input Type Multi-Blade (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 6V Current - Output (Max) 2.5A Power (Watts) 15W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 0.7mm I.D. x 2.5mm O.D. x 10.0mm Size / Dimension 2.82" L x 1.97" W x 1.31" H (71.7mm x 50.0mm x 33.2mm)	Package	-
Form Wall Mount Input Type Multi-Blade (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 6V Current - Output (Max) 2.5A Power (Watts) 15W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 0.7mm I.D. x 2.5mm O.D. x 10.0mm Size / Dimension 2.82" L x 1.97" W x 1.31" H (71.7mm x 50.0mm x 33.2mm)	Series	PSA15R
Input Type Multi-Blade (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 6V Current - Output (Max) 2.5A Power (Watts) 15W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 0.7mm I.D. x 2.5mm O.D. x 10.0mm Size / Dimension 2.82" L x 1.97" W x 1.31" H (71.7mm x 50.0mm x 33.2mm)	Region Utilized	International
Voltage - Input 90 ~ 264 VAC Voltage - Output 6V Current - Output (Max) 2.5A Power (Watts) 15W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 0.7mm I.D. x 2.5mm O.D. x 10.0mm Size / Dimension 2.82" L x 1.97" W x 1.31" H (71.7mm x 50.0mm x 33.2mm)	Form	Wall Mount
Voltage - Output Current - Output (Max) 2.5A Power (Watts) 15W No Load Power Consumption Polarization Polarization Applications ITE (Commercial) Efficiency Level V Operating Temperature O°C ~ 40°C Output Connector Barrel Plug, 0.7mm I.D. x 2.5mm O.D. x 10.0mm Size / Dimension 6V Current - Output (Max) 2.5A Power (Watts) 15W No Load Power Consumption 300mW (Max) Positive Center Positive Center O°C ~ 40°C Output Connector Barrel Plug, 0.7mm I.D. x 2.5mm O.D. x 10.0mm 2.82" L x 1.97" W x 1.31" H (71.7mm x 50.0mm x 33.2mm)	Input Type	Multi-Blade (Sold Separately)
Current - Output (Max) 2.5A Power (Watts) 15W No Load Power Consumption 300mW (Max) Polarization Positive Center ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 0.7mm I.D. x 2.5mm O.D. x 10.0mm Size / Dimension 2.82" L x 1.97" W x 1.31" H (71.7mm x 50.0mm x 33.2mm)	Voltage - Input	90 ~ 264 VAC
Power (Watts) $15W$ No Load Power Consumption $300mW$ (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature $0^{\circ}C \sim 40^{\circ}C$ Output ConnectorBarrel Plug, $0.7mm$ I.D. x $2.5mm$ O.D. x $10.0mm$ Size / Dimension $2.82"$ L x $1.97"$ W x $1.31"$ H $(71.7mm$ x $50.0mm$ x $33.2mm$)	Voltage - Output	6V
No Load Power Consumption 300mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 0.7mm I.D. x 2.5mm O.D. x 10.0mm Size / Dimension 2.82" L x 1.97" W x 1.31" H (71.7mm x 50.0mm x 33.2mm)	Current - Output (Max)	2.5A
Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 0.7mm I.D. x 2.5mm O.D. x 10.0mm Size / Dimension 2.82" L x 1.97" W x 1.31" H (71.7mm x 50.0mm x 33.2mm)	Power (Watts)	15W
Applications ITE (Commercial) Efficiency Level V Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 0.7mm I.D. x 2.5mm O.D. x 10.0mm Size / Dimension $2.82^{\circ}\text{L} \times 1.97^{\circ}\text{W} \times 1.31^{\circ}\text{H} (71.7\text{mm} \times 50.0\text{mm} \times 33.2\text{mm})$	No Load Power Consumption	300mW (Max)
Efficiency Level V Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 0.7mm I.D. x 2.5mm O.D. x 10.0mm Size / Dimension $2.82^{\circ}\text{L} \text{ x } 1.97^{\circ}\text{ W x } 1.31^{\circ}\text{H } (71.7\text{mm x } 50.0\text{mm x } 33.2\text{mm})$	Polarization	Positive Center
Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 0.7mm I.D. x 2.5mm O.D. x 10.0mm Size / Dimension $2.82^{\circ}\text{L} \times 1.97^{\circ}\text{W} \times 1.31^{\circ}\text{H} (71.7\text{mm} \times 50.0\text{mm} \times 33.2\text{mm})$	Applications	ITE (Commercial)
Output Connector Barrel Plug, 0.7mm I.D. x 2.5mm O.D. x 10.0mm Size / Dimension 2.82" L x 1.97" W x 1.31" H (71.7mm x 50.0mm x 33.2mm)	Efficiency	Level V
Size / Dimension 2.82" L x 1.97" W x 1.31" H (71.7mm x 50.0mm x 33.2mm)	Operating Temperature	0°C ~ 40°C
	Output Connector	Barrel Plug, 0.7mm I.D. x 2.5mm O.D. x 10.0mm
Report errors?	Size / Dimension	2.82" L x 1.97" W x 1.31" H (71.7mm x 50.0mm x 33.2mm)
		Report errors?

PSA15R-060PV-R-C5 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PSA15R-060PV-R-C5 Payment Methods



















PSA15R-060PV-R-C5 Shipping Methods













If you have any question about PSA15R-060PV-R-C5, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com