

PSA15R-060PV-R-CN1

PSA15R-060PV-R-CN1 Information

w/w.helsener.com

For Reference Only

Part Number PSA15R-060PV-R-CN1

Manufacturer Phihong USA

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC WALL MOUNT ADAPTER 6V 15W

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PSA15R-060PV-R-CN1 Specifications

Manufacturer Part Number PSA15R-060PV-R-CN1 Manufacturer Phihong USA Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series PSA15R Region Utilized International Form Wall Mount Input Type Multi-Blade (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 6V Current - Output (Max) 2.5A Power (Watts) 15W No Load Power Consumption 300mW (Max) Polarization Negative Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension 2.82" L x 1.97" W x 1.31" H (71.7mm x 50.0mm x 33.2mm) Report errors?		
CategoryPower Supplies - External/Internal (Off-Board)AC DC Desktop, Wall AdaptersPackage-SeriesPSA15RRegion UtilizedInternationalFormWall MountInput TypeMulti-Blade (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output6VCurrent - Output (Max)2.5APower (Watts)15WNo Load Power Consumption300mW (Max)PolarizationNegative CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mmSize / Dimension2.82" L x 1.97" W x 1.31" H (71.7mm x 50.0mm x 33.2mm)	Manufacturer Part Number	PSA15R-060PV-R-CN1
AC DC Desktop, Wall Adapters Package - Series PSA15R Region Utilized International Form Wall Mount Input Type Multi-Blade (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 6V Current - Output (Max) 2.5A Power (Watts) 15W No Load Power Consumption 300mW (Max) Polarization Negative Center Applications ITE (Commercial) Efficiency Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension AC DC Desktop, Wall Adapters PSA15R Adapters PSA15R PSA15R PSA15R PSA15R Adapters PSA1	Manufacturer	Phihong USA
Package-SeriesPSA15RRegion UtilizedInternationalFormWall MountInput TypeMulti-Blade (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output6VCurrent - Output (Max)2.5APower (Watts)15WNo Load Power Consumption300mW (Max)PolarizationNegative CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mmSize / Dimension2.82" L x 1.97" W x 1.31" H (71.7mm x 50.0mm x 33.2mm)	Category	Power Supplies - External/Internal (Off-Board)
SeriesPSA15RRegion UtilizedInternationalFormWall MountInput TypeMulti-Blade (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output6VCurrent - Output (Max)2.5APower (Watts)15WNo Load Power Consumption300mW (Max)PolarizationNegative CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mmSize / Dimension2.82" L x 1.97" W x 1.31" H (71.7mm x 50.0mm x 33.2mm)		AC DC Desktop, Wall Adapters
Region Utilized Form Wall Mount Input Type Multi-Blade (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 6V Current - Output (Max) Power (Watts) No Load Power Consumption Negative Center Applications ITE (Commercial) Efficiency Derating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension International Multi-Blade (Sold Separately) Apulti-Blade (Sold Separately) 80 Wall Mount 6V Current - Output (Max) 51 Size / Dimension International 6V Apulti-Blade (Sold Separately) 6V Current - Output (Max) 15W 15W 15W 15W 15W 15W 15W 15	Package	-
Form Wall Mount Input Type Multi-Blade (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 6V Current - Output (Max) 2.5A Power (Watts) 15W No Load Power Consumption 300mW (Max) Polarization Negative Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mm x 33.2mm) Size / Dimension 2.82" L x 1.97" W x 1.31" H (71.7mm x 50.0mm x 33.2mm)	Series	PSA15R
Input Type Multi-Blade (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 6V Current - Output (Max) 2.5A Power (Watts) 15W No Load Power Consumption 300mW (Max) Polarization Negative Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension 2.82" L x 1.97" W x 1.31" H (71.7mm x 50.0mm x 33.2mm)	Region Utilized	International
Voltage - Input 90 ~ 264 VAC Voltage - Output 6V Current - Output (Max) 2.5A Power (Watts) 15W No Load Power Consumption 300mW (Max) Polarization Negative Center Applications ITE (Commercial) Efficiency Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension 2.82" L x 1.97" W x 1.31" H (71.7mm x 50.0mm x 33.2mm)	Form	Wall Mount
Voltage - Output Current - Output (Max) 2.5A Power (Watts) 15W No Load Power Consumption 300mW (Max) Polarization Negative Center Applications ITE (Commercial) Efficiency Uevel V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension 2.82" L x 1.97" W x 1.31" H (71.7mm x 50.0mm x 33.2mm)	Input Type	Multi-Blade (Sold Separately)
Current - Output (Max) 2.5A Power (Watts) 15W No Load Power Consumption Negative Center Applications ITE (Commercial) Efficiency Level V Operating Temperature O°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension 2.82" L x 1.97" W x 1.31" H (71.7mm x 50.0mm x 33.2mm)	Voltage - Input	90 ~ 264 VAC
Power (Watts) 15W No Load Power Consumption 300mW (Max) Polarization Negative Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension 2.82" L x 1.97" W x 1.31" H (71.7mm x 50.0mm x 33.2mm)	Voltage - Output	6V
No Load Power Consumption 300mW (Max) Polarization Negative Center Applications ITE (Commercial) Efficiency Level V Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension 2.82" L x 1.97" W x 1.31" H (71.7mm x 50.0mm x 33.2mm)	Current - Output (Max)	2.5A
Polarization Negative Center Applications ITE (Commercial) Efficiency Level V Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension $2.82^{\circ}\text{L} \times 1.97^{\circ}\text{W} \times 1.31^{\circ}\text{H} (71.7\text{mm} \times 50.0\text{mm} \times 33.2\text{mm})$	Power (Watts)	15W
Applications ITE (Commercial) Efficiency Level V Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension $2.82^{\circ}\text{L x } 1.97^{\circ}\text{W x } 1.31^{\circ}\text{H } (71.7\text{mm x } 50.0\text{mm x } 33.2\text{mm})$	No Load Power Consumption	300mW (Max)
Efficiency Level V Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension $2.82^{\circ}\text{L} \times 1.97^{\circ}\text{W} \times 1.31^{\circ}\text{H} (71.7\text{mm} \times 50.0\text{mm} \times 33.2\text{mm})$	Polarization	Negative Center
Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension $2.82^{\circ}\text{L} \times 1.97^{\circ}\text{W} \times 1.31^{\circ}\text{H} (71.7\text{mm} \times 50.0\text{mm} \times 33.2\text{mm})$	Applications	ITE (Commercial)
Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension 2.82" L x 1.97" W x 1.31" H (71.7mm x 50.0mm x 33.2mm)	Efficiency	Level V
Size / Dimension 2.82" L x 1.97" W x 1.31" H (71.7mm x 50.0mm x 33.2mm)	Operating Temperature	0°C ~ 40°C
	Output Connector	Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mm
Report errors?	Size / Dimension	2.82" L x 1.97" W x 1.31" H (71.7mm x 50.0mm x 33.2mm)
		Report errors?

PSA15R-060PV-R-CN1 Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PSA15R-060PV-R-CN1 Payment Methods



















PSA15R-060PV-R-CN1 Shipping Methods













If you have any question about PSA15R-060PV-R-CN1, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com