



PSA15R-060PV Information



For Reference Only

Part Number PSA15R-060PV Manufacturer Phihong USA

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC WALL MOUNT ADAPTER 6V 15W

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PSA15R-060PV Specifications

Manufacturer Part NumberPSA15R-060PVManufacturerPhihong USACategoryPower Supplies - External/Internal (Off-Board)AC DC Desktop, Wall AdaptersPackage-SeriesPSA15R-VRegion UtilizedInternationalFormWall MountInput TypeMulti-Blade (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output6VCurrent - Output (Max)2.5APower (Watts)15WNo Load Power Consumption300mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mmSize / Dimension2.82" L x 1.97" W x 1.31" H (71.7mm x 50.0mm x 33.2mm)		
Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series PSA15R-V Region Utilized International Form Wall Mount Input Type Multi-Blade (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 6V Current - Output (Max) 2.5A Power (Watts) 15W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension 2.82" L x 1.97" W x 1.31" H (71.7mm x 50.0mm x 33.2mm)	Manufacturer Part Number	PSA15R-060PV
AC DC Desktop, Wall Adapters Package - Series PSA15R-V Region Utilized International Form Wall Mount Input Type Multi-Blade (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 6V Current - Output (Max) 2.5A Power (Watts) No Load Power Consumption 300mW (Max) Polarization Applications ITE (Commercial) Efficiency Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension AC DC Desktop, Wall Adapters PSA15R-V Adapter PSA15R-V Nall Adapters 1	Manufacturer	Phihong USA
Package-SeriesPSA15R-VRegion UtilizedInternationalFormWall MountInput TypeMulti-Blade (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output6VCurrent - Output (Max)2.5APower (Watts)15WNo Load Power Consumption300mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mmSize / Dimension2.82" L x 1.97" W x 1.31" H (71.7mm x 50.0mm x 33.2mm)	Category	Power Supplies - External/Internal (Off-Board)
SeriesPSA15R-VRegion UtilizedInternationalFormWall MountInput TypeMulti-Blade (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output6VCurrent - Output (Max)2.5APower (Watts)15WNo Load Power Consumption300mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mmSize / Dimension2.82" L x 1.97" W x 1.31" H (71.7mm x 50.0mm x 33.2mm)		AC DC Desktop, Wall Adapters
Region Utilized International Form Wall Mount Input Type Multi-Blade (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 6V Current - Output (Max) 2.5A Power (Watts) 15W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension 2.82" L x 1.97" W x 1.31" H (71.7mm x 50.0mm x 33.2mm)	Package	-
Form Wall Mount Input Type Multi-Blade (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 6V Current - Output (Max) 2.5A Power (Watts) 15W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension 2.82" L x 1.97" W x 1.31" H (71.7mm x 50.0mm x 33.2mm)	Series	PSA15R-V
Input Type Multi-Blade (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 6V Current - Output (Max) 2.5A Power (Watts) 15W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension 2.82" L x 1.97" W x 1.31" H (71.7mm x 50.0mm x 33.2mm)	Region Utilized	International
Voltage - Input 90 ~ 264 VAC Voltage - Output 6V Current - Output (Max) 2.5A Power (Watts) 15W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension 2.82" L x 1.97" W x 1.31" H (71.7mm x 50.0mm x 33.2mm)	Form	Wall Mount
Voltage - Output Current - Output (Max) 2.5A Power (Watts) 15W No Load Power Consumption Polarization Polarization Applications ITE (Commercial) Efficiency Operating Temperature O°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension 6V Current - Output (Max) 2.5A Power (Watts) 15W No Load Power Consumption 300mW (Max) Positive Center Positive Center O"C ~ 40°C Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension 2.82" L x 1.97" W x 1.31" H (71.7mm x 50.0mm x 33.2mm)	Input Type	Multi-Blade (Sold Separately)
Current - Output (Max) 2.5A Power (Watts) 15W No Load Power Consumption 300mW (Max) Polarization Positive Center ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension 2.82" L x 1.97" W x 1.31" H (71.7mm x 50.0mm x 33.2mm)	Voltage - Input	90 ~ 264 VAC
Power (Watts) 15W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension 2.82" L x 1.97" W x 1.31" H (71.7mm x 50.0mm x 33.2mm)	Voltage - Output	6V
No Load Power Consumption 300mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension 2.82" L x 1.97" W x 1.31" H (71.7mm x 50.0mm x 33.2mm)	Current - Output (Max)	2.5A
Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension $2.82^{\circ}\text{L} \times 1.97^{\circ}\text{W} \times 1.31^{\circ}\text{H} (71.7\text{mm} \times 50.0\text{mm} \times 33.2\text{mm})$	Power (Watts)	15W
Applications ITE (Commercial) Efficiency Level V Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension $2.82^{\circ}\text{L} \times 1.97^{\circ}\text{W} \times 1.31^{\circ}\text{H} (71.7\text{mm} \times 50.0\text{mm} \times 33.2\text{mm})$	No Load Power Consumption	300mW (Max)
Efficiency Level V Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension $2.82^{\circ}\text{L} \times 1.97^{\circ}\text{W} \times 1.31^{\circ}\text{H} (71.7\text{mm} \times 50.0\text{mm} \times 33.2\text{mm})$	Polarization	Positive Center
Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension $2.82^{\circ}\text{L} \times 1.97^{\circ}\text{W} \times 1.31^{\circ}\text{H} (71.7\text{mm} \times 50.0\text{mm} \times 33.2\text{mm})$	Applications	ITE (Commercial)
Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mm Size / Dimension 2.82" L x 1.97" W x 1.31" H (71.7mm x 50.0mm x 33.2mm)	Efficiency	Level V
Size / Dimension 2.82" L x 1.97" W x 1.31" H (71.7mm x 50.0mm x 33.2mm)	Operating Temperature	0°C ~ 40°C
	Output Connector	Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 10.0mm
Report errors?	Size / Dimension	2.82" L x 1.97" W x 1.31" H (71.7mm x 50.0mm x 33.2mm)
		Report errors?

PSA15R-060PV Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PSA15R-060PV Payment Methods



















PSA15R-060PV Shipping Methods













If you have any question about PSA15R-060PV, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com