

# PSA15R-120PV-R-CN4

#### PSA15R-120PV-R-CN4 Information



For Reference Only

Part Number PSA15R-120PV-R-CN4

Manufacturer Phihong USA

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

**Description** AC/DC WALL MOUNT ADAPTER 12V 15W

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## PSA15R-120PV-R-CN4 Specifications

Manufacturer Part Number         PSA15R-120PV-R-CN4           Manufacturer         Phihong USA           Category         Power Supplies - External/Internal (Off-Board)           AC DC Desktop, Wall Adapters           Package         -           Series         PSA15R           Region Utilized         International           Form         Wall Mount           Input Type         Multi-Blade (Sold Separately)           Voltage - Input         90 ~ 264 VAC           Voltage - Output         12V           Current - Output (Max)         1.25A           Power (Watts)         15W           No Load Power Consumption         300mW (Max)           Polarization         Negative Center           Applications         ITE (Commercial)           Efficiency         Level V           Operating Temperature         0°C ~ 40°C           Output Connector         Barrel Plug, 1.35mm I.D. x 3.5mm O.D. x 10.0mm           Size / Dimension         2.82" L x 1.97" W x 1.31" H (71.7mm x 50.0mm x 33.2mm)    Report errors?		
Category         Power Supplies - External/Internal (Off-Board)           AC DC Desktop, Wall Adapters           Package         -           Series         PSA15R           Region Utilized         International           Form         Wall Mount           Input Type         Multi-Blade (Sold Separately)           Voltage - Input         90 ~ 264 VAC           Voltage - Output         12V           Current - Output (Max)         1.25A           Power (Watts)         15W           No Load Power Consumption         300mW (Max)           Polarization         Negative Center           Applications         ITE (Commercial)           Efficiency         Level V           Operating Temperature         0°C ~ 40°C           Output Connector         Barrel Plug, 1.35mm I.D. x 3.5mm O.D. x 10.0mm           Size / Dimension         2.82" L x 1.97" W x 1.31" H (71.7mm x 50.0mm x 33.2mm)	Manufacturer Part Number	PSA15R-120PV-R-CN4
AC DC Desktop, Wall Adapters  Package - Series PSA15R Region Utilized International Form Wall Mount Input Type Multi-Blade (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 1.25A Power (Watts) 15W No Load Power Consumption 300mW (Max) Polarization Negative Center Applications ITE (Commercial) Efficiency Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 1.35mm I.D. x 3.5mm O.D. x 10.0mm Size / Dimension  AC DC Desktop, Wall Adapters PSA15R  Adapters PSA15R  POR Desktop, Wall Adapters PSA15R  PSA	Manufacturer	Phihong USA
Package Series PSA15R Region Utilized International Form Wall Mount Input Type Multi-Blade (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 1.25A Power (Watts) No Load Power Consumption 300mW (Max) Polarization Negative Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 1.35mm I.D. x 3.5mm O.D. x 10.0mm Size / Dimension 2.82" L x 1.97" W x 1.31" H (71.7mm x 50.0mm x 33.2mm)	Category	Power Supplies - External/Internal (Off-Board)
SeriesPSA15RRegion UtilizedInternationalFormWall MountInput TypeMulti-Blade (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output12VCurrent - Output (Max)1.25APower (Watts)15WNo Load Power Consumption300mW (Max)PolarizationNegative CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 1.35mm I.D. x 3.5mm O.D. x 10.0mmSize / Dimension2.82" L x 1.97" W x 1.31" H (71.7mm x 50.0mm x 33.2mm)		AC DC Desktop, Wall Adapters
Region Utilized International Form Wall Mount Input Type Multi-Blade (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 1.25A Power (Watts) 15W No Load Power Consumption 300mW (Max) Polarization Negative Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 1.35mm I.D. x 3.5mm O.D. x 10.0mm Size / Dimension 2.82" L x 1.97" W x 1.31" H (71.7mm x 50.0mm x 33.2mm)	Package	-
Form Wall Mount Input Type Multi-Blade (Sold Separately)  Voltage - Input 90 ~ 264 VAC  Voltage - Output 12V  Current - Output (Max) 1.25A  Power (Watts) 15W  No Load Power Consumption 300mW (Max)  Polarization Negative Center  Applications ITE (Commercial)  Efficiency Level V  Operating Temperature 0°C ~ 40°C  Output Connector Barrel Plug, 1.35mm I.D. x 3.5mm O.D. x 10.0mm  Size / Dimension 2.82" L x 1.97" W x 1.31" H (71.7mm x 50.0mm x 33.2mm)	Series	PSA15R
Input Type Multi-Blade (Sold Separately)  Voltage - Input 90 ~ 264 VAC  Voltage - Output 12V  Current - Output (Max) 1.25A  Power (Watts) 15W  No Load Power Consumption 300mW (Max)  Polarization Negative Center  Applications ITE (Commercial)  Efficiency Level V  Operating Temperature 0°C ~ 40°C  Output Connector Barrel Plug, 1.35mm I.D. x 3.5mm O.D. x 10.0mm  Size / Dimension 2.82" L x 1.97" W x 1.31" H (71.7mm x 50.0mm x 33.2mm)	Region Utilized	International
Voltage - Input  90 ~ 264 VAC  Voltage - Output  12V  Current - Output (Max)  1.25A  Power (Watts)  15W  No Load Power Consumption  300mW (Max)  Polarization  Negative Center  Applications  ITE (Commercial)  Efficiency  Operating Temperature  0°C ~ 40°C  Output Connector  Barrel Plug, 1.35mm I.D. x 3.5mm O.D. x 10.0mm  Size / Dimension  2.82" L x 1.97" W x 1.31" H (71.7mm x 50.0mm x 33.2mm)	Form	Wall Mount
Voltage - Output Current - Output (Max)  1.25A  Power (Watts)  1.5W  No Load Power Consumption  Negative Center Applications  ITE (Commercial)  Efficiency  Operating Temperature  O°C ~ 40°C  Output Connector  Barrel Plug, 1.35mm I.D. x 3.5mm O.D. x 10.0mm  Size / Dimension  12V  12V  12V  12V  12V  12V  12V  12	Input Type	Multi-Blade (Sold Separately)
Current - Output (Max)  1.25A  Power (Watts)  15W  No Load Power Consumption  Negative Center  Applications  ITE (Commercial)  Efficiency  Level V  Operating Temperature  O°C ~ 40°C  Output Connector  Barrel Plug, 1.35mm I.D. x 3.5mm O.D. x 10.0mm  Size / Dimension  1.25A  1.25A  1.25M  1	Voltage - Input	90 ~ 264 VAC
Power (Watts)  15W  No Load Power Consumption  300mW (Max)  Polarization  Negative Center  Applications  ITE (Commercial)  Efficiency  Level V  Operating Temperature  0°C ~ 40°C  Output Connector  Barrel Plug, 1.35mm I.D. x 3.5mm O.D. x 10.0mm  Size / Dimension  2.82" L x 1.97" W x 1.31" H (71.7mm x 50.0mm x 33.2mm)	Voltage - Output	12V
No Load Power Consumption 300mW (Max)  Polarization Negative Center  Applications ITE (Commercial)  Efficiency Level V  Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 1.35mm I.D. x 3.5mm O.D. x 10.0mm  Size / Dimension 2.82" L x 1.97" W x 1.31" H (71.7mm x 50.0mm x 33.2mm)	Current - Output (Max)	1.25A
Polarization Negative Center  Applications ITE (Commercial)  Efficiency Level V  Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 1.35mm I.D. x 3.5mm O.D. x 10.0mm  Size / Dimension $2.82^{\circ}\text{L} \times 1.97^{\circ}\text{W} \times 1.31^{\circ}\text{H} (71.7\text{mm} \times 50.0\text{mm} \times 33.2\text{mm})$	Power (Watts)	15W
Applications ITE (Commercial)  Efficiency Level V  Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 1.35mm I.D. x 3.5mm O.D. x 10.0mm  Size / Dimension $2.82^{\circ}\text{L} \times 1.97^{\circ}\text{W} \times 1.31^{\circ}\text{H} (71.7\text{mm} \times 50.0\text{mm} \times 33.2\text{mm})$	No Load Power Consumption	300mW (Max)
Efficiency Level V  Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 1.35mm I.D. x 3.5mm O.D. x 10.0mm  Size / Dimension $2.82^{\circ}\text{L} \text{ x } 1.97^{\circ}\text{ W x } 1.31^{\circ}\text{ H } (71.7\text{mm x } 50.0\text{mm x } 33.2\text{mm})$	Polarization	Negative Center
Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 1.35mm I.D. x 3.5mm O.D. x 10.0mm Size / Dimension $2.82^{\circ}\text{L} \times 1.97^{\circ}\text{W} \times 1.31^{\circ}\text{H} (71.7\text{mm} \times 50.0\text{mm} \times 33.2\text{mm})$	Applications	ITE (Commercial)
Output Connector         Barrel Plug, 1.35mm I.D. x 3.5mm O.D. x 10.0mm           Size / Dimension         2.82" L x 1.97" W x 1.31" H (71.7mm x 50.0mm x 33.2mm)	Efficiency	Level V
Size / Dimension 2.82" L x 1.97" W x 1.31" H (71.7mm x 50.0mm x 33.2mm)	Operating Temperature	0°C ~ 40°C
	Output Connector	Barrel Plug, 1.35mm I.D. x 3.5mm O.D. x 10.0mm
Report errors?	Size / Dimension	2.82" L x 1.97" W x 1.31" H (71.7mm x 50.0mm x 33.2mm)
		Report errors?

### PSA15R-120PV-R-CN4 Guarantees



#### **Ouality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### PSA15R-120PV-R-CN4 Payment Methods



















## PSA15R-120PV-R-CN4 Shipping Methods













If you have any question about PSA15R-120PV-R-CN4, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com