

### **PSA45-150 Information**

Heisener.com

Part Number PSA45-150 Manufacturer Phihong USA

Category Power Supplies - External/Internal (Off-Board)

**AC DC Converters** 

**Description** AC/DC CONVERTER 15V 45W

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **PSA45-150 Specifications**

Manufacturer Part Number         PSA45-150           Manufacturer         Phihong USA           Category         Power Supplies - External/Internal (Off-Board)           Rackage         -           Series         PSA45           Type         Open Frame           Number of Outputs         1           Voltage - Input         90 ~ 264 VAC           Voltage - Output 1         15V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         4A           Power (Watts)         45W (60W Forced Air)           Applications         ITE (Commercial)           Voltage - Isolation         1.5kV (1500V)           Efficiency         70%           Operating Temperature         0°C ~ 50°C           Features         Universal Input           Mounting Type         Chassis Mount           Size / Dimension         5.00" L x 3.00" W x 1.20" H (127.0mm x 76.2mm x 30.0mm)	-	
Category         Power Supplies - External/Internal (Off-Board)           AC DC Converters           Package         -           Series         PSA45           Type         Open Frame           Number of Outputs         1           Voltage - Input         90 ~ 264 VAC           Voltage - Output 1         15V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         4A           Power (Watts)         45W (60W Forced Air)           Applications         ITE (Commercial)           Voltage - Isolation         1.5kV (1500V)           Efficiency         70%           Operating Temperature         0°C ~ 50°C           Features         Universal Input           Mounting Type         Chassis Mount           Size / Dimension         5.00" L x 3.00" W x 1.20" H (127.0mm x 76.2mm x 30.0mm)	Manufacturer Part Number	PSA45-150
Package         -           Series         PSA45           Type         Open Frame           Number of Outputs         1           Voltage - Input         90 ~ 264 VAC           Voltage - Output 1         15V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         4A           Power (Watts)         45W (60W Forced Air)           Applications         ITE (Commercial)           Voltage - Isolation         1.5kV (1500V)           Efficiency         70%           Operating Temperature         0°C ~ 50°C           Features         Universal Input           Mounting Type         Chassis Mount           Size / Dimension         5.00" L x 3.00" W x 1.20" H (127.0mm x 76.2mm x 30.0mm)	Manufacturer	Phihong USA
Package         -           Series         PSA45           Type         Open Frame           Number of Outputs         1           Voltage - Input         90 ~ 264 VAC           Voltage - Output 1         15V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         4A           Power (Watts)         45W (60W Forced Air)           Applications         ITE (Commercial)           Voltage - Isolation         1.5kV (1500V)           Efficiency         70%           Operating Temperature         0°C ~ 50°C           Features         Universal Input           Mounting Type         Chassis Mount           Size / Dimension         5.00" L x 3.00" W x 1.20" H (127.0mm x 76.2mm x 30.0mm)	Category	Power Supplies - External/Internal (Off-Board)
Series         PSA45           Type         Open Frame           Number of Outputs         1           Voltage - Input         90 ~ 264 VAC           Voltage - Output 1         15V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         4A           Power (Watts)         45W (60W Forced Air)           Applications         ITE (Commercial)           Voltage - Isolation         1.5kV (1500V)           Efficiency         70%           Operating Temperature         0°C ~ 50°C           Features         Universal Input           Mounting Type         Chassis Mount           Size / Dimension         5.00" L x 3.00" W x 1.20" H (127.0mm x 76.2mm x 30.0mm)		AC DC Converters
Type         Open Frame           Number of Outputs         1           Voltage - Input         90 ~ 264 VAC           Voltage - Output 1         15V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         4A           Power (Watts)         45W (60W Forced Air)           Applications         ITE (Commercial)           Voltage - Isolation         1.5kV (1500V)           Efficiency         70%           Operating Temperature         0°C ~ 50°C           Features         Universal Input           Mounting Type         Chassis Mount           Size / Dimension         5.00" L x 3.00" W x 1.20" H (127.0mm x 76.2mm x 30.0mm)	Package	-
Number of Outputs         1           Voltage - Input         90 ~ 264 VAC           Voltage - Output 1         15V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         4A           Power (Watts)         45W (60W Forced Air)           Applications         ITE (Commercial)           Voltage - Isolation         1.5kV (1500V)           Efficiency         70%           Operating Temperature         0°C ~ 50°C           Features         Universal Input           Mounting Type         Chassis Mount           Size / Dimension         5.00" L x 3.00" W x 1.20" H (127.0mm x 76.2mm x 30.0mm)	Series	PSA45
Voltage - Input90 ~ 264 VACVoltage - Output 115VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)4APower (Watts)45W (60W Forced Air)ApplicationsITE (Commercial)Voltage - Isolation1.5kV (1500V)Efficiency70%Operating Temperature0°C ~ 50°CFeaturesUniversal InputMounting TypeChassis MountSize / Dimension5.00" L x 3.00" W x 1.20" H (127.0mm x 76.2mm x 30.0mm)	Туре	Open Frame
Voltage - Output 1  Voltage - Output 2  - Voltage - Output 3  Voltage - Output 4  - Current - Output (Max)  Applications  ITE (Commercial)  Voltage - Isolation  I.5kV (1500V)  Efficiency  Operating Temperature  O°C ~ 50°C  Features  Universal Input  Mounting Type  Size / Dimension  15V  Output (Max)  -  -  -  -  -  -  -  -  -  -  -  -  -	Number of Outputs	1
Voltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)4APower (Watts)45W (60W Forced Air)ApplicationsITE (Commercial)Voltage - Isolation1.5kV (1500V)Efficiency70%Operating Temperature0°C ~ 50°CFeaturesUniversal InputMounting TypeChassis MountSize / Dimension5.00" L x 3.00" W x 1.20" H (127.0mm x 76.2mm x 30.0mm)	Voltage - Input	90 ~ 264 VAC
Voltage - Output 3  Voltage - Output 4  - Current - Output (Max)  Applications  ITE (Commercial)  Voltage - Isolation  1.5kV (1500V)  Efficiency  Operating Temperature  O°C ~ 50°C  Features  Universal Input  Mounting Type  Size / Dimension  - Current - Output (Max)  - Chassis Mount  - Current - Output (Max)  - Current - Output (Max)  - Chassis Mount  - Chassis	Voltage - Output 1	15V
Voltage - Output 4  Current - Output (Max)  4A  Power (Watts)  45W (60W Forced Air)  Applications  ITE (Commercial)  Voltage - Isolation  1.5kV (1500V)  Efficiency  70%  Operating Temperature  0°C ~ 50°C  Features  Universal Input  Mounting Type  Chassis Mount  Size / Dimension	Voltage - Output 2	-
Current - Output (Max)  Power (Watts)  45W (60W Forced Air)  Applications  ITE (Commercial)  Voltage - Isolation  1.5kV (1500V)  Efficiency  70%  Operating Temperature  0°C ~ 50°C  Features  Universal Input  Mounting Type  Chassis Mount  Size / Dimension  4A  4A  4B  4B  4B  4B  4B  4B  4B  4B	Voltage - Output 3	-
Power (Watts) 45W (60W Forced Air)  Applications ITE (Commercial)  Voltage - Isolation 1.5kV (1500V)  Efficiency 70%  Operating Temperature 0°C ~ 50°C  Features Universal Input  Mounting Type Chassis Mount  Size / Dimension 5.00" L x 3.00" W x 1.20" H (127.0mm x 76.2mm x 30.0mm)	Voltage - Output 4	-
ApplicationsITE (Commercial)Voltage - Isolation $1.5 \text{kV} (1500 \text{V})$ Efficiency $70\%$ Operating Temperature $0^{\circ}\text{C} \sim 50^{\circ}\text{C}$ FeaturesUniversal InputMounting TypeChassis MountSize / Dimension $5.00$ " L x $3.00$ " W x $1.20$ " H $(127.0 \text{mm x } 76.2 \text{mm x } 30.0 \text{mm})$	Current - Output (Max)	4A
Voltage - Isolation $1.5 \text{kV} (1500 \text{V})$ Efficiency $70\%$ Operating Temperature $0^{\circ}\text{C} \sim 50^{\circ}\text{C}$ FeaturesUniversal InputMounting TypeChassis MountSize / Dimension $5.00$ " L x $3.00$ " W x $1.20$ " H $(127.0 \text{mm} \times 76.2 \text{mm} \times 30.0 \text{mm})$	Power (Watts)	45W (60W Forced Air)
Efficiency 70%   Operating Temperature $0^{\circ}\text{C} \sim 50^{\circ}\text{C}$ Features Universal Input   Mounting Type Chassis Mount   Size / Dimension $5.00^{\circ}\text{L x } 3.00^{\circ}\text{W x } 1.20^{\circ}\text{H } (127.0\text{mm x } 76.2\text{mm x } 30.0\text{mm})$	Applications	ITE (Commercial)
Operating Temperature $0^{\circ}\text{C} \sim 50^{\circ}\text{C}$ FeaturesUniversal InputMounting TypeChassis MountSize / Dimension $5.00$ " L x $3.00$ " W x $1.20$ " H ( $127.0$ mm x $76.2$ mm x $30.0$ mm)	Voltage - Isolation	1.5kV (1500V)
Features Universal Input  Mounting Type Chassis Mount  Size / Dimension 5.00" L x 3.00" W x 1.20" H (127.0mm x 76.2mm x 30.0mm)	Efficiency	70%
Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.20" H (127.0mm x 76.2mm x 30.0mm)	Operating Temperature	0°C ~ 50°C
Size / Dimension 5.00" L x 3.00" W x 1.20" H (127.0mm x 76.2mm x 30.0mm)	Features	Universal Input
	Mounting Type	Chassis Mount
Report errors?	Size / Dimension	5.00" L x 3.00" W x 1.20" H (127.0mm x 76.2mm x 30.0mm)
		Report errors?

### PSA45-150 Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# **PSA45-150 Payment Methods**


































If you have any question about PSA45-150, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com